



## Leisure Battery Charger

Our battery chargers are high quality UK manufactured intelligent systems. Designed for many applications including Leisure, fire & security, medical, automotive, mobility, industrial, golf, standby or cyclic.

### Product Features

- Controlled multistage charging
- Charges AGM, Flooded batteries
- Ability to charge batteries drained to a low voltage level
- Fully automatic charging
- Remote LED connection
- Illuminated on/off switch
- Ultra quiet fan
- Short circuit, over current protection
- LED indication of operating mode (3-stage / PSU)
- Switch between 3-stage (13.8v - 14.5v) and PSU (13.8v)
- Intelligent fan control
- Conforms to all the latest standards

### Protection Features

- Over current protection
- Short circuit protection
- High temperature protection



### Model Range & Part No

Current	Voltage	Voltage (float)	Voltage (bulk)	Input Voltage	Part No
12Amp	24V	27.6V	29.0V	230Vac	RE12A24PS
20Amp	12V	13.8V	14.5V	230Vac	RE20A12PS
25Amp	12V	13.8V	14.5V	230Vac	RE25A12PS

### Technical Specification



#### Protection

- Short circuit protection
- Over current protection
- High temperature protection

#### LED Indication

- Green LED: 3-stage charge mode (13.8v float & 14.5v bulk)
- Yellow LED: PSU mode (13.8v)

#### Technical

- Mains Input: 230Vac
- Mains variation: 207 - 258Vac 44 - 67Hz
- Operating temperature: -20 to +50 degree C fan cooled
- Humidity: 75% NC
- Case material: Painted steel case
- Dimensions: 224mm x 146mm x 85mm
- Weight: 2.1kg (approx)
- Input lead: 1mt long 3core 1.5mm sq black mains cable
- Output connection: 6.3mm x 0.8mm blades

#### Stontronics Ltd

Chancerygate Business Centre, Cradock Road, Reading, Berkshire, RG2 0AH  
 Tel: +44 (0) 118 931 1199 - Fax: +44 (0) 118 931 1145 - Email: info@stontronics.co.uk - www.stontronics.co.uk  
 Stontronics Ltd is not responsible for typographical errors. Product specifications are subject to change without notice.