



Features:

- +/- 10% Wide Input Range Voltage
- Industrial standard Pin Out
- Dual or Single Output
- Un-Regulated Output
- Efficiency up to 81%
- 1000Vdc Isolation
- 3 Year Warranty



Specification

Input Voltage	4.5-26.4Vdc
Output Power (Watts)	0-1W
Operating Temperature	-40°C to 85°C
Storage Temperature	-40°C to 125°C
Relative Humidity	0-95%
Dimensions (WxLxH)	7.1mm X 19.5mm X 10.2mm

Output Voltage and Current Rating Chart

Model Number	Input Voltage	Output Voltage	Output Current		Efficiency (Typ.)	Cap. Load
			Min	Max		
ACA01A-101	4.5 - 5.5Vdc (Nominal: 5V)	3.3Vdc	6.1mA	303mA	74%	220
ACA01A-102		5Vdc	4mA	200mA	78%	220
ACA01A-105		12Vdc	1.7mA	84mA	79%	220
ACA01A-106		15Vdc	1.3mA	67mA	79%	220
ACA01A-202		+/-5Vdc	+/-2.mA	+/-100mA	73%	100
ACA01A-205		+/-12Vdc	+/-0.8mA	+/-42mA	80%	100
ACA01A-206		+/-15Vdc	+/-0.7mA	+/-33mA	80%	100
ACB01A-101	10.8 - 13.2Vdc (Nominal: 12V)	3.3Vdc	6.1mA	303mA	76%	220
ACB01A-102		5Vdc	4mA	200mA	79%	220
ACB01A-105		12Vdc	1.7mA	84mA	80%	220
ACB01A-106		15Vdc	1.3mA	67mA	80%	220
ACB01A-202		+/-5Vdc	+/-2.mA	+/-100mA	75%	100
ACB01A-205		+/-12Vdc	+/-0.8mA	+/-42mA	81%	100
ACB01A-206		+/-15Vdc	+/-0.7mA	+/-33mA	81%	100
ACC01A-101	21.6 - 26.4Vdc (Nominal: 24V)	3.3Vdc	6.1mA	303mA	73%	220
ACC01A-102		5Vdc	4mA	200mA	77%	220
ACC01A-105		12Vdc	1.7mA	84mA	77%	220
ACC01A-106		15Vdc	1.3mA	67mA	79%	220
ACC01A-202		+/-5Vdc	+/-2.mA	+/-100mA	73%	100
ACC01A-205		+/-12Vdc	+/-0.8mA	+/-42mA	79%	100
ACC01A-206		+/-15Vdc	+/-0.7mA	+/-33mA	79%	100