



Features:

- Dual or Single Output
- Regulated Output
- Efficiency up to 86%
- 1500Vdc Isolation
- 3 Year Warranty



Specification

Input Voltage	9-75Vdc
Output Power (Watts)	0-4W
Operating Temperature	-40°C to 75°C
Storage Temperature	-40°C to 125°C
Relative Humidity	0-95%
Dimensions (WxLxH)	20.3mm X 31.8mm X 10.2mm

Output Voltage and Current Rating Chart

Model Number	Input Voltage	Output Voltage	Output Current		Efficiency (Typ.)	Cap. Load
			Min	Max		
ASB04A-101	9-18Vdc (Nominal: 12V)	3.3Vdc	45mA	900mA	79%	3300
ASB04A-102		5Vdc	33mA	660mA	81%	3300
ASB04A-105		12Vdc	17mA	335mA	83%	3300
ASB04A-106		15Vdc	14mA	270mA	83%	3300
ASB04A-202		+/-5Vdc	+/-17mA	+/-330mA	81%	1000
ASB04A-205		+/-12Vdc	+/-9mA	+/-168mA	83%	1000
ASB04A-206		+/-15Vdc	+/-7mA	+/-135mA	83%	1000
ASC04A-101	18-36Vdc (Nominal: 24V)	3.3Vdc	45mA	900mA	80%	3300
ASC04A-102		5Vdc	33mA	660mA	81%	3300
ASC04A-105		12Vdc	17mA	335mA	85%	3300
ASC04A-106		15Vdc	14mA	270mA	85%	3300
ASC04A-202		+/-5Vdc	+/-17mA	+/-330mA	81%	1000
ASC04A-205		+/-12Vdc	+/-9mA	+/-168mA	85%	1000
ASC04A-206		+/-15Vdc	+/-7mA	+/-135mA	85%	1000
ASD04A-101	36-75Vdc (Nominal: 48V)	3.3Vdc	45mA	900mA	80%	3300
ASD04A-102		5Vdc	33mA	660mA	81%	3300
ASD04A-105		12Vdc	17mA	335mA	85%	3300
ASD04A-106		15Vdc	14mA	270mA	85%	3300
ASD04A-202		+/-5Vdc	+/-17mA	+/-330mA	81%	1000
ASD04A-205		+/-12Vdc	+/-9mA	+/-168mA	85%	1000
ASD04A-206		+/-15Vdc	+/-7mA	+/-135mA	85%	1000