



Features:

- Dual or Single Output
- Efficiency up to 86%
- 1500Vdc Isolation
- 3 Year Warranty



Specification

Input Voltage	9-75Vdc
Output Power (Watts)	0-4W
Operating Temperature	-40°C to 71°C
Storage Temperature	-55°C to 125°C
Relative Humidity	0-95%
Dimensions (WxLxH)	20.3mm X 31.8mm X 10.2mm

Output Voltage and Current Rating Chart

Model Number	Input Voltage	Output Voltage	Output Current		Efficiency (Typ.)	Cap. Load
			Min	Max		
ASF04B-101	9-36Vdc	3.3Vdc	90mA	900mA	80%	3300
ASF04B-102		5Vdc	66mA	660mA	81%	3300
ASF04B-105		12Vdc	33mA	335mA	86%	3300
ASF04B-106		15Vdc	27mA	270mA	86%	3300
ASF04B-202		+/- 5Vdc	+/-33mA	+/-330mA	81%	1000
ASF04B-205		+/- 12Vdc	+/-17mA	+/-168mA	86%	1000
ASF04B-206		+/-15Vdc	+/-14mA	+/-135mA	86%	1000
ASG04B-101	18-75Vdc	3.3Vdc	90mA	900mA	80%	3300
ASG04B-102		5Vdc	66mA	660mA	81%	3300
ASG04B-105		12Vdc	33mA	335mA	86%	3300
ASG04B-106		15Vdc	27mA	270mA	86%	3300
ASG04B-202		+/- 5Vdc	+/-33mA	+/-330mA	81%	1000
ASG04B-205		+/- 12Vdc	+/-17mA	+/-168mA	86%	1000
ASG04B-206		+/-15Vdc	+/-14mA	+/-135mA	86%	1000