

GT-C Range

(Specifications)

Model	Nominal Voltage (V)	Nominal Capacity (20hr)(Ah)	Dimensions						H Over Terminal		Weight Approx(kg)	
			L		W		H					
			(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(Kg)	(lb)
GT6-4.5C	6	4.5	70	2.76	47	1.85	101	3.98	107	4.21	0.83	1.8
GT6-7C	6	8	151	5.94	34	1.34	94	3.70	100	3.94	1.36	3.0
GT6-12C	6	13.2	151	5.94	50	1.97	94	3.70	100	3.94	1.89	4.2
GT12-4.5C	12	4.5	90	3.54	70	2.76	101	3.98	107	4.21	1.70	3.7
GT12-7C	12	8	151	5.94	65	2.56	95	3.74	101	3.98	2.55	5.6
GT12-12C	12	13.2	151	5.94	98	3.86	95	3.74	101	3.98	4.00	8.8
GT12-14C	12	14	151	5.94	98	3.86	95	3.74	101	3.98	4.20	9.2
GT12-18C	12	20	181	7.13	77	3.03	167	6.57	167	6.57	6.00	13.2
GT12-26C	12	28	175	6.89	166	6.54	125	4.92	125	4.92	8.90	19.6
GT12-28C	12	28	165	6.50	126	4.96	175	6.89	182	7.17	8.50	18.7
GT12-30C	12	30	167	6.57	126	4.96	173	6.81	176	6.93	10.20	22.4
GT12-35C	12	35	195	7.68	130	5.12	159	6.26	180	7.09	10.50	23.1
GT12-40C	12	40	197	7.76	165	6.50	170	6.69	170	6.69	13.70	30.1
GT12-55C	12	56	229	9.02	138	5.43	206	8.11	226	8.90	17.00	37.4
GT12-65C	12	66	355	13.98	167	6.57	179	7.05	183	7.20	22.70	49.9
GT12-75C	12	76	258	10.16	168	6.61	208	8.19	226	8.90	23.00	50.6
GT12-90C	12	92	305	12.01	168	6.61	208	8.19	226	8.90	30.00	66.0
GT12-100C	12	102	330	12.99	172	6.77	215	8.46	221	8.70	31.00	68.2
GT12-100C-2	12	105	341	13.43	173	6.81	213	8.39	241	9.49	34.00	74.8
GT12-120C	12	122	405	15.94	175	6.89	208	8.19	235	9.25	38.00	83.6
GT12-134C	12	136	341	13.43	172	6.77	284	11.18	288	11.34	42.50	93.5
GT12-150C	12	154	485	19.09	172	6.77	240	9.45	240	9.45	45.00	99.0
GT12-200C	12	202	522	20.55	243	9.57	218	8.58	236	9.29	61.00	134.2
GT12-200C-2	12	205	498	19.61	259	10.20	218	8.58	238	9.37	72.00	158.4