

Features

- Center amplifying gate
- Metal case with ceramic insulator
- Low on-state and switching losses

Typical Applications

- AC controllers
- DC and AC motor control
- Controlled rectifiers

$I_{T(AV)}$ **360A**
 V_{DRM}/V_{RRM} **1100~1800V**
 I_{TSM} **4.65 kA**
 I^2t **108 10³A²S**



SYMBOL	CHARACTERISTIC	TEST CONDITIONS		T _J (°C)	VALUE			UNIT
					Min	Type	Max	
I _{T(AV)}	Mean on-state current	180° half sine wave 50Hz Double side cooled,	T _C =55°C	125			420	A
			T _C =70°C				360	
V _{DRM} V _{RRM}	Repetitive peak off-state voltage Repetitive peak reverse voltage	V _{DRM} &V _{RRM} tp=10ms V _{DSM} &V _{RSM} = V _{DRM} &V _{RRM} +100V		125	1100		1800	V
I _{DRM} I _{RRM}	Repetitive peak current	V _{DM} = V _{DRM} V _{RM} = V _{RRM}		125			16	mA
I _{TSM}	Surge on-state current	10ms half sine wave		125			4.65	kA
I ² t	I ² T for fusing coordination	V _R =0.6V _{RRM}					108	A ² s*10 ³
V _{TO}	Threshold voltage			125			0.85	V
r _T	On-state slop resistance						1.20	mΩ
V _{TM}	Peak on-state voltage	I _{TM} =770A, F=5.0kN		125			1.77	V
dv/dt	Critical rate of rise of off-state voltage	V _{DM} =0.67V _{DRM}		125			1000	V/μs
di/dt	Critical rate of rise of on-state current	V _{DM} = 67%V _{DRM} to 600A, Gate pulse t _r ≤0.5μs I _{GM} =1.5A		125			100	A/μs
Q _{rr}	Recovery charge	I _{TM} =600A, tp=2000μs, di/dt=-20A/μs, V _R =50V		125		800		μC
I _{GT}	Gate trigger current	V _A =12V, I _A =1A		25	30		200	mA
V _{GT}	Gate trigger voltage		0.8			2.0	V	
I _H	Holding current		20			150	mA	
V _{GD}	Non-trigger gate voltage	V _{DM} =67%V _{DRM}		125	0.3			V
R _{th(j-c)}	Thermal resistance Junction to case	At 180° sine double side cooled Clamping force 5.0kN					0.080	°C /W
R _{th(c-h)}	Thermal resistance case to heat sink						0.020	
F _m	Mounting force				3.3		5.5	kN
T _{stg}	Stored temperature				-40		140	°C
W _t	Weight					60		g
Outline	KT19aT							




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7




Fig.8




Fig.9




Fig.10

Outline:

