

### Features

- Interdigitated amplifying gates
- Fast turn-on and high di/dt
- Low switching losses

### Typical Applications

- Inductive heating
- Electronic welders
- Self-commutated inverters

$I_{T(AV)}$	<b>1920A</b>
$V_{DRM}/V_{RRM}$	<b>1900~2500V</b>
$t_q$	<b>40~80μs</b>
$I_{TSM}$	<b>21 kA</b>
$I^2t$	<b>2205 10<sup>3</sup>A<sup>2</sup>S</b>



SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T <sub>J</sub> (°C)	VALUE			UNIT
				Min	Type	Max	
I <sub>T(AV)</sub>	Mean on-state current	180° half sine wave 50Hz Double side cooled,	125			1920	A
						1300	
V <sub>DRM</sub> V <sub>RRM</sub>	Repetitive peak off-state voltage Repetitive peak reverse voltage	V <sub>DRM</sub> &V <sub>RRM</sub> , tp=10ms V <sub>DSM</sub> &V <sub>RSM</sub> = V <sub>DRM</sub> &V <sub>RRM</sub> +100V	125	1900		2500	V
I <sub>DRM</sub> I <sub>RRM</sub>	Repetitive peak current	V <sub>D</sub> = V <sub>DRM</sub> V <sub>R</sub> = V <sub>RRM</sub>	125			140	mA
I <sub>TSM</sub>	Surge on-state current	10ms half sine wave	125			21	kA
I <sup>2</sup> t	I <sup>2</sup> T for fusing coordination					2205	A <sup>2</sup> s*10 <sup>3</sup>
V <sub>TO</sub>	Threshold voltage	I <sub>TM</sub> =3600A, F=32kN	125			1.48	V
r <sub>T</sub>	On-state slop resistance					0.28	mΩ
V <sub>TM</sub>	Peak on-state voltage					2.49	V
dv/dt	Critical rate of rise of off-state voltage	V <sub>DM</sub> =0.67V <sub>DRM</sub>	125			500	V/μs
di/dt	Critical rate of rise of on-state current	V <sub>DM</sub> = 67%V <sub>DRM</sub> to2500A Gate pulse t <sub>r</sub> ≤0.5μs I <sub>GM</sub> =1.5A	125			1200	A/μs
Q <sub>rr</sub>	Recovery charge	I <sub>TM</sub> =2000A, tp=2000μs, di/dt=-60A/μs, V <sub>R</sub> =50V	125		1360		μC
t <sub>q</sub>	Circuit commutated turn-off time	I <sub>TM</sub> =1500A, tp=1000μs, V <sub>R</sub> =50V dv/dt=30V/μs , di/dt=-20A/μs	125	40		80	μs
I <sub>GT</sub>	Gate trigger current	V <sub>A</sub> =12V, I <sub>A</sub> =1A	25	40		450	mA
V <sub>GT</sub>	Gate trigger voltage			0.9		4.5	V
I <sub>H</sub>	Holding current			20		800	mA
V <sub>GD</sub>	Non-trigger gate voltage	V <sub>DM</sub> =67%V <sub>DRM</sub>	125	0.3			V
R <sub>th(j-c)</sub>	Thermal resistance Junction to case	At 180° sine double side cooled Clamping force 32kN				0.013	°C /W
R <sub>th(c-h)</sub>	Thermal resistance case to heat sink					0.0035	
F <sub>m</sub>	Mounting force			27		34	kN
T <sub>stg</sub>	Stored temperature			-40		140	°C
W <sub>t</sub>	Weight					820	g
Outline	KT60cT65						




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6

Outline:

