


## DATASHEET 1312-24030

### Operating Modes Setting

Current:	Voltage:	Resistance:	Power:
0 ... 200 A	0 ... 100	10 Ω ... 16.6	0 ... 8000 W
0 ... 600 A	0 ... 300 V	3.3 Ω ... 5.55	0 ... 24000 W



### Accuracy of the Manual Setting, without Presetting:

	of setting	of corresponding range
Voltage	±0.2%	±0.05%
Current	±0.2%	±0.05%

### Accuracy of Manual Setting with Presetting:

	of setting	of corresponding range
Voltage	±0.6%	±0.05%
Current	±0.6%	±0.05%
Resistance	±1.4%	±0.3% of current range
Power	±1.4%	±0.5%
Current Limitation	±1.4%	±0.3%
Trigger Voltage	±1.4%	±0.3%
Time Setting	±1.4%	±0.5% of B1 or B2
Time ranges for internal modulator		
	B1	100ms
	B2	1000ms

### Accuracy of Display:

	of measured value (real value)	of corresponding range
Voltage	±0.2%	±0.05%
Current	±0.2%	±0.05%

## Accuracy of Analog Programming: 0 ... 5V / 0 ... 10V for Current, Voltage, Power

	of setting	of corresponding range
Voltage	$\pm 0.2\%$	$\pm 0.1\%$
Current	$\pm 0.2\%$	$\pm 0.1\%$
Power	$\pm 2\%$	$\pm 0.5\%$
Current Limitation *	$\pm 1\%$	$\pm 0.4\%$
Trigger Voltage *	$\pm 1\%$	$\pm 0.4\%$

\* only when option ZS08 is installed  
 Input impedance of the analog inputs:  $> 10k\Omega$   
 GND max.  $\pm 2V$  against negative load input <sup>1)</sup>

## Accuracy of Analog Monitor Outputs: 0 ... 10V for Current, Voltage, Power

	of the analog signal of the real value	offset voltage
Voltage	$\pm 0.2\%$	$\pm 15mV$
Current	$\pm 0.2\%$	$\pm 15mV$
Power	$\pm 2\%$	$\pm 30mV$

GND max.  $\pm 2V$  against negative load input <sup>1)</sup>  
 Loading capacity minimum  $2k\Omega$

## Accuracy of Setting Programming via Data Interface:

	of setting	of corresponding range
Voltage	$\pm 0.2\%$	$\pm 0.05\%$
Current	$\pm 0.2\%$	$\pm 0.05\%$
Resistance	$\pm 1\%$	$\pm 3\%$ of current range
Power	$\pm 1\%$	$\pm 0.5\%$
Current Limitation	$\pm 1\%$	$\pm 0.3\%$
Trigger Voltage	$\pm 1\%$	$\pm 0.3\%$
Resolution Setting	<b>16 bit</b>	

## Accuracy of Measurement, Reading via Data Interface:

	of measured value (real value)	of corresponding range
Voltage	$\pm 0.1\%$	$\pm 0.05\%$
Current	$\pm 0.2\%$	$\pm 0.05\%$
Resolution Measurement	<b>18 bit</b>	
Reading Rate	<b>330ms</b> not triggerable	

## Accuracy of Measurement, Reading via Data Interface: Option ZS13

	of measured value (real value)	of corresponding range
Voltage	$\pm 0.2\%$	$\pm 0.05\%$
Current	$\pm 0.2\%$	$\pm 0.05\%$
Resolution Measurement	<b>13 bit</b>	

Reading Rate **min. 200 $\mu$ s** (into memory)  
triggerable

## Cooling

cooling medium	<b>water or water-glycol-mixture</b>
Materials in the cooling circuit	<b>cooper, brass, plastic</b>
Max. Cooling Medium Temperature	<b>12°C for nominal power</b>
Min. Cooling Medium Temperature	<b>5°C</b>
Derating at higher Cooling Medium Temperature	<b>-5% / °C</b>
Pressure for Nominal Power	<b>min. 3 bar</b>
Max. Pressure	<b>5 bar</b>
Cooling Medium Connection	<b>1/2 inch per 8000W</b>
Minimum Input Voltage	<b>approx. 2V for full current</b>

## Input Impedance

> 50 k $\Omega$  at deactivated load input

## Input Capacitance

approx. 2 $\mu$ F / 1000W

## Operating Temperature

5°C ... 40°C


## External Control

- Load switching
- Trigger input and output
- Range switching
- Mode switching
- Emergency shutdown

## Protection Equipment


- Current and power limitation
- Over-voltage protection up to 110% of rated voltage
- Protection against reverse polarity up to rated current (diode)<sup>3)</sup>
- Over-temperature deactivation
- Transient protection

## Minimum voltage



Full current up from approx. 2V.  
Below 2V linear Derating.

## Modulator



Puls t1: 100µs ... 1s  
 Puls t2: 100µs ... 1s  
 (in two ranges)  
 Load level: each 0 ...  
 100%

<b>Rise and Fall Time</b> <sup>5)</sup>	500 µs
<b>Parallel Operation</b>	up to 3 devices in master-slave operation (hardware-controlled)
<b>Cooling</b>	liquid cooled
<b>Case</b> <sup>4)</sup> , <b>Weight</b>	<b>19" / 11 HU, 143 kg</b>
<b>Mains Supply</b>	115/230V ± 10%, 50 ... 60Hz
<b>Power Consumption</b>	<b>145 VA</b>
<b>Electric Safety</b>	DIN EN 61010-1
<b>EMC, CE-Mark</b>	DIN EN 61326-1 DIN EN 61000-3-2 DIN EN 61000-3-3
<b>Permissible Operating Voltages: Negative Load Input - Case</b>	
Standard	125V AC
with Option ZS06	500V AC <sup>3)</sup>
<b>Colour</b>	
Front Panel	RAL7032 (pebble grey)
Sides, Lid	RAL7037 (stone grey)

1) 500 V with option ZS06 (except a Zero-Volt-Option is installed)

2) no protection against reverse polarity at installed Zero-Volt-Option

3) except a Zero-Volt-Option is installed

4) 1HU = 44.45mm

5) Rise and fall times are defined as 10%...90% and 90%...10% of the maximum current (measured in constant current mode - FAST)