


DATASHEET 1311-U-1V20C80

Output:

- Voltage: -1 V ... 20 V
- Current: -80 A ... 80 A
- Power: 1600 W



The specified accuracies refer to an ambient temperature of 25°C ±5°C.

The specified accuracies are valid when the unit is connected to undisturbed voltages (Ripple and Noise <0.1%). At voltages with higher disturbance values the accuracy can change for the worse.

Accuracy of Setting

	of setting	of corresponding range
Voltage	±0.1%	±0.05%
Current	±0.2%	±0.05%
Voltage Limitation	±0.1%	±0.05%
Current Limitation	±0.2%	±0.05%
Resolution Setting		16 Bit
Ripple		±0.05% RMS of range
Load Effect 0-100%		0.1%
Line Effect AC ±10%		0.02%

Accuracy of Display:

HEIDEN power GmbH
Am Wiesengrund
86932 Pürgen
Germany

Tel.: +49-8196-9988-0
Fax.: +49-8196-9988-77
Email: info@heidenpower.com
www.heidenpower.com

	of measured value (real value)	of corresponding range
Voltage	±0.1%	±0.05%
Current	±0.2%	±0.05%
Resistance	Quotient of voltage and current	
Power	Product of voltage and current	

Accuracy of Analog Programming:
-5V ... 0 ... 5V / -10V ... 0 ... 10V for Current, Voltage

	of setting	of corresponding range
Voltage	±0.2%	±0.15%
Current	±0.4%	±0.15%
Voltage Limitation * (upper and lower)	±0.2%	±0.15%
Current Limitation * (upper and lower)	±0.4%	±0.15%

* only -10V ... 0 ... +10V

Input impedance of the analog inputs: > 10kΩ
 GND max. ±2V against negative output terminal¹⁾

Accuracy of Analog Monitor Outputs:
-10V ... 0 ... 10V for Current, Voltage

	of analog signal of the real value	offset voltage
Voltage	±0.1%	±15mV
Current	±0.2%	±15mV

GND max. ±2V against negative output terminal¹⁾
 Minimum loading capacity 2kΩ

Accuracy of Measurement, Reading via Data Interface:

	of measured value (real value)	of corresponding range
Voltage	±0.1%	±0.05%

Current	±0.2%	±0.05%
Resolution Measurement	18 Bit	
Reading Rate (free running)	330ms not triggerable	

Accuracy of Measurement, Reading via Data Interface: NL13 Option

		of measured value (real value)	of corresponding range
Voltage	±0.15%	±0.07%	
Current	±0.3%	±0.07%	
Resolution Measurement	13 Bit		
Reading Rate	min. 200µs (in memory) triggerable		

Power

Nominal Power	up to $T_A = 21\text{ °C}$
Derating	-1.2% / °C for $T_A > 21\text{ °C}$

Input Impedance > 50 kΩ in standby

Operating Temperature 5°C ... 40°C

External Control Functions

- Stand-by
- Trigger input and output
- Mode switching
- Emergency shutdown

Protection Equipment

- Current and voltage limitation
- Over-temperature deactivation

Rise and Fall Time²⁾ **200 µs**

Parallel Operation up to 3 devices in master-slave operation
(hardware-controlled in current mode only)

Cooling Current and temperature-controlled fans

Dimension³⁾, **Weight** **19" / 8 HU, 55 kg**

Mains Supply **230 VAC ± 10%**
50 ... 60Hz

Power Consumption **2700 VA**

Electric Safety DIN EN 61010-1

EMC, CE-Mark DIN EN 61326-1
DIN EN 61000-3-2
DIN EN 61000-3-3

Measuring Device Category CAT I

Permissible Operating Voltages: Negative Output Terminal- Case

±125V DC

**Permissible Operating Voltages:
Analog Interface - Negative Output Terminal**

Standard ±2V DC

with NL06 Option ±125V DC

Colour

Front Panel RAL7032 (pebble grey)

Sides, Lid RAL7037 (stone grey)

1) ±125V with NL06 Option

2) Rise and fall times are defined as 10%...90% and 90%...10% of the maximum current (measured in constant current mode - FAST)

3) 1HU = 44.45mm