


## DATASHEET **1311-U-1V10C180**

### Output:

- Voltage: **-1 V ... 10 V**
- Current: **-180 A ... 180 A**
- Power: **1800 W**



The specified accuracies refer to an ambient temperature of 25°C ±5°C.

The specified accuracies are valid when the unit is connected to undisturbed voltages (Ripple and Noise <0.1%). At voltages with higher disturbance values the accuracy can change for the worse.

---

### Accuracy of Setting

	of setting	of corresponding range
Voltage	<b>±0.1%</b>	<b>±0.05%</b>
Current	<b>±0.2%</b>	<b>±0.05%</b>
Voltage Limitation	<b>±0.1%</b>	<b>±0.05%</b>
Current Limitation	<b>±0.2%</b>	<b>±0.05%</b>
Resolution Setting		<b>16 Bit</b>
Ripple		<b>±0.05%</b> RMS of range
Load Effect 0-100%		<b>0.1%</b>
Line Effect AC ±10%		<b>0.02%</b>

## Accuracy of Display:

	of measured value (real value)	of corresponding range
Voltage	$\pm 0.1\%$	$\pm 0.05\%$
Current	$\pm 0.2\%$	$\pm 0.05\%$
Resistance	<b>Quotient of voltage and current</b>	
Power	<b>Product of voltage and current</b>	

## Accuracy of Analog Programming:

**-5V ... 0 ... 5V / -10V ... 0 ... 10V for Current, Voltage**

	of setting	of corresponding range
Voltage	$\pm 0.2\%$	$\pm 0.15\%$
Current	$\pm 0.4\%$	$\pm 0.15\%$
Voltage Limitation * (upper and lower)	$\pm 0.2\%$	$\pm 0.15\%$
Current Limitation * (upper and lower)	$\pm 0.4\%$	$\pm 0.15\%$

\* only -10V ... 0 ... +10V

Input impedance of the analog inputs: > 10k $\Omega$   
GND max.  $\pm 2V$  against negative output terminal<sup>1)</sup>

## Accuracy of Analog Monitor Outputs:

**-10V ... 0 ... 10V for Current, Voltage**

	of analog signal of the real value	offset voltage
Voltage	$\pm 0.1\%$	$\pm 15mV$
Current	$\pm 0.2\%$	$\pm 15mV$

GND max.  $\pm 2V$  against negative output terminal<sup>1)</sup>  
Minimum loading capacity 2k $\Omega$

## Accuracy of Measurement, Reading via Data Interface:

	of measured value (real value)	of corresponding range
--	-----------------------------------	---------------------------

Voltage	<b>±0.1%</b>	<b>±0.05%</b>
Current	<b>±0.2%</b>	<b>±0.05%</b>
Resolution Measurement	<b>18 Bit</b>	
Reading Rate (free running)	<b>330ms</b> not triggerable	

### Accuracy of Measurement, Reading via Data Interface: NL13 Option

	of measured value (real value)	of corresponding range
Voltage	<b>±0.15%</b>	<b>±0.07%</b>
Current	<b>±0.3%</b>	<b>±0.07%</b>
Resolution Measurement	<b>13 Bit</b>	
Reading Rate	<b>min. 200µs</b> (in memory) triggerable	

---

### Power

Nominal Power	up to $T_A = 21\text{ °C}$
Derating	-1.2% / °C for $T_A > 21\text{ °C}$

---

**Input Impedance** > 50 kΩ in standby

**Operating Temperature** 5°C ... 40°C

**External Control Functions**

- Stand-by
- Trigger input and output
- Mode switching
- Emergency shutdown

**Protection Equipment**

- Current and voltage limitation
- Over-temperature deactivation

**Rise and Fall Time** <sup>2)</sup> **200 µs**

**Parallel Operation** up to 3 devices in master-slave operation  
(hardware-controlled in current mode only)

**Cooling** Current and temperature-controlled fans

<b>Dimension<sup>3)</sup>, Weight</b>	<b>19" / 11 HU, 80 kg</b>
<b>Mains Supply</b>	<b>230/400 VAC -16A ± 10%</b> <b>50 ... 60Hz</b>
<b>Power Consumption</b>	<b>3775 VA</b>
<b>Electric Safety</b>	DIN EN 61010-1
<b>EMC, CE-Mark</b>	DIN EN 61326-1 DIN EN 61000-3-2 DIN EN 61000-3-3

**Measuring Device Category** CAT I

---

**Permissible Operating Voltages: Negative Output Terminal- Case**

±125V DC

---

**Permissible Operating Voltages:  
Analog Interface - Negative Output Terminal**

Standard	±2V DC
with NL06 Option	±125V DC

---

**Colour**

Front Panel	RAL7032 (pebble grey)
Sides, Lid	RAL7037 (stone grey)

---

---

1) ±125V with NL06 Option

2) Rise and fall times are defined as 10%...90% and 90%...10% of the maximum current (measured in constant current mode - FAST)

3) 1HU = 44.45mm