


## DATASHEET 1311-B-20V20C60

### Output:

- Voltage: -20 V ... 20 V

- Current: -60 A ... 60 A

- Power: 1200 W



The specified accuracies refer to an ambient temperature of 25°C ±5°C.

The specified accuracies are valid when the unit is connected to undisturbed voltages (Ripple and Noise <0.1%). At voltages with higher disturbance values the accuracy can change for the worse.

---

### Accuracy of Setting

	of setting	of corresponding range
Voltage	±0.1%	±0.05%
Current	±0.2%	±0.05%
Voltage Limitation	±0.1%	±0.05%
Current Limitation	±0.2%	±0.05%
Resolution Setting		16 Bit
Ripple		±0.05% RMS of range
Load Effect 0-100%		0.1%
Line Effect AC ±10%		0.02%

---

## Accuracy of Display:

	of measured value (real value)	of corresponding range
Voltage	$\pm 0.1\%$	$\pm 0.05\%$
Current	$\pm 0.2\%$	$\pm 0.05\%$
Resistance	<b>Quotient of voltage and current</b>	
Power	<b>Product of voltage and current</b>	

## Accuracy of Analog Programming:

**-5V ... 0 ... 5V / -10V ... 0 ... 10V for Current, Voltage**

	of setting	of corresponding range
Voltage	$\pm 0.2\%$	$\pm 0.15\%$
Current	$\pm 0.4\%$	$\pm 0.15\%$
Voltage Limitation * (upper and lower)	$\pm 0.2\%$	$\pm 0.15\%$
Current Limitation * (upper and lower)	$\pm 0.4\%$	$\pm 0.15\%$

\* only -10V ... 0 ... +10V

Input impedance of the analog inputs: > 10k $\Omega$   
GND max.  $\pm 2V$  against negative output terminal<sup>1)</sup>

## Accuracy of Analog Monitor Outputs:

**-10V ... 0 ... 10V for Current, Voltage**

	of analog signal of the real value	offset voltage
Voltage	$\pm 0.1\%$	$\pm 15mV$
Current	$\pm 0.2\%$	$\pm 15mV$

GND max.  $\pm 2V$  against negative output terminal<sup>1)</sup>  
Minimum loading capacity 2k $\Omega$

## Accuracy of Measurement, Reading via Data Interface:

	of measured value (real value)	of corresponding range
--	-----------------------------------	---------------------------

Voltage	<b>±0.1%</b>	<b>±0.05%</b>
Current	<b>±0.2%</b>	<b>±0.05%</b>
Resolution Measurement	<b>18 Bit</b>	
Reading Rate (free running)	<b>330ms</b> not triggerable	

**Accuracy of Measurement, Reading via Data Interface: NL13 Option**

	of measured value (real value)	of corresponding range
Voltage	<b>±0.15%</b>	<b>±0.07%</b>
Current	<b>±0.3%</b>	<b>±0.07%</b>
Resolution Measurement	<b>13 Bit</b>	
Reading Rate	<b>min. 200µs</b> (in memory) triggerable	

**Power**

Nominal Power	up to $T_A = 21\text{ °C}$
Derating	-1.2% / °C for $T_A > 21\text{ °C}$

**Input Impedance** > 50 kΩ in standby

**Operating Temperature** 5°C ... 40°C

**External Control Functions**  
 Stand-by  
 Trigger input and output  
 Mode switching  
 Emergency shutdown

**Protection Equipment**  
 Current and voltage limitation  
 Over-temperature deactivation

**Rise and Fall Time <sup>2)</sup>** **200 µs**

**Parallel Operation** up to 3 devices in master-slave operation  
 (hardware-controlled in current mode only)

**Cooling** Current and temperature-controlled fans

**Dimension<sup>3)</sup>, Weight**      **19" / 11 HU, 80 kg**

**Mains Supply**                **230 VAC ± 10%**  
**50 ... 60Hz**

**Power Consumption**        **2200 VA**

**Electric Safety**                **DIN EN 61010-1**

**EMC, CE-Mark**                **DIN EN 61326-1**  
**DIN EN 61000-3-2**  
**DIN EN 61000-3-3**

**Measuring Device Category** **CAT I**

---

**Permissible Operating Voltages: Negative Output Terminal- Case**

±125V DC

---

**Permissible Operating Voltages:  
Analog Interface - Negative Output Terminal**

Standard                         ±2V DC

with NL06 Option                ±125V DC

---

**Colour**

Front Panel                        RAL7032 (pebble grey)

Sides, Lid                         RAL7037 (stone grey)

---

1) ±125V with NL06 Option

2) Rise and fall times are defined as 10%...90% and 90%...10% of the maximum current (measured in constant current mode - FAST)

3) 1HU = 44.45mm