

PLASTIC SILICON RECTIFIER

VOLTAGE RANGE: 1250 V

CURRENT: 1.0 A


FEATURES

- ◇ Molded case feature for auto insertion
- ◇ High current capability
- ◇ Low leakage current
- ◇ High surge capability
- ◇ High temperature soldering guaranteed:
250°C/10sec/0.375" (9.5mm) lead length at 5 lbs tension

MECHANICAL DATA

- ◇ Case: JEDEC DO -41, molded plastic
- ◇ Terminals: Axial lead, solderable per MIL-STD-202, Method 208
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.012 ounces, 0.34 grams
- ◇ Mounting position: Any

DO - 41



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

		BY127	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	1250	V
Maximum RMS voltage	V_{RMS}	875	V
Maximum DC blocking voltage	V_{DC}	1250	V
Maximum average forward rectified current 9.5mm lead length, @ $T_A=75^\circ\text{C}$	$I_{F(AV)}$	1.0	A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load @ $T_J=125^\circ\text{C}$	I_{FSM}	30.0	A
Maximum instantaneous forward voltage @ 1.0 A	V_F	1.1	V
Maximum reverse current @ $T_A=25^\circ\text{C}$ at rated DC blocking voltage @ $T_A=100^\circ\text{C}$	I_R	5.0 50.0	μA
Typical junction capacitance (Note1)	C_J	10	pF
Typical thermal resistance (Note2)	$R_{\theta JA}$	50	$^\circ\text{C/W}$
Operating junction temperature range	T_J	- 55 ---- + 150	$^\circ\text{C}$
Storage temperature range	T_{STG}	- 55 ---- + 150	$^\circ\text{C}$

NOTE: 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

www.galaxycn.com

2. Thermal resistance from junction to ambient at 0.375"(9.5mm) lead length, P.C. board mounted

FIG.1 – TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2 – TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.3 – MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.4 – TYPICAL REVERSE CHARACTERISTICS




FIG.5 – TYPICAL JUNCTION CAPACITANCE

