

SURFACE MOUNT RECTIFIERS

REVERSE VOLTAGE: 50 - 1000 V
FORWARD CURRENT: 3.0 A


FEATURES

Plastic package has underwriters laboratories
flammability classification 94V-0
For surface mount applications
Low profile package
Easy pick and place
Ultrafast recovery times for high efficiency
Low forward voltage, low power loss
Built-in strain relief, ideal for automated placement
High temperature soldering:
250°C/10 seconds on terminals

MECHANICAL DATA

Case: JEDEC DO-214AB, molded plastic body
c over passivated chip
Terminals: Solder Plated, solderable per MIL-STD-750,
Method 2026
Polarity: Color band denotes cathode end
Weight: 0.007 ounces, 0.21 gram

DO-214AB(SMC)



Dimensions in millimeters

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified

		US3A	US3B	US3D	US3G	US3J	US3K	US3M	UNITS
Device marking code		US3A	US3B	US3D	US3G	US3J	US3K	US3M	
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V _{RWS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V _{DC}	50	100	200	400	600	800	1000	V
Maximum average forw ard rectified current at T _L =110°C	I _{F(AV)}	3.0							A
Peak forw ard surge current 8.3ms single half-sine-wave superimposed on rated load(JEDEC Method)	I _{FSM}	100							A
Maximum instantaneous forw ard voltage at 3A	V _F	1.0				1.7			V
Maximum DC reverse current @T _A =25°C at rated DC blockjing voltage @T _A =125°C	I _R	10 500							μ A
Maximum reverse recovery time at I _F =0.5A I _R =1.0A I _{rr} =0.25A	t _{rr}	50				75			ns
Typical junction capacitance at 4.0V,1MH _z	C _J	70				50			pF
Maximum thermal resistance (NOTE1)	R _{θJA}	25							°C/W
Operating temperature range	T _J	-55-----+150							°C
Storage temperature range	T _{STG}	-55-----+150							°C

NOTE: 1. P.C.B. mounted on 0.2X0.2" (5.0X5.0mm) copper pad area

www.galaxycn.com

FIG.1 -- FORWARD CURRENT DERATING CURVE




FIG.3 -- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.5 -- TYPICAL JUNCTION CAPACITANCE




FIG.2 -- MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.4 -- TYPICAL REVERSE CHARACTERISTICS




FIG.6 -- TYPICAL TRANSIENT THERMAL IMPEDANCE

