

FAST RECOVERY RECTIFIERS

VOLTAGE RANGE: 50 --- 1000 V

CURRENT: 5.0 A


FEATURES

- ◇ Low cost
- ◇ Glass passivated junction
- ◇ Low leakage
- ◇ Low forward voltage drop
- ◇ High current capability
- ◇ Easily cleaned with Freon, Alcohol, Isopropanol and similar solvents
- ◇ The plastic material carries U/L recognition 94V-0

MECHANICAL DATA

- ◇ Case: JEDEC R-6, molded plastic
- ◇ Terminals: Axial lead, solderable per MIL-STD-750, Method 2026
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.072 ounces, 2.04 grams
- ◇ Mounting position: Any

R-6



Dimensions in millimeters

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

		RGP 50A	RGP 50B	RGP 50D	RGP 50G	RGP 50J	RGP 50K	RGP 50M	UNITS
Maximum recurrent peak reverse voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V _{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V _{DC}	50	100	200	400	600	800	1000	V
Maximum average forward rectified current 9.5mm lead length, @T _A =55°C	I _{F(AV)}	5.0							A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load @T _J =125°C	I _{FSM}	300							A
Maximum instantaneous forward voltage @ 5.0 A	V _F	1.3							V
Maximum reverse current @T _A =25°C at rated DC blocking voltage @T _A =100°C	I _R	5.0 100.0							μ A
Maximum reverse recovery time (Note1)	t _{rr}	150				250	500		ns
Typical junction capacitance (Note2)	C _J	32							pF
Typical thermal resistance (Note3)	R _{θJA}	10							°C/W
Operating junction temperature range	T _J	- 55---- +175							°C
Storage temperature range	T _{STG}	- 55---- + 175							°C



NOTE:1. Measured with $I_F=0.5\text{A}$, $I_R=1\text{A}$, $t_{rr}=0.25\text{A}$.

2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

3. Thermal resistance from junction to ambient.

www.galaxycn.com

FIG.1 -REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM




NOTES: 1. RESE TIME=7ns MAX.INPUT IMPEDANCE=1MΩ.22pF.
2. RESE TIME=10ns MAX.SOURCE IMPEDANCE=500Ω

SET TIME BASE FOR: 50/100 ns /cm

FIG.2 -PEAK FORWARD SURGE CURRENT


PEAK FORWARD SURGE CURRENT
AMPERES



NUMBER OF CYCLES AT 60Hz

FIG.4-FORWARD CURRENT DERATING CURVE


AVERAGE FORWARD CURRENT
AMPERES



AMBIENT TEMPERATURE, °C

FIG.3-TYPICAL FORWARD CHARACTERISTICS


INSTANTANEOUS FORWARD CURRENT
AMPERES



INSTANTANEOUS FORWARD CURRENT

FIG.5-TYPICAL REVERSE CHARACTERISTICS

JUNCTION CAPACITANCE,pF



REVERSE VOLTAGE, VOLTS