

SUPER FAST RECTIFIERS

VOLTAGE RANGE: 100 --- 600 V
CURRENT: 5.0 A


FEATURES

- ◇ Low cost
- ◇ Low leakage
- ◇ Low forward voltage drop
- ◇ High current capability
- ◇ Easily cleaned with alcohol, Isopropanol and similar solvents
- ◇ The plastic material carries U/L recognition 94V-0

MECHANICAL DATA

- ◇ Case: JEDEC D²PAK, molded plastic
- ◇ Terminals: Solderable per MIL-STD-750, Method 2026
- ◇ Polarity: As marked
- ◇ Weight: 0.087 ounces, 2.2 grams
- ◇ Mounting position: Any

D²PAK



Dimensions in millimeters

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

		USF 510BC	USF 520BC	USF 530BC	USF 540BC	USF 550BC	USF 560BC	UNITS
Maximum recurrent peak reverse voltage	V _{RRM}	100	200	300	400	500	600	V
Maximum RMS voltage	V _{RMS}	70	140	210	280	350	420	V
Maximum DC blocking voltage	V _{DC}	100	200	300	400	500	600	V
Maximum average forw ard rectified current @T _c =100°C	I _{F(AV)}	5.0						A
Peak forw ard surge current 8.3ms single half-sine-w ave superimposed on rated load @T _j =125°C	I _{FSM}	40						A
Maximum instantaneous forw ard voltage @ 2.5A	V _F	0.98		1.3		1.7		V
Maximum reverse current @T _A =25°C at rated DC blocking voltage @T _A =150°C	I _R	5.0 250		10 500				μ A
Maximum reverse recovery time (Note1)	t _{rr}	25						ns
Operating junction temperature range	T _j	- 55 ----- + 150						°C
Storage temperature range	T _{STG}	- 55 ----- + 150						°C

NOTE: 1. Measured with $I_F=0.5\text{A}$, $I_R=1\text{A}$, $t_{rr}=0.25\text{A}$.

www.galaxycn.com

FIG.1 – TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC




FIG.2 – TYPICAL FORWARD CHARACTERISTIC




FIG.3 – PEAK FORWARD SURGE CURRENT




FIG.4-FORWORD DERATING CURVE

