

PNP Silicon Epitaxial Planar Transistor**KTA1505****FEATURES**


- Complementary To KTC3876.
- Excellent H_{FE} Linearity.
- Low noise.



Lead-free

APPLICATIONS

- General purpose application, switching application.

**ORDERING INFORMATION**

Type No.	Marking	Package Code
KTA1505	AZO/AZY/AZG	SOT-23

MAXIMUM RATING @ $T_a=25^{\circ}\text{C}$ unless otherwise specified

Symbol	Parameter	Value	Units
V_{CBO}	Collector-Base Voltage	-35	V
V_{CEO}	Collector-Emitter Voltage	-30	V
V_{EBO}	Emitter-Base Voltage	-5	V
I_C	Collector Current -Continuous	-500	mA
P_C	Collector Power Dissipation	150	mW
T_j, T_{stg}	Junction and Storage Temperature	-55~150	$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS @ $T_a=25^{\circ}\text{C}$ unless otherwise specified

PNP Silicon Epitaxial Planar Transistor**KTA1505**

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C = -100\mu A, I_E = 0$	-35			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C = -1mA, I_B = 0$	-30			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E = -100\mu A, I_C = 0$	-5			V
Collector cut-off current	I_{CBO}	$V_{CB} = -35V, I_E = 0$			-0.1	μA
Emitter cut-off current	I_{EBO}	$V_{EB} = -5V, I_C = 0$			-0.1	μA
DC current gain	h_{FE}	$V_{CE} = -1V, I_C = -100mA$	70		400	
		$V_{CE} = -6V, I_C = -400mA$	25			
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = -100mA, I_B = -10mA$		-0.1	-0.25	V
Base-emitter saturation voltage	V_{BE}	$V_{CE} = -1V, I_C = -100mA$		-0.8	-1.0	V
Transition frequency	f_T	$V_{CE} = -6V, I_C = -20mA$		200		MHz
Collector output capacitance	C_{ob}	$V_{CB} = -6V, I_E = 0, f = 1MHz$		13		pF






CLASSIFICATION OF h_{FE}

Rank	O	Y	G
Range	70-140	120-240	200-400
Marking	AZO	AZY	AZG

PNP Silicon Epitaxial Planar Transistor

KTA1505

TYPICAL CHARACTERISTICS @ $T_a=25^\circ\text{C}$ unless otherwise specified




PNP Silicon Epitaxial Planar Transistor

KTA1505


PACKAGE OUTLINE

Plastic surface mounted package

SOT-23



SOLDERING FOOTPRINT



PACKAGE INFORMATION

Device	Package	Shipping
KTA1505	SOT-23	3000/Tape&Reel