

Surface Mount Fast Switching Diodes


MMBD4148TW/BAS16TW

FEATURES

- Fast switching speed.
- For general purpose switching application.
- Ultra-small surface mount package.
- High conductance.



Lead-free



SOT-363

APPLICATIONS

- For general purpose switching application.

ORDERING INFORMATION

Type No.	Marking	Package Code
MMBD4148TW	KA2	SOT-363
BAS16TW	KA2•	SOT-363

MAXIMUM RATING @ Ta=25°C unless otherwise specified

Symbol	Characteristic	Value	Unit
V_{RM}	Non-repetitive peak reverse Voltage	100	V
V_{RRM} V_{RWM} V_R	Peak repetitive reverse Voltage Working peak reverse voltage DC reverse voltage	75	V
I_{FM}	Forward continuous current	300	mA
I_O	Average rectified output current	150	mA
I_{FSM}	Non-Repetitive peak forward surge current @t=1.0μs @t=1.0s	2.0 1.0	A
P_D	Power Dissipation	200	mW
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	625	°C/W
T_j, T_{stg}	Junction and Storage Temperature	-65to+150	°C





Surface Mount Fast Switching Diodes

MMBD4148TW/BAS16TW

ELECTRICAL CHARACTERISTICS @ $T_a=25^\circ\text{C}$ unless otherwise specified

Parameter	Symbol	Test conditions	MIN	MAX	UNIT
Reverse breakdown voltage	$V_{(BR)R}$	$I_R=1\mu\text{A}$	75	-	V
Forward voltage	V_F	$I_F=1.0\text{mA}$ $I_F=10\text{mA}$ $I_F=50\text{mA}$ $I_F=150\text{mA}$	-	0.715 0.855 1.0 1.25	V
Total Capacitance	C_T	$V_{CB}=10\text{V}, f=1.0\text{MHz}, I_E=0$	-	2.0	pF
Reverse Recovery time	t_{rr}	$I_F=I_R=10\text{mA}, I_{rr}=0.1 \cdot I_R, R_L=100\Omega$	-	4.0	ns

TYPICAL CHARACTERISTICS @ $T_a=25^\circ\text{C}$ unless otherwise specified




Surface Mount Fast Switching Diodes
MMBD4148TW/BAS16TW


PACKAGE OUTLINE

Plastic surface mounted package

SOT-363



SOLDERING FOOTPRINT



PACKAGE INFORMATION

Device	Package	Shipping
MMBD4148TW/BAS16TW	SOT-363	3000/Tape&Reel