

e-disk® Altima™ 3.5" Fibre Channel SSD

Think hard.

When it comes to ruggedness, no drive beats e-disk Altima. You can truly take your data anywhere.

E-disk Altima SSDs set the standard for reliable data storage in extreme environments. E-disk Altima SSDs operate under extreme temperatures, shock (1,500 Gs), vibration (16.4 Grms), humidity (5%-95%) and altitude (120,000 ft).

Powered by BITMICRO's EDSA™ flash I/O controller and LUNETE™ memory flash interface ASICs, e-disk Altima SSDs boost system performance by eliminating seek time and latency for faster I/O and sustained transfer rates.

BITMICRO provides the highest quality of service you'll experience. Our sales & support teams understand the development cycle and work to service you through your entire project and long after our product has even been deployed in the field.

Applications

E-disk Altima SSDs are ideal for military and industrial applications such as: ISR, aviation & avionics, industrial & embedded, pipeline inspection, medical equipment, and industrial automation.

Features

- Extreme ruggedness
- PowerGuard® Data Loss Protection
- Low Voltage Detection
- SecurErase® Military Sanitization

Environmental

Operational Temperature	Commercial: 0 to 70°C Industrial: -40 to 85°C
--------------------------------	--

Max Temperature Change Rate	3°C/min
------------------------------------	---------

Altitude	-1,200 to 120,000 ft
-----------------	----------------------

Humidity	5 to 95% (non-condensing)
-----------------	---------------------------

Shock	1,500G
--------------	--------

Vibration	16.4 Grms
------------------	-----------

Security

SecurErase Standard Compliance	NISPOM DoD 5220.22-M NSA 130-2 Air Force AFSSI 5020 Army 380-19 IRIG-106 NISPOMSUP AFSSI 5020/2003 AFSSI 5020/2003 CLR NSA 9-12
---------------------------------------	---

For Information...

Email: sales@bitmicro.com

Call: +1 (510) 743-3475

Fax: +1 (510) 623-2342



e-disk[®] Altima[™] 3.5" Fibre Channel SCSI SSD

Additional Specifications

Physical

Form Factor	3.5"
Mounting	HDD standard, all orientations
Connector	40-Pin SCA-2 (Level 4 Hot Swap) Fibre Channel ANSI Standards
Size (L x W x H)	5.75" x 4.00" x 0.536"
Weight	9.360 oz. to 29.394 oz.

Note: Size and weight numbers are approximate. Contact your sales representative for specific measurements and tolerances for your configuration.

Capacity

SLC	20 GB to 1.1 TB
------------	-----------------

Performance

Burst Rate	800 MB/s
Cache	Up to 256 MB

Power

Voltage	5V (±5%) or 5V/12V (±5%) Auto-detect
----------------	--------------------------------------

Reliability

Error Correction	Corrects up to 9 bits per 528B
Write Endurance	76.71 years @ 100 GB/day write-erase cycles (20 GB drive)

Compliance

Interface	FC-AL-2, FC-PH, FC-PLDA, FC-FCP, FC-FLA, FCA-IP, IETF-IPFC
EMC	ICES-003 Issue 4, February 7, 2004 Class A VCCI V-3/2008.04 and V-4/2007.04 Class A AS/NZS CISPR 22: 2006 Class A EN 55022: 2006 – Emissions EN 55024:2003 - Immunity
Safety	UL 60950-1 CSA C22.2 No. 60950-1 EN 60950-1
RoHS	EU RoHS 2002/95/EC

Warranty

Standard	1 year
Extended	Up to 5 years