




PRODUCT FEATURES

1. Surface mount low pass filter with a small size of 1.0 X 0.5 X 0.4 mm, RoHS compliant.
2. Provide low insertion loss and high rejection rate.
3. Highly stable under temperature and humidity changes.

RF CHARACTERISTICS


P/N LP0915M0402AT	Specification
Frequency range	824-915 MHz
Insertion Loss (max)	0.65 dB at +25°C
VSWR	2.0 max
Impedance	50 Ω
Attenuation (min.)	25 dB @ 1648- 1830 MHz 25 dB @ 2472- 2745 MHz 25 dB @ 3296- 3660 MHz
Operating temperature range	-40°C to +85°C

PHYSICAL DIMENSIONS




Symbol	Dimension (mm)
L	1.00 $\pm$ 0.10
W	0.50 $\pm$ 0.10
T	0.40 $\pm$ 0.10
A	0.35 $\pm$ 0.10
B, E	0.30 $\pm$ 0.10
C, D	0.15 $\pm$ 0.10

TERMINAL CONFIGURATION




PIN	Definition
P1	Input
P2	GND
P3	Output
P4	GND

PCB DESIGN/LAYOUT CONSIDERATION



Note:

- Unit in mm
- Design trace width to be 50 Ω impedance.





Typical RF Performance

