P-55 Thermal Disc Printer

Print high-quality, photo-realistic images directly onto thermal discs with the TEAC P-55 Thermal Disc Printer—optimized to produce vibrant colors with increased clarity and sharpness. The resolution is the highest dye-sublimation disc printing resolution in the industry today.

Printing Method: Thermal re-transfer printing
Media: 12cm or 8cm CD/DVD discs
Ribbon Capacity: 500 images/ribbon (full color)
Print Speed: < 60 seconds/disc (full color)
Print Resolution: 400 dpi
Interface: USB 2.0
Printer Driver: Windows XP, Vista, 7 (32 and 64-bit)
Power Voltage: 100-240VAC / 50-60Hz (manual switch)
Power Consumption: 500W or less
Dimensions: 11.875"W x 9.5"H x 15.312"D   **Weight:** 48.5 lbs.

P-55/220, 550 Autoloader

Printer Model: TEAC P-55 (see above)
Controller: Series 5 with True Copy System
Printing Method: Thermal dye-sublimation
Ribbon Capacity: 500 images/ribbon (full-color)
Disc Capacity: 220 or 550 depending on system
Print Resolution: Up to 400dpi
Interface: USB 2.0
OS Requirements: Windows 2000/XP/Linux
Dimensions: 14.4"L x 18"W x 13.5"H
Weight: 39 lbs.

Automatically print hundreds of CDs or DVDs quickly and easily with a TEAC Autoloader, an advanced robotic mechanism used to transport discs from the input bins to the integrated disc printer, then to the output bins.

With an integrated P-55 Thermal Disc Printer, the Autoloader uses VersaMax ribbons which produce superior photo-grade images! Available in 220 or 550-disc systems.

AP-55 Discathlon Automatic Thermal Disc Printer

The TEAC AP-55 automatically prints up to 300 discs using high-resolution thermal dye-sublimation printing technology.
The Discathlon offers the ultimate in high-precision robotic disc printing. Using scratch-resistant, fade-resistant, water-proof media, the end result is a beautiful professional disc.

PRINTER SPECIFICATIONS
Printing Method: Thermal re-transfer printing
Supported Interface: USB 2.0
Print Speed: < 60 seconds per disc (full color)
Installable Printers: Up to 2
Disc Capacity: 300
OS Requirements: Windows 2000, XP Professional
LOADER SPECIFICATIONS
Supported Interface: RS-232C
Media Capacity: Up to 300 discs
Disc Loading Method: Robotic mechanism
Dimensions: 20"W x 30.55"D x 22.52"H, 125 lbs.

TEAC Consumables

Photo Ribbon Set (+TFR): PHOTO/RIBBON/SET
Color Ribbon Set (+TFR): COLOR/RIBBON/SET
VersaMax Ribbon Set (+TFR): VERSAMAX/RIBBON/SET
Black Ribbon: BLACK/RIBBON
Transfer Ribbon: TRANSFER/RIBBON

Photo/Color Cartridge: CARTRIDGE/INK
Black Cartridge: CARTRIDGE/BLK
VersaMax Color Cartridge: CARTRIDGE/VERSAMAX
Transfer Cartridge: CARTRIDGE/TFR
Cleaning Cartridge: CLEANING/CART/P-55

800.646.8881   microboards.com

TEAC DISC/USB PRINTERS