



LL270STR

Technical Specification

Image not found

<http://www.giatech.eu/wp-content/uploads/2014/07/LL-stranded-75.jpg>

The braid configuration and the expanded PTFE dielectrics of the LL cable constructions contribute to lower attenuation levels at higher frequencies, while providing shielding effectiveness levels that exceed those of flexible MIL-DTL-17 cables. Flat strips of silver plated copper are braided over the dielectric core with an intermediate metallized polyester or polyimide layer, and an outer round wire braid. Harbour's LL cables with expanded PTFE dielectrics exhibit low coefficients of expansion over the entire operating temperature range from -55° C to +200° C. Impedance discontinuities are minimized at the cable-to-connector interface. Higher levels of power can be transmitted because higher temperatures do not affect the cable due to the thermal stability of the tape. Where phase versus temperature requirements are critical, Harbour's LL cables allow for an approximately 75% lower phase shift and change in propagation time delay due to temperature. Temperature cycling tests have been performed on a number of Harbour's cables with positive results.

Stranding (metric)	7/0.58
Stranding (awg)	7/0.023
Conductor Material	Silver plated copper
Conductor Diameter Min (mm)	1.73
Conductor Diameter Min (in)	0.068
Insulation Material	Expanded PTFE
Diameter over insulation - Min. (mm)	4.70
Diameter over insulation - Min. Inch	0.185
Number of cores	1
1st Shield material	round silver plated copper braid
1st shield Diameter (mm)	4.95
1st shield Diameter (in)	0.195
2nd Shield material	Aluminium Polyester Tape
2nd shield Diameter (mm)	5.08
2nd shield Diameter (in)	0.200
3rd Shield material	Round Silver Plated Copper Braid
3rd shield Diameter (in)	5.58
3rd shield Diameter (mm)	0.220
Jacket Material	FEP
Jacket diameter (mm)	6.85
Jacket diameter (in)	0.270
Minimum Temperature °C	-55
Maximum Temperature °C	200
Weight (kg/km)	104.40
Weight (lbs/kft)	70

For technical assistance or to order this product please contact Giatech on:
Tel: +44 (0) 1202 890975 Email: info@giatech.eu

Giatech has a policy of continuous product improvement and reserves the right to change technical specifications at any time without prior notice.
Therefore, before ordering this product, please contact us to check you have the latest specifications for this product.

Giatech offers in excess of 300 specialist standard products for applications in Airframe, Airborne Data, Mil Spec, Hookup / Equipment Wire, RF / Coaxial, Telecomms / Data and Aerospace Special Application. We also provide a Custom Cable Design service for your unique applications.

For full details go to www.giatech.eu

Rendered: September 15, 2015, 5:05 pm
www.giatech.eu