



## TRX400

### Technical Specification

Image not found

TRX400 [www.giatech.eu/wp-content/uploads/2014/07/TRX-75.jpg](http://www.giatech.eu/wp-content/uploads/2014/07/TRX-75.jpg)

These triaxial cables have been designed to perform in situations where isolation of shields in a coaxial cable is an important consideration. An interlayer between first and second braid is added to achieve complete isolation of the two shields.

Stranding (metric)	19/0.203
Stranding (awg)	19/0.008
Conductor Material	Silver plated copper
Conductor Diameter Min (mm)	0.98
Conductor Diameter Min (in)	0.0384
Insulation Material	PTFE
Diameter over insulation - Min. (mm)	2.95
Diameter over insulation - Min. Inch	0.116
Number of cores	1
1st Shield material	round silver plated copper braid
1st shield Diameter (mm)	3.45
1st shield Diameter (in)	0.136
2nd Shield material	Round silver plated copper braid
2nd shield Diameter (mm)	4.72
2nd shield Diameter (in)	0.186
Jacket Material	FEP
Jacket diameter (mm)	5.46
Jacket diameter (in)	0.215

For technical assistance or to order this product please contact Giatech on:  
Tel: +44 (0) 1202 890975 Email: [info@giatech.eu](mailto:info@giatech.eu)

Giatech has a policy of continuous product improvement and reserves the right to change technical specifications at any time without prior notice. Therefore, before ordering this product, please contact us to check you have the latest specifications for this product.

*Giatech offers in excess of 300 specialist standard products for applications in Airframe, Airborne Data, Mil Spec, Hookup / Equipment Wire, RF / Coaxial, Telecomms / Data and Aerospace Special Application. We also provide a Custom Cable Design service for your unique applications.*

*For full details go to [www.giatech.eu](http://www.giatech.eu)*

Rendered: September 15, 2015, 5:06 pm  
[www.giatech.eu](http://www.giatech.eu)