



M17/158-00001

Technical Specification

1st shield Diameter (in)	0.162
1st shield Diameter (mm)	4.11
1st Shield material	Double round silver plated copper braid
Competitors Part Number	RGU-142
Conductor Diameter Min (in)	0.037
Conductor Diameter Min (mm)	0.94
Conductor Material	Silver Plated Copper Weld
Conductor resistance (ohms/1000ft)	19.5
Conductor resistance (ohms/1000m)	64
Diameter over insulation - Min. Inch	0.116
Diameter over insulation - Min. (mm)	2.95
Insulation Material	PTFE
Jacket diameter (in)	0.195
Jacket diameter (mm)	4.95
Jacket Material	FEP
Maximum Temperature °C	200
Minimum Temperature °C	-55
Number of cores	1
Specification	MIL-DTL-17
Stranding (awg)	1/0.037
Stranding (metric)	1/0.94
Voltage (volts)	1900
Weight (kg/km)	83.44
Weight (lbs/kft)	56
Impedance (ohms)	50
Capacitance (pF/m)	96.46
Capacitance (pF/ft)	29.4

This specification is cancelled - refer MIL-DTL-17/060-RG142

For technical assistance or to order this product please contact Giatech on:
Tel: +44 (0) 1202 890975 Email: info@giatech.eu

Giatech has a policy of continuous product improvement and reserves the right to change technical specifications at any time without prior notice.
Therefore, before ordering this product, please contact us to check you have the latest specifications for this product.

Giatech offers in excess of 300 specialist standard products for applications in Airframe, Airborne Data, Mil Spec, Hookup / Equipment Wire, RF / Coaxial, Telecomms / Data and Aerospace Special Application. We also provide a Custom Cable Design service for your unique applications.

For full details go to www.giatech.eu

Rendered: September 15, 2015, 5:09 pm
www.giatech.eu