



- Ultra Low drive thru platform with separate ramps
- Standard deck height: 40-50mm (height may vary according to capacity of platform)
- single or double ramps
- Mild steel or Stainless steel 304 and 316 construction
- IP67 or IP68 cells
- Many other options available
- Price on application

## 1530 mild steel drive thru platforms (EC approved)

**Mild steel construction with hammer spray finish.** Fitted with Nickel IP67 C3 (R60) load cells

Model	Deck Size (mm)	Height (mm)	Capacities (kg)	C4, C5, C6 & MI cells can be fitted at extra cost
88DT	800x800	50	300-1500	
1010DT	1000x1000	50	300-1500	
1210DT	1200x1000	50	300-1500	
1212DT	1200x1200	50	300-1500	
1412DT	1400x1200	50	300-1500	
1515DT	1500x1500	50	300-1500	
Platform width: deck width + 250mm      Ramp length: 500mm				

## 1530 stainless steel drive thru platforms (EC approved)

**'304' Stainless steel construction with bead blast finish.**  
Fitted with stainless steel IP68 C3 (R60) load cells

Model	Deck Size (mm)	Height (mm)	Capacities (kg)	C4, C5, C6 & MI cells can be fitted at extra cost
88SDT	800x800	50	300-1500	
1010SDT	1000x1000	50	300-1500	
1210SDT	1200x1000	50	300-1500	
1212SDT	1200x1200	50	300-1500	
1412SDT	1400x1200	50	300-1500	
1515SDT	1500x1500	50	300-1500	
Platform width: deck width + 250mm      Ramp length: 500mm				



Deeter Weighing Systems follows a policy of continual development of its products and reserves the right to change specifications and/or features without notice

Deeter House, Valley Road, Hughenden Valley, Bucks. HP14 4LW

Tel: +44 (0) 1494 566046 Fax: +44 (0) 1494 563961 Email: [sales@deeter.co.uk](mailto:sales@deeter.co.uk)

[www.deeter.co.uk](http://www.deeter.co.uk)