


PLEASE NOTE:

B = _____



NOTES:

1. MAXIMUM PERMISSIBLE OUT OF SQUARE OF PIN TO MOULDING TO BE 0.10mm IN ANY DIRECTION.
2. CONTACT LEG VARIATION ON COMPLETE ASSEMBLY NOT TO EXCEED 0.10mm.
3. CO-PLANARITY: DEVIATION FROM FLATNESS OF SMT TAILS MUST NOT EXCEED 0.20mm.
4. ANGULAR DISPLACEMENT OF SMT TAILS MUST NOT EXCEED 2° PER SIDE.

**THIS SKETCH IS FOR
QUOTATION PURPOSES
ONLY**

SPECIFICATION:

MATERIAL:

MOULDING = HIGH TEMPERATURE
NYLON 6T, UL94V-0, BLACK

PINS = BRASS

FINISH:

PINS: SEE BOX BELOW

ELECTRICAL:

CURRENT RATING = 1A MAX

CONTACT RESISTANCE = 30 mΩ MAX

INSULATION RESISTANCE = 5,000 MΩ MIN

DIELECTRIC STRENGTH = 500V AC/DC

ENVIRONMENTAL:

TEMPERATURE RANGE = -55°C TO +105°C

PACKING:

BAG

FINISH

(TICK APPLICABLE):



100% TIN



GOLD

DATE OF SKETCH:

REQUESTED BY:

No. OF CONTACTS
PER ROW:

HARWIN

HARWIN INC
U.S.A.

TEL: (812) 542 2540

FAX: (812) 542 2541

HARWIN PLC
U.K.

TEL: 023 9231 4545

FAX: 023 9231 4590

HARWIN PTE
SINGAPORE

TEL: 65 6779 4909

FAX: 65 6779 3868

THIS DRAWING AND ANY
INFORMATION OR DESCRIPTIVE
MATTER SET OUT HEREON ARE
CONFIDENTIAL AND COPYRIGHT
PROPERTY OF THE HARWIN
GROUP AND MUST NOT BE
DISCLOSED, LOANED, COPIED
OR USED FOR MANUFACTURING,
TENDERING OR FOR ANY
OTHER PURPOSE WITHOUT
THEIR WRITTEN PERMISSION.

TOLERANCES

X. = ±1mm

X.X = ±0.25mm

X.XX = ±0.10mm

X.XXX = ±0.01mm

ANGLES = ±5°

UNLESS STATED

TITLE:

1.27 x 2.54mm PITCH DIL VERTICAL
SMT PIN HEADER VARIANT

DRAWING No.:

M52- _____ S _____

SHT
1
OF
1