



ADVANCED ULTRA-RUGGED FOR FIRST RESPONDERS

# APX™ 7000XE MULTIBAND PORTABLE RADIO

Our radios are like a lifeline to first responders. Their lives and the lives of others may depend on them. Designed by first responders for first responders, the APX™ 7000XE is our most advanced, ultra-rugged radio.

Featuring a large top display and easy-to-operate glove-friendly controls, the APX 7000XE delivers superior audio - significantly louder and clearer, so every word is heard, even with extreme background noise. The APX™ 7000XE is a mission critical multiband, multi-protocol radio for truly interoperable communications.

## ADVANCED ERGONOMICS FOR EXTREME CONDITIONS

- Easy to grip, hold and control in harsh conditions
- Glove-friendly controls are big, recognizable and easy to distinguish
- Well-spaced knobs eliminate accidental activation
- Enlarged top display is easy to read, in dark or low light
- Shielded Push-To-Talk button is easy to use with a gloved hand
- Largest emergency button in the industry

## EXCEPTIONAL AUDIO MEANS EVERY WORD IS HEARD

- 50% louder and clearer without distortion
- Dual microphone locates the speaker, cancels out ambient noise
- Extreme Audio Profile reduces background noise and improves voice clarity
- Equipped with the latest AMBE digital voice vocoder
- New speaker grill design for improved water runoff

## NEXT GENERATION TECHNOLOGY

- Project 25 Phase 2 technology provides twice the voice capacity
- Multiband operation ensures seamless interoperability
- Backwards and forwards compatible with all Motorola Mission Critical radio systems
- Future-ready for applications like Mission Critical Wireless and GPS location tracking

- Channel capacity
- Top display - 1,200
- Dual Display - 2,000
- Universal Push-To-Talk
- T-grip
- Dual battery latch
- Extra large emergency button
- 16-position rotary switch
- 2-position concentric switch
- 3-position toggle switch
- 3 programmable side buttons
- Transmit LED indicator
- Tall top display
  - 1 line of icons
  - 1 line x 8 characters of text
- Standard Rugged
- FM Certified

**PRODUCT SPEC SHEET**  
APX™ 7000XE



**FEATURES AND BENEFITS:**

- Available in 700-800 MHz, VHF, UHF Range 1 and UHF Range 2 bands
- Operational multiband operation
- Trunking standards supported:
  - Clear or digital encrypted ASTRO® 25 Trunked Operation
  - Capable of SmartZone®, SmartZone Omnilink, SmartNet®
- Analog MDC-1200 and Digital APCO P25 Conventional System Configurations
- Narrow and wide bandwidth digital receiver\* (6.25 kHz equivalent / 12.5 kHz / 30 kHz / 25 kHz)
- Embedded digital signalling (ASTRO & ASTRO 25)
- Integrated GPS capable
- Seamless wideband scan
- Intelligent lighting
- Radio profiles
- Expansion slot
- Micro SD removable memory card
- User programmable voice announcement
- Meets Applicable MIL-STD-810C, D, E, F and G
- Ships standard, FM Certified and Rugged\*\*
- Yellow and green coloured housing options

Superior audio features:

- Extreme aAudio Profile
  - 1W high audio speaker
  - Dual speakers (model 3.5 only)
  - Dual-sided 2-microphone noise cancelling technology
- Utilises Windows XP, Windows 7, and Vista Customer Programming Software (CPS)
- Supports USB communications
  - Built in FLASHport™ support

Full portfolio of accessories including the Remote Speaker Microphone specifically designed for performance in extreme environments.

**OPTIONAL FEATURES:**

- Mission Critical Wireless\*\*\*
- Enhanced encryption capability
- Programming Over Project 25 (POP25)
- Over the Air Rekeying (OTAR)
- Text messaging
- Man Down

**TRANSMITTER - TYPICAL PERFORMANCE SPECIFICATIONS**

	700 MHz	800 MHz	VHF	UHF Range 1	UHF Range 2
Frequency Range/Bandsplits	763-776 MHz 793-806 MHz	806-824 MHz 851-870 MHz	136-174 MHz	380-470 MHz	450-520 MHz
Channel Spacing	25/12.5 kHz	25/12.5 kHz	30/25/12.5 kHz	25/20/12.5 kHz	25/12.5 kHz
Maximum Frequency Separation	Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit
Rated RF Output Power Adj <sup>1</sup>	1-2.5 Watts	1-3 Watts	1-6 Watts	1-5 Watts	1-5 Watts
Frequency Stability <sup>1</sup> (-30°C to +60°C; +25°C Ref.)	±0.00010%	±0.00010%	±0.00010%	±0.00010%	±0.00010%
Modulation Limiting <sup>1</sup>	±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz
Emissions (Conducted and Radiated) <sup>1</sup>	-75 dB	-75 dB	-75 dB	-75 dB	-75 dB
Audio Response <sup>1</sup>	+1, -3 dB	+1, -3 dB	+1, -3 dB	+1, -3 dB	+1, -3 dB
FM Hum & Noise	25 kHz -48 dB 12.5 kHz -46 dB	-47 dB -45 dB	-47 dB -45 dB	-47 dB -45 dB	-47 dB -45 dB
Audio Distortion <sup>1</sup>	0.60 %	1 %	0.50 %	0.50 %	0.50 %

**BATTERIES FOR APX 7000XE**

Battery Capacity / Type	Dimensions (HxWxD)	Weight	Battery Part Number	Battery Capacity
Li-Ion IMPRES 2300 mAh FM <sup>2</sup> Rugged <sup>†</sup>	3.39" x 2.34" x 1.65"	6.53 oz	NNTN8092	2300 mAh
Li-Ion IMPRES 2150 mAh IP67	3.39" x 2.34" x 1.45"	5.0 oz	PMNN4403	2150 mAh
Li-Ion IMPRES 2900 mAh IP67	3.39" x 2.34" x 1.65"	6.53 oz	NNTN7038	2900 mAh
Li-Ion IMPRES 4200 mAh IP67	5.07" x 2.34" x 1.65"	11.29 oz	NNTN7034	4200 mAh
Li-Ion IMPRES 4100 mAh FM <sup>2</sup> IP67	5.07" x 2.34" x 1.65"	11.29 oz	NNTN7033	4100 mAh
NiMH IMPRES 2100 mAh IP67	5.12" x 2.34" x 1.57"	11.82 oz	NNTN7037	2100 mAh
NiMH IMPRES 2000 mAh FM <sup>2</sup> IP67	5.12" x 2.34" x 1.57"	11.82 oz	NNTN7036	2000 mAh
NiMH IMPRES 2000 mAh FM <sup>2</sup> Rugged	5.12" x 2.34" x 1.57"	11.82 oz	NNTN7035	2000 mAh
NiMH IMPRES 2100 mAh Rugged	5.12" x 2.34" x 1.57"	11.82 oz	NNTN7573	2100 mAh

<sup>†</sup> Standard shipping battery  
<sup>\*</sup>Per the FCC Narrowbanding rules, new products (APX 7000XE UHF R1 - UHF R2 combination) submitted for FCC certification after January 1st, 2011 are restricted from being granted certification at 25 kHz for United States - State & Local Markets only. All other band combinations will comply with FCC Narrowbanding rules January 1st, 2013.  
<sup>\*\*</sup> Rugged radios exceed industry standards (IPx7) for immersion and provide a higher level of water protection—MIL-STD-810E, Method 512.3 Immersion. These radios meet the incremental requirement of submersion in 1 meter of fresh water that is 27C colder than the product.  
 FM Certification & Level is dependent on configuration ordered.  
<sup>\*\*\*</sup> Compatible with BT 2.0 and HSP and PAN BT Profiles

**PRODUCT SPEC SHEET**  
APX™ 7000XE

**RECEIVER - TYPICAL PERFORMANCE SPECIFICATIONS**

	700 MHz	800 MHz	VHF	UHF Range 1	UHF Range 2
Frequency Range/Bandsplits	763-776 MHz	851-870 MHz	136-174 MHz	380-470 MHz	450-520 MHz
Channel Spacing	25/12.5 kHz	25/12.5 kHz	30/25/12.5 kHz	25/12.5 kHz	25/12.5 kHz
Maximum Frequency Separation	Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit
Audio Output Power at Rated <sup>1</sup>	1000 mW	1000 mW	1000 mW	1000 mW	1000 mW
Frequency Stability <sup>1</sup> (-30°C to +60°C; +25°C Ref.)	±0.00010 %	±0.00010 %	±0.00010 %	±0.00010 %	±0.00010 %
Analog Sensitivity <sup>3</sup>	12 dB SINAD 0.250 µV	0.250 µV	0.216 µV	0.234 µV	0.234 µV
Digital Sensitivity <sup>4</sup>	1% BER 0.347 µV	0.333 µV	0.277 µV	0.307 µV	0.307 µV
	5% BER 0.251 µV	0.251 µV	0.188 µV	0.207 µV	0.207 µV
Selectivity <sup>1</sup>	25 kHz channel 12.5 kHz channel	75.7 dB 67.5 dB	75.7 dB 67.5 dB	79.3 dB 70 dB	78.3 dB 68.1 dB
					78.3 dB 67.5 dB
Intermodulation Rejection	80 dB	80 dB	80.5 dB	80.2 dB	80.2 dB
Spurious Rejection	76.6 dB	76.6 dB	93.2 dB	80.3 dB	80.3 dB
FM Hum & Noise	25 kHz 12.5 kHz	-54 dB -48 dB	-54 dB -48 dB	-53.8 dB -48 dB	-53.5 dB -47.4 dB
Audio Distortion <sup>1</sup>	0.9 %	0.9 %	1.20 %	0.91 %	0.91 %

**RADIO MODELS**

**Model 1.5 Top Display**

Display	Tall monochromatic LCD top display ■ 1 line text, 8 characters ■ 1 line of icons ■ No menu support ■ Multi-color backlight
Keypad	None
Channel Capacity	1200
FLASHport Memory	64 MB
700/800 MHz (763-870 MHz)	Model H49TGD9PW1AN, Primary QA00569, Secondary QA00573
VHF (136-174 MHz)	Model H49TGD9PW1AN, Primary QA00570, Secondary QA00574
UHF Range 1 (380-470 MHz)	Model H49TGD9PW1AN, Primary QA00571, Secondary QA00575
UHF Range 2 (450-520 MHz)	Model H49TGD9PW1AN, Primary QA00572, Secondary QA00576
Buttons & Switches	Large PTT button ■ Angled on/off volume knob ■ X-large emergency button ■ 16 position top mounted rotary knob ■ 2-position concentric switch ■ 3-position toggle switch ■ 3 programmable side buttons
Embedded	GPS LED Yes Multi-color

**Model 3.5 Dual Display**

Display	Tall monochromatic LDC top display ■ Large color LCD front display ■ 4 lines text, 14 characters ■ 2 lines of icons ■ 1 menu line, 3 menus, White backlight
Keypad	Backlight Keypad ■ 3 soft keys ■ 4-direction navigation key ■ 4x3 keypad ■ Home and Data buttons
Channel Capacity	3000
FLASHport Memory	64 MB
700/800 MHz (764-870 MHz)	Model H49TGD9PW1AN Primary QA00569 Secondary QA00573 Keypad/Dual Display QA00577
VHF (136-174 MHz)	Model H49TGD9PW1AN Primary QA00570 Secondary QA00574 Keypad/Dual Display QA00577
UHF Range 1 (380-470 MHz)	Model H49TGD9PW1AN Primary QA00571 Secondary QA00575 Keypad/Dual Display QA00577
UHF Range 2 (450-520 MHz)	Model H49TGD9PW1AN Primary QA00572 Secondary QA00576 Keypad/Dual Display QA00577
Buttons & Switches	Large PTT button ■ Angled On/Off Volume knob ■ Extra large emergency button ■ 16 position top mounted rotary knob ■ 2-position concentric switch ■ 3-position toggle switch ■ 3 programmable side buttons ■ Multi-color backlight
Embedded	GPS LED Yes Multi-color

**Transmitter Certification - per FCC Grant of Equipment Authorization**

VHF – 700/800 MHz	AZ489FT7036 (136-174 MHz and 764-869 MHz)
UHF R1 – 700/800 MHz	AZ489FT7040 (380-470 MHz and 764-869 MHz)
UHF R1 – VHF	AZ489FT4886 (380-470 MHz and 136-174 MHz)
UHF R2 – 700/800 MHz	AZ489FT7042 (450-520 MHz and 764-869 MHz)
UHF R2 – VHF	AZ489FT4893 (450-520 MHz and 136-174 MHz)
Bluetooth	AZ489FT6000 (2402-2480 MHz)

**FCC Emission Designators**

FCC Emission Designators	11K0F3E, 16K0F3E, 8K10F1D, 8K10F1E, 8K10F1W, 20K0F1E*
--------------------------	---

**Power Supply**

Power Supply	One rechargeable 2300 mAh FM/Rugged Li-Ion Battery Standard (NNTN8092), with alternate battery options available
--------------	--

\*Per the FCC Narrowbanding rules, new products (APX 7000XE UHF R1 and UHF R2 combination) submitted for FCC certification after January 1st, 2011 are restricted from being granted certification at 25 kHz for United States - State & Local Markets only.

All other band combinations will comply with FCC Narrowbanding rules January 1st, 2013.

**PORTABLE MILITARY STANDARDS 810 C, D, E, F & G**

	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G	
	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II
High Temperature	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Basic Hot	501.5	I/A1, II/A2
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1	502.5	I/C3, II/C1
Temperature Shock	503.1	I	503.2	I/A1C3	503.3	I/A1C3	503.4	I	503.5	I/C
Solar Radiation	505.1	II	505.2	I	505.3	I	505.4	I	505.5	I/A1
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.5	I, III
Humidity	507.1	II	507.2	II	507.3	II	507.4	1 Proc	507.5	II/Aggravated
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	1 Proc	509.5	1 Proc
Blowing Dust	510.1	I	510.2	I	510.3	I	510.4	I	510.5	I
Blowing Sand	1 Proc	1 Proc	510.2	II	510.3	II	510.4	II	510.5	II
Immersion (Delta-T)	512.1	I	512.2	I	512.3	I	512.4	I	512.5	I
Vibration	514.2	VIII/F, Curve-W	514.3	I/10, II/3	514.4	I/10, II/3	514.5	I/24	514.6	I/24
Shock	516.2	I, III, V	516.3	I, V, VI	516.4	I, V, VI	516.5	I, V, VI	516.6	I, V, VI
Shock (Drop)	516.2	II	516.2	IV	516.4	IV	516.5	IV	516.6	IV

**ENCRYPTION**

Supported Encryption Algorithms	ADP, AES, DES, DES-XL, DES-OFB, DVP-XL
Encryption Algorithm Capacity	8
Encryption Keys per Radio	Module capable of storing 1024 keys. Programmable for 128 Common Key Reference (CKR) or 16 Physical Identifier (PID)
Encryption Frame Re-sync Interval	P25 CAI 300 mSec
Encryption Keying	Key Loader
Synchronization	XL – Counter Addressing OFB – Output Feedback
Vector Generator	National Institute of Standards and Technology (NIST) approved random number generator
Encryption Type	Digital
Key Storage	Tamper protected volatile or non-volatile memory
Key Erasure	Keyboard command and tamper detection
Standards	FIPS 140-2 Level 3 FIPS 197

**RUGGED OPTION SPECIFICATIONS**

Leakage (immersion)	MIL-STD-810 C,D,E,F and G Method 512.X Procedure I
Housing Availability	Black (Standard), Public Safety Yellow and High Impact Green

**ENVIRONMENTAL SPECIFICATIONS**

Operating Temperature	-30°C / +60°C
Storage Temperature	-40°C / +85°C
Humidity	MIL-STD 507.x PROC. II
ESD	IEC 801-2 KV
Water and Dust Intrusion	IP67 and MIL-STD's noted above
Immersion (Delta-T)	MIL-STD 512.X/I

**GPS SPECIFICATIONS**

Channels	12
Tracking Sensitivity	-151 dBm
Accuracy <sup>2</sup>	<10 meters (95%)
Cold Start	<60 seconds (95%)
Hot Start	<10 seconds (95%)
Mode of Operation	Autonomous (Non-Assisted) GPS

**DIMENSIONS OF THE RADIOS WITHOUT BATTERY**

	Inches	Millimeters
Height	6.94	176.3
Width Push-To-Talk button	2.39	60.8
Depth Push-To-Talk button	1.40	35.6
Width Top	3.32	84.3
Depth Top	2.18	55.4
Depth Bottom	1.25	31.7
Weight of the radios without battery	15.4 oz	439 g

<sup>1</sup> Measured in the analog mode per TIA / EIA 603 under nominal conditions

<sup>2</sup> When used with an FM approved intrinsically safe radio

<sup>3</sup> Measured conductively in analog mode per TIA / EIA 603 under nominal conditions

<sup>4</sup> Measured conductively in digital mode per TIA / EIA IS 102.CAAA under nominal conditions

<sup>5</sup> Accuracy specs are for long-term tracking (95th percentile values >5 satellites visible at a nominal -130 dBm signal strength)

<sup>6</sup> Temperatures listed are for radio specifications. Battery storage is recommended at 25°C, ±5°C to ensure best performance

Specifications subject to change without notice. All specifications shown are typical.

Radio meets applicable regulatory requirements.

**PRODUCT SPEC SHEET**  
**APX™ 7000XE**

**REGULATORY COMPLIANCE**

Radio (R&TTE Article 3.2)	Directive 1999/5/EC RTTE EN 300 086-2 v1.3.1
	EN 300 113-2 v1.5.1
	EN 300 328 v1.7.1
EMC (R&TTE Article 3.1.b)	EN 301 489-1 V1.9.2
	EN 301 489-5 V1.3.1
	EN 301 489-17 V2.1.1
Electrical Safety (R&TTE Article 3.1.a)	EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011 + AC:2011
	ICNIRP(1998) Occupational Controlled Environment
Environmental	Directive 2002/96/EC WEEE
	Directive 2011/65/EU RoHS-2
Year of first application of CE Mark	2011 (136-174MHz) ; 2011 (380-470MHz)
Type Designator	PMA302D, P (136-174MHz) ; PMA502D, P (380-470MHz);
	PMA902D35, P35 ; PMF902D35, P35 (Dual Band)