



## POWERFUL AND FLEXIBLE VOIP COMMUNICATIONS

# MCD 5000 DESKSET SYSTEM

Expand your communications with VoIP technology. Scalable from small operations to complex control centers and geographically disbursed operations, you can depend on the new modular MCD 5000 Deskset System with VoIP technology for your conventional and trunked communications. Whether used in dispatch environments, back-up sites, special events or call monitoring, you can easily expand communication capabilities throughout your organization using your IP network. This easy-to-deploy solution enables communications across your network

when and where you need it most, increasing safety, awareness and coordination.

### **MCD 5000 DESKSET**

A flexible desktop console, the MCD 5000 Deskset provides digital control for a variety of Motorola two-way radios, and can connect directly to a radio or over an IP network using the MCD 5000 Radio Gateway Unit (RGU).

The MCD 5000 Deskset digital control link emulates the buttons and display of the connected radio and performs all the functions of the radio control head.


And with a large and easy-to-read color LCD screen, intuitive layout and an adjustable viewing angle, the MCD 5000 Deskset is ergonomically designed for both occasional and constant everyday use.




## EXAMPLE MCD 5000 DESKSET SYSTEM SHOWING 3 OPERATOR POSITIONS CONTROLLING UP TO 8 RADIOS

The MCD 5000 Deskset system allows multiple desksets to dynamically switch to different MCD 5000 RGUs, giving you access to additional radios for expanded communications. Each MCD 5000 Deskset can connect to one radio at a time.


EACH DESKSET CAN SELECT ANY ONE OF THE 8 RADIOS BELOW



MCD 5000 DESKSET



MCD 5000 DESKSET



MCD 5000 DESKSET

IP NETWORK  
WAN / LAN

MCD 5000 RGU



EACH MCD 5000 RGU  
SUPPORTS UP TO 4 RADIOS

MCD 5000 RGU



TWO-WAY RADIO DEVICES



TWO-WAY RADIO DEVICES



CONVENTIONAL/TRUNKING/DIGITAL/ANALOG



### TWO-WAY RADIO DEVICES

The MCD 5000 Deskset lets you control a wide variety of digital radios:

#### APX™ 7500 Multiband Console

#### ASTRO® Console (W9):

ASTRO® Spectra™  
ASTRO® Spectra Plus™  
ASTRO® XTL™ 5000

#### CDM Series Radios:

CDM 1550™  
CDM 1550 LS™  
CDM 1550 LS+™

#### Dimetra TETRA Mobile Radios:

MTM5400  
MTM800E

#### MCS 2000™ Model III Control Station

TRC Radios/Base-Station/Adaptors

4-Wire E&M Radios

**PRODUCT SPEC SHEET**  
MCD 5000 DESKSET

**SPECIFICATIONS**

**MCD 5000 DESKSET**

Dimensions	Height: 4.17 in (106 mm) Width: 10.35 in (263 mm) Depth: 8.27 in (210 mm) Weight: 3.97 lbs (1.8 kg)
Environmental	Operating temperature: 0 °C to 50 °C (32 °F to 122 °F) Storage temperature: -40 °C to 80 °C (-40 °F to 176 °F) Humidity: 5% to 95% @ +50° C (122° F), Non-Condensing
Power	Input power: +10.8 to +13.2VDC, (+12 V nominal) Dissipation: 12.5W Max. 37VDC to 57VDC. Powered via POE-PD; meeting 802.3af Standard for Powered Desksets class 0
Audio	The end-to-end distortion is no more than 3% THD The generated audio is no more than -50 dBm of Hum and Noise below the rate audio output The crosstalk between any audio signals is no more than -65 dBm at 0 dBm transmit audio power
Supported Radio Protocols	RS-232 TTL using RJ-45 connector, SB9600, IP, 4W-E&M, TRC
Regulatory-EMC	FCC part 15 class A
Safety	EN60950-1
Green Product	RoHS, WEEE Mark
Certified Standard Compliance Requirements	CE Mark, FCC part 15 A Mark, UL Mark (for P.S. only) US federal government Environmentally Preferable Specification (EPP) Program
Non-certified Standard Compliance Requirements	CSA, UL, MOTOROLA W18 certification, CMM
Vocoders	G.711 and G.729

**MCD 5000 DESKSET SYSTEM CAPACITIES**

Maximum Number of Radio Resources	512
Maximum Number of MCD 5000 Radio Gateway Units (RGUs)	128
Maximum Number of Radios per MCD 5000 Radio Gateway Unit (RGU)	4
Maximum Number of MCD 5000 Desksets	100
Maximum Number of Groups per MCD 5000 Deskset	20
Maximum Number of Users per MCD 5000 Deskset	8 (Non-OMC System) 1,000 (OMC System)

**MCD 5000 RADIO GATEWAY UNIT**

Dimensions	Height: 1.65 in (42 mm) Width: 8.58 in (218 mm) Depth: 10.39 in (264 mm) Weight: 5.73 lbs (2.6 kg)
Environmental	Operating temperature: -30 °C to 60 °C (-22 °F to 140 °F) Storage temperature: -40 °C to 80 °C (-40 °F to 176 °F) Humidity: 5% to 95% @ +50° C (122° F), Non-Condensing
Power	Input power:+10.8 to +14VDC, (+12 V nominal) Dissipation: 9W Max. 37VDC to 57VDC. Powered via POE-PD; meeting 802.3af Standard for Powered Desksets class 0
Audio	The end-to-end distortion is no more than 3% THD The generated audio is no more than -50 dBm of Hum and Noise below the rate audio output The crosstalk between any audio signals is no more than -65 dBm at 0 dBm transmit audio power
Supported Radio Protocols	RS-232 TTL, SB9600, IP, 4W-E&M, TRC
Regulatory-EMC	FCC part 15 class A
Safety	EN60950-1
Green Product	RoHS, WEEE Mark
Certified Standard Compliance Requirements	CE Mark, FCC part 15 A Mark, UL Mark (for P.S. only) US federal government Environmentally Preferable Specification (EPP) Program
Non-certified Standard Compliance Requirements	CSA, UL, MOTOROLA W18 certification, CMM
Vocoders	G.711 and G.729

To learn more about how the MCD 5000 Deskset System can help you implement powerful and flexible VoIP communications on your network, contact your Motorola representative or visit [motorola.com/dispatch](http://motorola.com/dispatch).

Motorola Solutions, Inc. 1301 E. Algonquin Road, Schaumburg, Illinois 60196 U.S.A. [motorolasolutions.com](http://motorolasolutions.com)

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. Microsoft, Windows, Windows Me and Windows Vista are registered trademarks of Microsoft Corporation in the United States and other countries. All other trademarks are the property of their respective owners. © 2012 Motorola Solutions, Inc. All rights reserved. R3-13-2015A

