

13 12 11 10 9 8 7 6 5 4 3 2 1

J  
I  
H  
G  
F  
E  
D  
C  
B  
A

- NOTES:  
 1. MATERIAL:  
     HOUSING: POLYESTER(PBT), GLASS FILLED, UL94 V-0;  
     COLOR: BLACK  
     TERMINAL: PHOSPHOR BRONZE  
 2. FINISH:  
     TIN: 3.81 MICROMETERS/150 MICROINCHES MINIMUM TIN  
     OVER NICKEL UNDERPLATE OVERALL  
 3. TO BE USED WITH 24 AWG STRANDED WIRE WITH (1.35)/.053  
     DIAMETER MAXIMUM INSULATION  
 4. SEE TABLE FOR AVAILABLE CIRCUIT SIZES  
 5. STANDARD PACKAGING PER PK-70873-0001. OPTIONAL PACKAGING  
     MAY BE AVAILABLE, REQUEST DRAWING PK-70400  
 6. PARTS STACKABLE END TO END ON (2.54)/.100 CENTERS  
 7. PRODUCT SPECIFICATION: PS-70400  
 8. SEE DRAWING SDA-70400-\*\*\*\* (SHEET 3) FOR OPTIONAL  
     HOUSING DETAILS  
 9. 4 CIRCUIT SHOWN. 3-25 CIRCUITS HAVE 2 RIBS  
 10. TO MATE WITH MOLEX PART NUMBERS: A-70373-\*\*\*\*,  
     A-70375-\*\*\*\*, A-70389-\*\*\*\*, A-70391-\*\*\*\*,  
     A-70107-\*\*\*\*, A-70018-\*\*\*\*, A-70543-\*\*\*\*,  
     A-70553-\*\*\*\*, A-70541-\*\*\*\*, A-70551-\*\*\*\*,  
     A-70545-\*\*\*\*, A-70555-\*\*\*\*  
 11. 2 CIRCUIT ASSEMBLIES SUPPLIED AS GROUPED PAIRS



⌋

⌋

QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS	
			MM/IN			INCH	
		mm	INCH				
		4 PLACES ± ---	± ---	MSI BARRA	2010/10/19		
		3 PLACES ± ---	± .010				
	2 PLACES ± 0.25	± .014	WAZ	1984/10/09			
	1 PLACE ± 0.35	± ---					
	ANGULAR ± 1/2°		SMILLER	2010/11/24			
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE				
	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY T						

12 11 10 9 8 7 6 5 4 3 2 1