

F

E

D

C

B

A

F

E



D

C


B

A



POZI SLOT SHOWN
SLOTTED SCREW OPTIONAL



OPTIONAL IMPRINTING, 3.2 (1/8),
10A SHOWN, 11A REVERSED



- NOTES:
1. MATERIAL: SEE TABLE.
 2. FINISHES: SEE TABLE.
 3. PRODUCT SPECIFICATION: NOT REQUIRED.
 4. PACKAGING: NOT REQUIRED.
 5. MATES WITH: NONE.
 6. ALL FEATURES ARE TYPICAL UNLESS OTHERWISE NOTED.
 7. PART IS DESIGNED TO MEET UL 1059 CLASS C 300V, 60A.
 8. "XX" REFERS TO NUMBER OF CIRCUITS.
 9. FOR OPTIONAL IMPRINTING REFER TO SD-38120-005
 10. ASSEMBLY IS ROHS COMPLIANT.



SECTION Z-Z

7	XX	SCREW, M4 X .07 POZI-SLOT (-56 OPT)	ST. STEEL	TIN PLATE	UPDATE TERM. HEIGHT DIM. EC NO: WNA2009-0445 DRWN: JENC INAS 2009/07/01 CHKD: CYORK 2009/07/02 APPR: JMACNE IL 2009/07/02	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE		
6	XX	SCREW, M4 X 0.7 SLOTTED	BRONZE	TIN PLATE				MM/IN		3:2	INCH	PROJECTION		
5	XX	TERMINAL	COPPER	TIN PLATE				DRAWN BY DATE		TITLE 10.16MM/.400 SINGLE ROW BTS ASSY, 6 AWG, 300V 60A				
4	XX	CAGE	BRASS	NICKEL PLATE				R. STONE 2002/09/13						
3	XX	SCREW, M4 X .07 POZI-SLOT	BRONZE	TIN PLATE				CHECKED BY DATE						
2	1	COVER	POLYESTER (PBT)	BLACK				R. KEMP 2002/09/13						
1	1	BODY	POLYESTER (PBT)	BLACK				APPROVED BY DATE		MOLEX MOLEX INCORPORATED				
								L. ROTHHAUS 2002/09/27						
								ANGULAR ± 2 °		MATERIAL NO.		DOCUMENT NO.		SHEET NO.
								DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		SD-39970-003		1 OF 2
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH	REV	SIZE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION							

10	9	8	7	6	5	4	3	2	39970																																																																																																																																												
F									F																																																																																																																																												
E									E																																																																																																																																												
D									D																																																																																																																																												
C									C																																																																																																																																												
B									B																																																																																																																																												
A									A																																																																																																																																												
<table><tr><th>STD MATERIAL NUMBER</th><th>OPTIONAL 10A IMPRINT</th><th>OPTIONAL 11A IMPRINT</th><th>OPTIONAL SS SCREW (OPT. -56)</th><th>OPTIONAL SLOTTED SCREW</th><th>OPTIONAL SLOTTED SCREW W/10A IMPRINT</th><th>OPTIONAL SLOTTED SCREW W/11A IMPRINT</th><th>NUMBER OF CIRCUITS</th><th>"A" DIM.</th><th>"B" DIM.</th></tr><tr><td>399700102</td><td>399720102</td><td>399730102</td><td>399700602</td><td>399700402</td><td>399720402</td><td>399730402</td><td>2</td><td>21.84 [.86]</td><td>10.16 [.400]</td></tr><tr><td>399700103</td><td>399720103</td><td>399730103</td><td>399700603</td><td>399700403</td><td>399720403</td><td>399730403</td><td>3</td><td>32.00 [1.26]</td><td>20.32 [.800]</td></tr><tr><td>399700104</td><td>399720104</td><td>399730104</td><td>399700604</td><td>399700404</td><td>399720404</td><td>399730404</td><td>4</td><td>42.16 [1.66]</td><td>30.48 [1.200]</td></tr><tr><td>399700105</td><td>399720105</td><td>399730105</td><td>399700605</td><td>399700405</td><td>399720405</td><td>399730405</td><td>5</td><td>52.32 [2.06]</td><td>40.64 [1.600]</td></tr><tr><td>399700106</td><td>399720106</td><td>399730106</td><td>399700606</td><td>399700406</td><td>399720406</td><td>399730406</td><td>6</td><td>62.48 [2.46]</td><td>50.80 [2.000]</td></tr><tr><td>399700107</td><td>399720107</td><td>399730107</td><td>399700607</td><td>399700407</td><td>399720407</td><td>399730407</td><td>7</td><td>72.64 [2.86]</td><td>60.96 [2.400]</td></tr><tr><td>399700108</td><td>399720108</td><td>399730108</td><td>399700608</td><td>399700408</td><td>399720408</td><td>399730408</td><td>8</td><td>82.80 [3.26]</td><td>71.12 [2.800]</td></tr><tr><td>399700109</td><td>399720109</td><td>399730109</td><td>399700609</td><td>399700409</td><td>399720409</td><td>399730409</td><td>9</td><td>92.96 [3.66]</td><td>81.28 [3.200]</td></tr><tr><td>399700110</td><td>399720110</td><td>399730110</td><td>399700610</td><td>399700410</td><td>399720410</td><td>399730410</td><td>10</td><td>103.12 [4.06]</td><td>91.44 [3.600]</td></tr><tr><td>399700111</td><td>399720111</td><td>399730111</td><td>399700611</td><td>399700411</td><td>399720411</td><td>399730411</td><td>11</td><td>113.28 [4.46]</td><td>101.60 [4.000]</td></tr><tr><td>399700112</td><td>399720112</td><td>399730112</td><td>399700612</td><td>399700412</td><td>399720412</td><td>399730412</td><td>12</td><td>123.44 [4.86]</td><td>111.76 [4.400]</td></tr><tr><td>399700113</td><td>399720113</td><td>399730113</td><td>399700613</td><td>399700413</td><td>399720413</td><td>399730413</td><td>13</td><td>133.60 [5.26]</td><td>121.92 [4.800]</td></tr><tr><td>399700114</td><td>399720114</td><td>399730114</td><td>399700614</td><td>399700414</td><td>399720414</td><td>399730414</td><td>14</td><td>143.76 [5.66]</td><td>132.08 [5.200]</td></tr></table>										STD MATERIAL NUMBER	OPTIONAL 10A IMPRINT	OPTIONAL 11A IMPRINT	OPTIONAL SS SCREW (OPT. -56)	OPTIONAL SLOTTED SCREW	OPTIONAL SLOTTED SCREW W/10A IMPRINT	OPTIONAL SLOTTED SCREW W/11A IMPRINT	NUMBER OF CIRCUITS	"A" DIM.	"B" DIM.	399700102	399720102	399730102	399700602	399700402	399720402	399730402	2	21.84 [.86]	10.16 [.400]	399700103	399720103	399730103	399700603	399700403	399720403	399730403	3	32.00 [1.26]	20.32 [.800]	399700104	399720104	399730104	399700604	399700404	399720404	399730404	4	42.16 [1.66]	30.48 [1.200]	399700105	399720105	399730105	399700605	399700405	399720405	399730405	5	52.32 [2.06]	40.64 [1.600]	399700106	399720106	399730106	399700606	399700406	399720406	399730406	6	62.48 [2.46]	50.80 [2.000]	399700107	399720107	399730107	399700607	399700407	399720407	399730407	7	72.64 [2.86]	60.96 [2.400]	399700108	399720108	399730108	399700608	399700408	399720408	399730408	8	82.80 [3.26]	71.12 [2.800]	399700109	399720109	399730109	399700609	399700409	399720409	399730409	9	92.96 [3.66]	81.28 [3.200]	399700110	399720110	399730110	399700610	399700410	399720410	399730410	10	103.12 [4.06]	91.44 [3.600]	399700111	399720111	399730111	399700611	399700411	399720411	399730411	11	113.28 [4.46]	101.60 [4.000]	399700112	399720112	399730112	399700612	399700412	399720412	399730412	12	123.44 [4.86]	111.76 [4.400]	399700113	399720113	399730113	399700613	399700413	399720413	399730413	13	133.60 [5.26]	121.92 [4.800]	399700114	399720114	399730114	399700614	399700414	399720414	399730414	14	143.76 [5.66]	132.08 [5.200]
STD MATERIAL NUMBER	OPTIONAL 10A IMPRINT	OPTIONAL 11A IMPRINT	OPTIONAL SS SCREW (OPT. -56)	OPTIONAL SLOTTED SCREW	OPTIONAL SLOTTED SCREW W/10A IMPRINT	OPTIONAL SLOTTED SCREW W/11A IMPRINT	NUMBER OF CIRCUITS	"A" DIM.	"B" DIM.																																																																																																																																												
399700102	399720102	399730102	399700602	399700402	399720402	399730402	2	21.84 [.86]	10.16 [.400]																																																																																																																																												
399700103	399720103	399730103	399700603	399700403	399720403	399730403	3	32.00 [1.26]	20.32 [.800]																																																																																																																																												
399700104	399720104	399730104	399700604	399700404	399720404	399730404	4	42.16 [1.66]	30.48 [1.200]																																																																																																																																												
399700105	399720105	399730105	399700605	399700405	399720405	399730405	5	52.32 [2.06]	40.64 [1.600]																																																																																																																																												
399700106	399720106	399730106	399700606	399700406	399720406	399730406	6	62.48 [2.46]	50.80 [2.000]																																																																																																																																												
399700107	399720107	399730107	399700607	399700407	399720407	399730407	7	72.64 [2.86]	60.96 [2.400]																																																																																																																																												
399700108	399720108	399730108	399700608	399700408	399720408	399730408	8	82.80 [3.26]	71.12 [2.800]																																																																																																																																												
399700109	399720109	399730109	399700609	399700409	399720409	399730409	9	92.96 [3.66]	81.28 [3.200]																																																																																																																																												
399700110	399720110	399730110	399700610	399700410	399720410	399730410	10	103.12 [4.06]	91.44 [3.600]																																																																																																																																												
399700111	399720111	399730111	399700611	399700411	399720411	399730411	11	113.28 [4.46]	101.60 [4.000]																																																																																																																																												
399700112	399720112	399730112	399700612	399700412	399720412	399730412	12	123.44 [4.86]	111.76 [4.400]																																																																																																																																												
399700113	399720113	399730113	399700613	399700413	399720413	399730413	13	133.60 [5.26]	121.92 [4.800]																																																																																																																																												
399700114	399720114	399730114	399700614	399700414	399720414	399730414	14	143.76 [5.66]	132.08 [5.200]																																																																																																																																												
1b_frame_B_P_ME_T	9	8	7	6	5	4	3	2	1																																																																																																																																												
Rev. E 2006/04/15																																																																																																																																																					

SEE SHEET ONE

EC NO: WNA2009-0445

IT

DRWN: JENC INAS 2009/07/01

CHKD: CYORK 2009/07/02

APPR: JMAGNE IL 2009/07/02

REV

QUALITY SYMBOLS

▽=0

▽=0

DESCRIPTION

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± .005
2 PLACES	± 0.13	± .01
1 PLACE	± 0.3	± ---

ANGULAR ± 2 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE

MM/IN

DRAWN BY	DATE
R. STONE	2002/09/13
CHECKED BY	DATE
R. KEMP	2002/09/13
APPROVED BY	DATE
L. ROTHMAUS	2002/09/27

MATERIAL NO.

SEE CHART

SIZE

B

SCALE

3:2

DESIGN UNITS

INCH

THIRD ANGLE PROJECTION

TITLE

10.16MM/.400 SINGLE ROW
BTS ASSY, 6 AWG,
300V 60A

molex

MOLEX INCORPORATED

DOCUMENT NO.

SD-39970-003

SHEET NO.

2 OF 2

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION