

7. PRODUCT SPECIFICATION: PS-5556-001, PS-5556-002, PS-5556-003

C	ADD PS NOTE UCP2003-0385 8/30/2002 SAMIEC
B	REV 28-30 GA.DIM ECN *U40405 94-04-06 A.GUZIK
A2	ADDED EDP'S PER ECN U21527 GEP 10-15-92 RJF
A1	REVISED 28-30 AWG ECN U21318 9-3-92 RJF
A	FINAL RELEASE PER ECN U20768 6-12-92 RJF
LTR.	REVISIONS

	13	12	11	10	9	8	7	6	5558		4	3	2	1	
J	PART NO.	ENG. NO.	FORM	MAT'L	WIRE GAGE	RANGE OF INSULATION DIA.	QUANTITY PER REEL (FORMED)	DIM. "A"	DIM. "B"	DIM. "C"	DIM. "D"	DIM. "E"	DIM. "F"		
I	39-00-0120	5558-S	CHAIN	A	18-24 GA.	.051-.122 (1.30-3.10)	4,000	.075 (1.90)	.091 (2.30)	.020 (.50)	.142 (3.60)	.177 (4.50)	.035 (.90)		
	39-00-0121	5558-SL	LOOSE		22-28 GA.	.035-.071 (.90-1.80)	6,000	.071 (1.80)	.065 (1.65)	.016 (.40)	.091 (2.30)	.091 (2.30)	.024 (.60)		
	39-00-0122	5558-S2	CHAIN												
	39-00-0123	5558-S2L	LOOSE												
	39-00-0124	5558-S3	CHAIN		16 GA.	.122 (3.10) MAX.	4,000	.091 (2.30)	.106 (2.70)	.024 (.60)	.142 (3.60)	.177 (4.50)	.035 (.90)		
	39-00-0125	5558-S3L	LOOSE		14 GA.	.122 (3.10) MAX.	4,000	.091 (2.30)	.114 (2.90)	.024 (.60)	.142 (3.60)	.177 (4.50)	.035 (.90)		
	NOT TOOLED	5558-S4	CHAIN												
	NOT TOOLED	5558-S4L	LOOSE												
	39-00-0259	5558-S5	CHAIN		28-30 GA.	.020-.035 (.50-.90)	6,000	.050 (1.27)	.044 (1.12)	.010 (.25)	.091 (2.30)	.091 (2.30)	.024 (.60)		
H	39-00-0260	5558-S5L	LOOSE	B	18-24 GA.	.051-.122 (1.30-3.10)	4,000	.075 (1.90)	.091 (2.30)	.020 (.50)	.142 (3.60)	.177 (4.50)	.035 (.90)		
	39-00-0126	5558-PBS	CHAIN		22-28 GA.	.035-.071 (.90-1.80)	6,000	.071 (1.80)	.065 (1.65)	.016 (.40)	.091 (2.30)	.091 (2.30)	.024 (.60)		
	39-00-0127	5558-PBSL	LOOSE												
	39-00-0128	5558-PBS2	CHAIN												
	39-00-0129	5558-PBS2L	LOOSE		16 GA.	.122 (3.10) MAX.	4,000	.091 (2.30)	.106 (2.70)	.024 (.60)	.142 (3.60)	.177 (4.50)	.035 (.90)		
	39-00-0130	5558-PBS3	CHAIN		14 GA.	.122 (3.10) MAX.	4,000	.091 (2.30)	.114 (2.90)	.024 (.60)	.142 (3.60)	.177 (4.50)	.035 (.90)		
	39-00-0131	5558-PBS3L	LOOSE												
	NOT TOOLED	5558-PBS4	CHAIN												
	NOT TOOLED	5558-PBS4L	LOOSE		28-30 GA.	.020-.035 (.50-.90)	6,000	.050 (1.27)	.044 (1.12)	.010 (.25)	.091 (2.30)	.091 (2.30)	.024 (.60)		
G	39-00-0263	5558-PBS5	CHAIN												
	39-00-0264	5558-PBS5L	LOOSE												
F															
E															
D															
C															
B															
A															
	13	12	11	10	9	8	7	6	5	4	3	2	1		

LEGEND:

5558-***S**

BASE NO. _____
MATERIAL _____
BLANK= BRASS
PB= PHOS. BRONZE
S= TIN OVER NICKEL _____
CRIMP SIZE _____
BLANK = 18-24 AWG
2 = 22-28 AWG
3 = 16 AWG
4 = 14 AWG
5 = 28-30 AWG
CHAIN OR LOOSE _____
BLANK= CHAIN
L= LOOSE

DIMENSIONS SHOWN (METRIC) INCH		▽ = 0 ▼ = 0		REVISE ONLY ON CAD SYSTEM	
UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 1/2°		TITLE		MALE CRIMP TERMINAL WITH TIN OVER NICKEL POSTPLATE (MINI-FIT JR. SERIES)	
INCH METRIC		MOX MOLEX INCORPORATED		SHEET NO. 2 DATE 5/12/92	
3 PLACE ± --- ± ---		L15LEJLL 60932 U.S.A.		PART NO. SD-5558-***S**	
2 PLACE ± --- ± ---		SEE CHART.		DRWG. NO. CP C	
1 PLACE --- ± ---		FILE NAME 5558S5X2.DWG		REV. SIZE	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.		CP C	
DRWG. BY R.J.F.	CHKD. BY G.E.P.	SCALE --:--			
APP'D. BY RAS					

B	SEE SHEET I.
A2	SEE SHEET I.
A1	SEE SHEET I.
A	SEE SHEET I.

5558

A