

BDT64-A-B-C

SILICON DARLINGTON POWER TRANSISTORS

PNP epitaxial-base transistors in a monolithic Darlington circuit and housed in a TO-220 envelope. They are intended for output stages in audio equipment, general amplifiers, and analogue switching application.

NPN complements are BDT65-A-B-C

Compliance to RoHS.

ABSOLUTE MAXIMUM RATINGS

Symbol	Ratings		Value	Unit
V_{CBO}	Collector-Base Voltage	BDT64	-60	V
		BDT64A	-80	
		BDT64B	-100	
		BDT64C	-120	
V_{CEO}	Collector-Emitter Voltage	BDT64	-60	V
		BDT64A	-80	
		BDT64B	-100	
		BDT64C	-120	
V_{EBO}	Emitter-Base Voltage	BDT64	-5	V
		BDT64A		
		BDT64B		
		BDT64C		
I_C	Collector Current	BDT64	-12	A
		BDT64A		
		BDT64B		
		BDT64C		
I_{CM}	Collector Peak Current	BDT64	-20	A
		BDT64A		
		BDT64B		
		BDT64C		

BDT64-A-B-C

ABSOLUTE MAXIMUM RATINGS

Symbol	Ratings			Value	Unit	
I_B	Base Current		BDT64	-500	mA	
			BDT64A			
			BDT64B			
			BDT64C			
P_T	Power Dissipation	@ $T_{mb} < 25^\circ$	BDT64	125	Watts	
			BDT64A			
			BDT64B			
			BDT64C			
T_J	Junction Temperature		BDT64	150	$^\circ\text{C}$	
			BDT64A			
			BDT64B			
			BDT64C			
T_s	Storage Temperature range		BDT64	-65 to +150		
			BDT64A			
			BDT64B			
			BDT64C			

Limiting values in accordance with the Absolute Maximum System (IEC 134)

THERMAL CHARACTERISTICS

Symbol	Ratings	Value	Unit
R_{thj-c}	Thermal Resistance, Junction to Case	1	$^\circ\text{C}/\text{W}$

BDT64-A-B-C

ELECTRICAL CHARACTERISTICS

TC=25°C unless otherwise noted

Symbol	Ratings	Test Condition(s)		Min	Typ	Max	Unit
I _{CBO}	Collector Cutoff Current	I _E = 0 V _{CB} = -V _{CBO} max	BDT64	-	-	-0.4	mA
			BDT64A				
			BDT64B				
			BDT64C				
		I _E = 0 V _{CB} = -1/2 V _{CBO} max T _j = 150 °C	BDT64	-	-	-2	mA
			BDT64A				
			BDT64B				
			BDT64C				
I _{CEO}	Collector Cutoff Current	I _E = 0 V _{CE} = -1/2 V _{CEO} max	BDT64	-	-	-0.2	mA
			BDT64A				
			BDT64B				
			BDT64C				
I _{EBO}	Emitter Cutoff Current	V _{EB} = -5 V, I _C = 0	BDT64	-	-	-5	mA
			BDT64A				
			BDT64B				
			BDT64C				
V _{CEO}	Collector-Emitter Breakdown Voltage	I _C = -30 mA, I _B = 0	BDT64	-60	-	-	V
			BDT64A	-80	-	-	
			BDT64B	-100	-	-	
			BDT64C	-120	-	-	
V _{CE(SAT)}	Collector-Emitter saturation Voltage (*)	I _C = -5 A, I _B = -20 mA	BDT64	-	-	-2	V
			BDT64A				
			BDT64B				
			BDT64C				
		I _C = -10 A, I _B = -100 mA	BDT64	-	-	-3	
			BDT64A				
			BDT64B				
			BDT64C				

BDT64-A-B-C

ELECTRICAL CHARACTERISTICS

TC=25°C unless otherwise noted

Symbol	Ratings			Min	Typ	Max	Unit
$V_{BE(on)}$	Base-Emitter Voltage (*)	$I_C = -5\text{ A}$, $V_{CE} = -4\text{ V}$	BDT64	-	-	-2.5	V
			BDT64A				
			BDT64B				
			BDT64C				
V_{ECF}	C-E Diode Forward Voltage	$I_F = -5\text{ A}$	BDT64	-	-	-2	V
			BDT64A				
			BDT64B				
			BDT64C				
		$I_F = -12\text{ A}$	BDT64	-	-2	-	
			BDT64A				
			BDT64B				
			BDT64C				
h_{FE}	DC Current Gain (*)	$V_{CE} = -4\text{ V}$, $I_C = -1\text{ A}$	BDT64	-	1500	-	-
			BDT64A				
			BDT64B				
			BDT64C				
		$V_{CE} = -4\text{ V}$, $I_C = -5\text{ A}$	BDT64	1000	-	-	
			BDT64A				
			BDT64B				
			BDT64C				
		$V_{CE} = -4\text{ V}$, $I_C = -12\text{ A}$	BDT64	-	750	-	
			BDT64A				
			BDT64B				
			BDT64C				
C_{OB}	Output Capacitance	$I_E = 0$, $V_{CB} = -10\text{ V}$ $f_{test} = 1\text{ MHz}$	BDT64	-	200	-	pF
			BDT64A				
			BDT64B				
			BDT64C				

SWITCHING TIMES


Symbol	Ratings	Test Condition(s)	Min	Typ	Max	Unit
t_{on}	turn-on time	$I_C = -5\text{ A}$, $V_{CC} = -30\text{ V}$ $I_{B1} = -I_{B2} = -20\text{ mA}$	-	0.5	2	μs
t_{off}	turn-off time		-	2.5	5	

(*) Pulse Width $\approx 300\text{ }\mu\text{s}$, Duty Cycle $\angle 2.0\%$

BDT64-A-B-C

MECHANICAL DATA CASE TO-220

DIMENSIONS (mm)		
	Min.	Max.
A	9,90	10,30
B	15,65	15,90
C	13,20	13,40
D	6,45	6,65
E	4,30	4,50
F	2,70	3,15
G	2,60	3,00
H	15,75	17,15
L	1,15	1,40
M	3,50	3,70
N	-	1,37
P	0,46	0,55
R	2,50	2,70
S	4,98	5,08
T	2,49	2,54
U	0,70	0,90



Pin 1 :	Base
Pin 2 :	Collector
Pin 3 :	Emitter
Package	Collector

Revised August 2012

Information furnished is believed to be accurate and reliable. However, Comset Semiconductors assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may results from its use. Data are subject to change without notice. Comset Semiconductors makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Comset Semiconductors assume any liability arising out of the application or use of any product and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Comset Semiconductors' products are not authorized for use as critical components in life support devices or systems.