

2N2322 to 2N2326

SILICON THYRISTORS

All-diffused PNP thyristors designed for grating operation in mA/ μ A signal or detection circuits
Compliance to RoHS.

MAXIMUM RATINGS (*)

$T_J=125^{\circ}\text{C}$ unless otherwise noted, $R_{GK}=1000\Omega$

Symbol	Ratings	2N2322	2N2323	2N2324	2N2325	2N2326	Unit
$V_{RRM(REP)}$	Peak reverse blocking voltage (*)	25	50	100	150	200	V
$V_{RSM(NON-REP)}$	Non-repetitive peak blocking reverse voltage ($t<5.0$ ms)	40	75	150	225	300	V
$I_{T(RMS)}$	Forward Current RMS (all conduction angles)	1.6					A
I_{TSM}	Peak Surge Current (One-Half Cycle, 60Hz) No Repetition Until Thermal Equilibrium is Restored.	15					A
P_{GM}	Peak Gate Power – Forward	0.1					W
$P_{G(AV)}$	Average Gate Power - Forward	0.01					W
I_{GM}	Peak Gate Current – Forward	0.1					A
V_{GFM}	Peak Gate Voltage - Forward	6.0					V
V_{GRM}	Peak Gate Voltage - Reverse	6.0					V
T_J	Operating Junction Temperature Range	-65 to +125					$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range						

2n2322 to 2n2326

ELECTRICAL CHARACTERISTICS (*)

$T_J=25^{\circ}\text{C}$ unless otherwise noted, $R_{GK}=1000\Omega$

Symbol	Ratings		2N2322	2N2323	2N2324	2N2325	2N2326	Unit
V _{DRM}	Peak Forward Blocking Voltage (1)	Min :	25	50	100	150	200	V
I _{RRM}	Peak Reverse Blocking Current (Rated V _{DRM} , T _J =125°C)		Max : 100					μA
I _{DRM}	Peak Forward Blocking Current (Rated V _{DRM} , T _J =125°C)		Max : 100					μA
V _{TM}	Forward « on » Voltage I _{TM} =1.0 A Peak		Max : 1.5					V
	I _{TM} =3.14 A Peak T _C =85°C		Max : 2.0					
I _{GT}	Gate Trigger Current (2) Anode Voltage=6.0 Vdc R _L =100Ω		Max : 200					μA
	Anode Voltage=6.0 Vdc R _L =100Ω, T _C =-65°C		Max : 350					
V _{GT}	Gate Trigger Voltage Anode Voltage=6.0 V R _L =100Ω		Max : 0.8					V
	Anode Voltage=6.0 V R _L =100Ω, T _C =-65°C		Max : 1.0					
	V _{DRM} = Rated R _L =100Ω, T _J =125°C		Min : 0.1					
I _H	Holding Current Anode Voltage=6.0 V		Max : 2.0					mA
	Anode Voltage=6.0 V T _C =-65°C		Max : 3.0					
	Anode Voltage=6.0 V T _C =125°C		Min : 0.15					

(*) JEDEC Registered Values

(1) V_{RSM} and V_{DRM} can be applied for all types on a continuous dc basis without incurring damage.


(2) R_{GK} current is not included in measurement.

2n2322 to 2n2326

MECHANICAL DATA CASE TO-39

DIMENSIONS (mm)		
	min	max
A	8.50	9.39
B	7.74	8.50
C	6.09	6.60
D	0.40	0.53
E	-	0.88
F	2.41	2.66
G	4.82	5.33
H	0.71	0.86
J	0.73	1.02
K	12.70	-
L	42°	48°

Pin 1 :	kathode
Pin 2 :	Gate
Pin 3 :	Anode
Case :	anode



Revised October 2012

Information furnished is believed to be accurate and reliable. However, Comset Semiconductors assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may results from its use. Data are subject to change without notice. Comset Semiconductors makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Comset Semiconductors assume any liability arising out of the application or use of any product and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Comset Semiconductors' products are not authorized for use as critical components in life support devices or systems.