



NPN 2N3866

SILICON PLANAR EPITAXIAL TRANSISTORS

The 2N3866 are NPN transistors mounted in TO-39 metal package with the collector connected to the case .
They are intended for VHF-UHF class A, B or C amplifier circuits and oscillator applications.
Compliance to RoHS.

ABSOLUTE MAXIMUM RATINGS

Symbol	Ratings	Value	Unit
V_{CEO}	Collector-Emitter Voltage	30	V
V_{CES}	Collector-Emitter Voltage ($V_{BE} = 0$)	55	V
V_{EBO}	Emitter-Base Voltage	3.5	V
I_C	Collector Current	0.5	A
P_D	Total Power Dissipation @ $T_{case} = 25^\circ$	5	Watts
T_J	Junction Temperature	200	$^\circ C$
T_{Stg}	Storage Temperature range	-65 to +200	$^\circ C$

THERMAL CHARACTERISTICS

Symbol	Ratings	Value	Unit
R_{thJ-c}	Thermal Resistance, Junction-case	35	$^\circ C / W$

ELECTRICAL CHARACTERISTICS

TC=25 $^\circ C$ unless otherwise noted

Symbol	Ratings	Test Condition(s)	Min	Typ	Max	Unit
I_{CEO}	Collector Cutoff Current	$V_{CE}=28 V, I_B=0$	-	-	20	μA
$V_{CEO} (*)$	Collector Emitter Sustaining Voltage	$I_C=5 mA, I_B=0$	30	-	-	V
V_{CES}	Collector Base Breakdown Voltage	$I_C=100 \mu A, V_{BE}=0$	55	-	-	V
V_{EBO}	Emitter Base Breakdown Voltage	$I_E=100 \mu A, I_C=0$	3.5	-	-	V
$h_{FE} (*)$	DC Current Gain	$I_C=50 mA, V_{CE}=5 V$	10	-	200	-
		$I_C=360 mA, V_{CE}=5 V$	5	-	-	
$V_{CE(SAT)} (*)$	Collector-Emitter saturation Voltage	$I_C=100 mA, I_B=20 mA$	-	-	1	V

NPN 2N3866


Symbol	Ratings	Test Condition(s)	Min	Typ	Max	Unit
f_T	Transition Frequency	$I_C=50 \text{ mA}$, $V_{CE}=15 \text{ V}$ $f=200\text{MHz}$	500	-	-	MHz
C_{CB0}	Collector-Base Capacitance	$I_E=0$, $V_{CB}=-28 \text{ V}$ $f=1\text{MHz}$	-	-	3	pF
$P_o^{(**)}$	Output Power	$V_{CC}=-28\text{V}$ $P_i=100 \text{ mW}$ $f=400 \text{ MHz}$	1	-	-	pF
$\eta^{(**)}$	Collector Efficiency	$V_{CC}=-28\text{V}$, $P_o=1 \text{ W}$ $f=400 \text{ MHz}$	45	-	-	ps

(*) Pulse conditions : $t_p < 300 \mu\text{s}$, $\delta = 1\%$.

(**) See test circuit.

MECHANICAL DATA CASE TO-39

DIMENSIONS	
	mm
A	6,25
B	13,59
C	9,24
D	8,24
E	0,78
F	1,05
G	0,42
H	45°
L	4,1



Pin 1 :	Emitter
Pin 2 :	Base
Pin 3 :	Collector
Case :	Collector

Revised August 2012

Information furnished is believed to be accurate and reliable. However, Comset Semiconductors assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. Data are subject to change without notice. Comset Semiconductors makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Comset Semiconductors assume any liability arising out of the application or use of any product and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Comset Semiconductors' products are not authorized for use as critical components in life support devices or systems.