

N-Channel Enhancement Mode

Low Q_g and R_g

High dv/dt

Nanosecond Switching

50MHz Maximum Frequency

Symbol	Test Conditions	Maximum Ratings	
V_{DSS}	$T_J = 25^\circ\text{C to } 150^\circ\text{C}$	1000	V
V_{DGR}	$T_J = 25^\circ\text{C to } 150^\circ\text{C}; R_{GS} = 1\text{ M}\Omega$	1000	V
V_{GS}	Continuous	± 20	V
V_{GSM}	Transient	± 30	V
I_{D25}	$T_c = 25^\circ\text{C}$	12	A
I_{DM}	$T_c = 25^\circ\text{C}$, pulse width limited by T_{JM}	72	A
I_{AR}	$T_c = 25^\circ\text{C}$	12	A
E_{AR}	$T_c = 25^\circ\text{C}$	30	mJ
dv/dt	$I_S \leq I_{DM}$, $di/dt \leq 100\text{A}/\mu\text{s}$, $V_{DD} \leq V_{DSS}$, $T_J \leq 150^\circ\text{C}$, $R_G = 0.2\Omega$	5	V/ns
	$I_S = 0$	>200	V/ns
P_{DC}		940	W
P_{DHS}	$T_c = 25^\circ\text{C}$ Derate $3.7\text{W}/^\circ\text{C}$ above 25°C	425	W
P_{DAMB}	$T_c = 25^\circ\text{C}$	4.5	W
R_{thJC}		0.16	C/W
R_{thJHS}		0.35	C/W


Symbol	Test Conditions	Characteristic Values		
T _J = 25°C unless otherwise specified		min.	typ.	max.
V _{DSS}	V _{GS} = 0 V, I _D = 3 ma	1000		V
V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μa	4.0	4.7	5.5 V
I _{GSS}	V _{GS} = ±20 V _{DC} , V _{DS} = 0			±100 nA
I _{DSS}	V _{DS} = 0.8 V _{DSS} T _J = 25°C V _{GS} = 0 T _J = 125°C			50 μA 1 mA
R _{DS(on)}	V _{GS} = 15 V, I _D = 0.5I _{D25} Pulse test, t ≤ 300μS, duty cycle d ≤ 2%			1.05 Ω
g _{fs}	V _{DS} = 15 V, I _D = 0.5I _{D25} , pulse test		6.7	8.0 S
T _J		-55		+175 °C
T _{JM}			175	°C
T _{stg}		-55		+175 °C
T _L	1.6mm (0.063 in) from case for 10 s		300	°C
Weight			3	g

$$V_{DSS} = 1000\text{ V}$$

$$I_{D25} = 12\text{ A}$$

$$R_{DS(on)} \leq 1.05\text{ }\Omega$$

$$P_{DC} = 940\text{ W}$$



Features

- Isolated Substrate
 - high isolation voltage (>2500V)
 - excellent thermal transfer
 - Increased temperature and power cycling capability
- IXYS advanced low Q_g process
- Low gate charge and capacitances
 - easier to drive
 - faster switching
- Low $R_{DS(on)}$
- Very low insertion inductance (<2nH)
- No beryllium oxide (BeO) or other hazardous materials

Advantages

- Optimized for RF and high speed switching at frequencies to 50MHz
- Easy to mount—no insulators needed
- High power density

Symbol	Test Conditions	Characteristic Values		
(T _J = 25°C unless otherwise specified)		min.	typ.	max.
R_G			0.3	Ω
C_{iss}			2500	pF
C_{oss}	V _{GS} = 0 V, V _{DS} = 0.8 V _{DSS(max)} , f = 1 MHz		110	pF
C_{rss}			25	pF
C_{stray}	Back Metal to any Pin		33	pF
T_{d(on)}			5	ns
T_{on}	V _{GS} = 15 V, V _{DS} = 0.8 V _{DSS} I _D = 0.5 I _{DM}		3	ns
T_{d(off)}	R _G = 0.2 Ω (External)		5	ns
T_{off}			8	ns
Q_{g(on)}			77	nC
Q_{gs}	V _{GS} = 10 V, V _{DS} = 0.5 V _{DSS} I _D = 0.5 I _{D25}		16	nC
Q_{gd}			42	nC

Source-Drain Diode
Characteristic Values

(T_J = 25°C unless otherwise specified)

Symbol	Test Conditions	min.	typ.	max.
I_S	V _{GS} = 0 V			12 A
I_{SM}	Repetitive; pulse width limited by T _{JM}			72 A
V_{SD}	I _F = I _S , V _{GS} = 0 V, Pulse test, t ≤ 300 μs, duty cycle ≤ 2%			1.5 V
T_{rr}			200	ns
Q_{RM}	I _F = I _S , -di/dt = 100A/μs, V _R = 100V		0.6	μC
I_{RM}			7	A

CAUTION: Operation at or above the Maximum Ratings values may impact device reliability or cause permanent damage to the device.

Information in this document is believed to be accurate and reliable. IXYS RF reserves the right to make changes to information published in this document at any time and without notice.

For detailed device mounting and installation instructions, see the “*Device Installation & Mounting Instructions*” technical note on the IXYS RF web site at;

http://www.ixysrf.com/pdf/switch_mode/appnotes/7de_series_mosfet_installation_instructions.pdf

IXYS RF reserves the right to change limits, test conditions and dimensions.

IXYS RF MOSFETS are covered by one or more of the following U.S. patents:

4,835,592	4,860,072	4,881,106	4,891,686	4,931,844	5,017,508
5,034,796	5,049,961	5,063,307	5,187,117	5,237,481	5,486,715
5,381,025	5,640,045				

Fig. 1

Typical Transfer Characteristics

$V_{DS} = 100V$, $PW = 40\mu S$




Fig. 2

Typical Output Characteristics




Fig. 3

Gate Charge vs. Gate-to-Source Voltage

$V_{DS} = 500V$, $I_D = 6A$




Fig. 4

Extended Output Characteristics




Fig. 5

V_{DS} vs. Capacitance




Figure 1: Schematic diagram of the device structure. The top view shows a central channel (G) flanked by source (S) and drain (D) regions. Dimensions are provided in micrometers (μm) and millimeters (mm). The bottom view shows the cross-section of the device, including the gate (G) and source (S) regions, with dimensions in micrometers (μm) and millimeters (mm).

102N12A DE-SERIES SPICE Model

The DE-SERIES SPICE Model is illustrated in Figure 7. The model is an expansion of the SPICE level 3 MOSFET model. It includes the stray inductive terms L_G , L_S and L_D . R_d is the $R_{DS(ON)}$ of the device, R_{ds} is the resistive leakage term. The output capacitance, C_{OSS} , and reverse transfer capacitance, C_{RSS} are modeled with reversed biased diodes. This provides a varactor type response necessary for a high power device model. The turn on delay and the turn off delay are adjusted via R_{on} and R_{off} .




Figure 7 DE-SERIES SPICE Model

This SPICE model may be downloaded as a text file from the IXYSRF web site at

http://www.ixysrf.com/products/switch_mode.html

<http://www.ixysrf.com/spice/de375-102n12a.html>

Net List:

```
.SUBCKT 102N12A 10 20 30
```

```
* TERMINALS: D G S
```

```
* 1000 Volt 12 Amp 0.95 ohm N-Channel Power MOSFET
```

```
* REV.A 01-09-02
```

```
M1 1 2 3 3 DMOS L=1U W=1U
```

```
RON 5 6 0.3
```

```
DON 6 2 D1
```

```
ROF 5 7 .1
```

```
DOF 2 7 D1
```

```
D1CRS 2 8 D2
```

```
D2CRS 1 8 D2
```

```
CGS 2 3 2.5N
```

```
RD 4 1 0.95
```

```
DCOS 3 1 D3
```

```
RDS 1 3 5.0MEG
```

```
LS 3 30 .5N
```

```
LD 10 4 1N
```

```
LG 20 5 1N
```

```
.MODEL DMOS NMOS (LEVEL=3 VTO=3.0 KP=3.8)
```

```
.MODEL D1 D (IS=.5F CJO=1P BV=100 M=.5 VJ=.6 TT=1N)
```

```
.MODEL D2 D (IS=.5F CJO=400P BV=1000 M=.4 VJ=.6 TT=400N RS=10M)
```

```
.MODEL D3 D (IS=.5F CJO=900P BV=1000 M=.3 VJ=.4 TT=400N RS=10M)
```

```
.ENDS
```

Doc #9200-0249 Rev 6
 © 2009 IXYS RF