

Rectifier Diode Stud

Types W0438S/RX160 to M0334S/RX240

The data sheet on the subsequent pages of this document is a scanned copy of existing data for this product.

(Rating Report 80NR8 Issue 2)

This data reflects the old part number for this product which is: SW16-24PHN/R320. This part number must **NOT** be used for ordering purposes – please use the ordering particulars detailed below.

The limitations of this data are as follows:
Only S/RC outline drawing (W24) in datasheet
No reverse recovery data available

The following links will direct you to the appropriate outline drawings

[Outline W24](#) – ¾" ceramic stud
[Outline W26](#) – ¾" ceramic stud removed

Where any information on the product matrix page differs from that in the following data, the product matrix must be considered correct

An electronic data sheet for this product is presently in preparation.

For further information on this product, please contact your local ASM or distributor.

Alternatively, please contact Westcode as detailed below.

Ordering Particulars			
W0438	S/RX	◆◆	0
Fixed Type Code	S/RC - ¾" ceramic stud S/RD - ¾" ceramic stud removed	Voltage code V _{RRM} /100 16-24	Fixed Code
Typical Order Code: W0438SD180, Forward polarity, ¾" ceramic stud removed, 1800V V _{RRM}			

IXYS Semiconductor GmbH
Edisonstraße 15
D-68623 Lampertheim
Tel: +49 6206 503-0
Fax: +49 6206 503-627
E-mail: marcom@ixys.de

IXYS Corporation
3540 Bassett Street
Santa Clara CA 95054 USA
Tel: +1 (408) 982 0700
Fax: +1 (408) 496 0670
E-mail: sales@ixys.net

WESTCODE
An  IXYS Company

www.westcode.com

www.ixys.com

Westcode Semiconductors Ltd
Langley Park Way, Langley Park,
Chippenham, Wiltshire, SN15 1GE.
Tel: +44 (0)1249 444524
Fax: +44 (0)1249 659448
E-mail: WSL.sales@westcode.com

Westcode Semiconductors Inc
3270 Cherry Avenue
Long Beach CA 90807 USA
Tel: +1 (562) 595 6971
Fax: +1 (562) 595 8182
E-mail: WSI.sales@westcode.com

The information contained herein is confidential and is protected by Copyright. The information may not be used or disclosed except with the written permission of and in the manner permitted by the proprietors Westcode Semiconductors Ltd.

© Westcode Semiconductors Ltd.

In the interest of product improvement, Westcode reserves the right to change specifications at any time without prior notice.

Devices with a suffix code (2-letter, 3-letter or letter/digit/letter combination) added to their generic code are not necessarily subject to the conditions and limits contained in this report.

QUALITY EVALUATION LABORATORY

Rating Report: 80NR8 (Issue 2)

Date: 15th January, 1987

Origin:

Pages: 9

Diode Type SW16-24PHN/R320

Written by: *M/W Jmlyp*

Checked: *M/W Jmlyp*

Approved: *B. L. H.*

This diode consists of a diffused 24 mm diameter silicon slice mounted under spring pressure in a stud base, top hat housing with a flexible lead.

This Report supersedes Rating Report No. 80NR8 (Issue 1)

Ratings

Voltage Grades	: 16-24
V_{RSM}	: 1700-2500
V_{RRM}	: 1600-2400

I_F (AV); Single phase; 50 Hz, 180°C half sinewave; $T_{CASE} = 100^\circ C$: 320A

I_F (rms) max. : 595A

I_F d.c. max. : 595A

I_{FSM} : $t = 10$ ms half sinewave; T_J (initial) = 180°C ; $V_{RM} = 0.6V_{RRM}$ (MAX) : 4000A

I_{FSM} : $t = 10$ ms half sinewave; T_J (initial) = 180°C ; $V_{RM} = 10V$: 4400A

I^2_t : $t = 10$ ms; T_J (initial) = 180°C ; $V_{RM} = 0.6V_{RRM}$ (MAX) : $80 \times 10^3 A^2 S$

I^2_t : $t = 10$ ms; T_J (initial) = 180°C ; $V_{RM} = 10V$: $96.8 \times 10^3 A^2 S$

I^2_t : $t = 3$ ms; T_J (initial) = 180°C ; $V_{RM} = 10V$: $71.6 \times 10^3 A^2 S$

T_C Operating Range : -40 to +180°C

T_{stg} Non-operating : -40 to +200°C

Characteristics

(maximum values unless otherwise stated)

$V_D; T_J = 180^{\circ}\text{C}$	: 1.0V
$r_s; T_J = 180^{\circ}\text{C}$	: 0.835mohms
$V_{FM}; I_{FM} = 1000\text{A} \quad T_{VJ} = 180^{\circ}\text{C}$	: 1.835V
$R_{th(J-C)}$	: 0.15°C/W
	: 0.04°C/W
$R_{th(C-HS)}$	: 15mA
$I_{RRM} : T_J = 180^{\circ}\text{C} : V_{RM} = V_{RRM(Max)}$	:
$Q_{rr} (I_{FM} = \quad ; dI/dt = \quad)$	:
$t_{rr} (V_{RM} = 50\text{V}; T_{VJ} = \quad)$	: 2.5 - 2.77 Kg.f.m.
Mounting torque	: 100A280
Outline drawing	:
JEDEC Outline No.	:

CONTENTS

	<u>Page</u>
Ratings	1
Characteristics	2
Contents	3
Voltage Ratings	4
Dissipation and Case Temperature vs Mean Current	5
Limit Forward voltage Characteristics	6
Transient Thermal Impedance Characteristic	7
Surge Current and I^2t vs Duration of Surge	8
Outline Drawing	9



Changes to 80NR8 (Issue 1)


p1	V_{RWM} omitted
	T_C (operating range) MIN reduced to -40°C
p6	$I_F - V_F$ and $Z_{th} - t$ curves drawn on separate sheets


Voltage Ratings

Voltage Class	V_{RRM} V	V_{RSM} V
16	1600	1700
18	1800	1900
20	2000	2100
22	2200	2300
24	2400	2500

This Report is applicable to higher or lower voltage grades when supply has been agreed by Sales/Production.








320948

MAXIMUM NON REPETITIVE SURGE CURRENT AT INITIAL JUNCTION TEMPERATURE 180°C




SCALE	1/1
DRN	68
CHKD	
APPD	
S	A
S	NI

INTERNATIONAL OUTLINE No.
 WEIGHT. 250 GRAMS.
 FINISH. BRIGHT NICKEL PLATE.
 DEVICE MARKING INCLUDES MONOGRAM, TYPE No., SPEC.
 No. AND POLARITY SYMBOL.
 DEVICE MOUNTING:
 MOUNTING TORQUE TO BE
 27 - 24.5 Nm (2.77 - 2.5 kgf m).
 THREAD MUST NOT BE LUBRICATED.

DIODE TYPE NUMBER
 PHN/R 380
 PHN/R320
 PHN/R174

G.A. DRG. No. 102A216H04.




DRAWING IS SUPPLIED IN CONFIDENCE
 AND IS PROTECTED BY COPYRIGHT. THE
 INFORMATION MAY NOT BE DISCLOSED
 EXCEPT WITH THE WRITTEN PERMISSION
 OF AND IN MANNER PERMITTED BY THE
 PROPRIETORS, WESTINGHOUSE BRAKE
 AND SIGNAL CO. LTD.

WESTINGHOUSE BRAKE AND SIGNAL CO. LTD.
 CHIPPENHAM, WILTSHIRE, SN15 1JD, ENGLAND.



WESTCODE®
 SEMICONDUCTORS

THIRD ANGLE PROJECTION



DIMNS. IN MILLIMETRES

DRG. No.

100A280

ISS	REVISIONS
1	11.9.78
4	12.12.79 M806 REDRAWN. DRG. No. WAS 100A257.
5	27.11.84 11/218 FIN WAS ET