


FEATURES

- Max. propagation delay of 1300ps
- IEE min. of -63mA
- Industry standard 100K ECL levels
- Extended supply voltage option:
V_{EE} = -4.2V to -5.5V
- Voltage and temperature compensation for improved noise immunity
- Internal 75k Ω input pull-down resistors
- 70% faster than Fairchild
- 40% lower power than Fairchild
- Function and pinout compatible with Fairchild F100K
- Available in 28-pin PLCC packages

DESCRIPTION

The SY100S364 is a 16-input multiplexer designed for use in high-performance ECL systems. The four Data Select inputs (S₀, S₁, S₂, S₃) determine the bit from the 16 inputs (I_n) that will be passed on to the output as shown in the Truth Table. The output data polarity is the same as the input. The inputs on the device have 75k Ω pull-down resistors.

BLOCK DIAGRAM



Ordering Information



Part Number	Package Type	Operating Range	Package Marking	Lead Finish
SY100S364JC	J28-1	Commercial	SY100S364JC	Sn-Pb
SY100S364JCTR ⁽¹⁾	J28-1	Commercial	SY100S364JC	Sn-Pb
SY100S364JZ ⁽²⁾	J28-1	Commercial	SY100S364JZ with Pb-Free bar-line indicator	Matte-Sn
SY100S364JZTR ^(1, 2)	J28-1	Commercial	SY100S364JZ with Pb-Free bar-line indicator	Matte-Sn

1. Tape and Reel.
2. Pb-Free package is recommended for new designs.

TRUTH TABLE⁽¹⁾

Pin	Function
I ₀ – I ₁₅	Data Inputs
S ₀ – S ₃	Select Inputs
Z	Data Output
VEES	VEE Substrate
VCCA	VCCO for ECL Outputs

Select Inputs				Output
S ₀	S ₁	S ₂	S ₃	Z
L	L	L	L	l ₀
H	L	L	L	l ₁
L	H	L	L	l ₂
H	H	L	L	l ₃
L	L	H	L	l ₄
H	L	H	L	l ₅
L	H	H	L	l ₆
H	H	H	L	l ₇
L	L	L	H	l ₈
H	L	L	H	l ₉
L	H	L	H	l ₁₀
H	H	L	H	l ₁₁
L	L	H	H	l ₁₂
H	L	H	H	l ₁₃
L	H	H	H	l ₁₄
H	H	H	H	l ₁₅

1. H = HIGH Voltage Level
L = LOW Voltage Level

DC ELECTRICAL CHARACTERISTICS

$V_{EE} = -4.2V$ to $-5.5V$ unless otherwise specified; $V_{CC} = V_{CCA} = GND$


Symbol	Parameter	Min.	Typ.	Max.	Unit	Condition
I_{IH}	Input HIGH Current				μA	$V_{IN} = V_{IH} (Max.)$
	I_{in}	—	—	200		
	S_0, S_1	—	—	200		
	S_2, S_3	—	—	200		
I_{EE}	Power Supply Current	-63	-45	-30	mA	Inputs Open

AC ELECTRICAL CHARACTERISTICS

$V_{EE} = -4.2V$ to $-5.5V$ unless otherwise specified; $V_{CC} = V_{CCA} = GND$

Symbol	Parameter	$T_A = 0^\circ C$		$T_A = +25^\circ C$		$T_A = +85^\circ C$		Unit	Condition
		Min.	Max.	Min.	Max.	Min.	Max.		
t_{PLH} t_{PHL}	Propagation Delay $I_0 - I_{15}$ to Output	400	1300	400	1300	400	1300	ps	
t_{PLH} t_{PHL}	Propagation Delay S_0, S_1 to Output	400	1800	400	1800	400	1800	ps	
t_{PLH} t_{PHL}	Propagation Delay S_2, S_3 to Output	400	1600	400	1600	400	1600	ps	
t_{TLH} t_{THL}	Transition Time 20% to 80%, 80% to 20%	300	900	300	900	300	900	ps	

TIMING DIAGRAM





Propagation Delay and Transition Times

Note:

$V_{EE} = -4.2V$ to $-5.5V$ unless otherwise specified; $V_{CC} = V_{CCA} = GND$

28-PIN PLCC (J28-1)



NOTES:

1. DIMENSIONS ARE IN INCHES [MM].
2. CONTROLLING DIMENSION: INCHES.
3. DIMENSION DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS, EITHER OF WHICH SHALL NOT EXCEED 0.008 [0.203].
4. LEAD DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION.
5. MAXIMUM AND MINIMUM SPECIFICATIONS ARE INDICATED AS FOLLOWS: MAX/MIN
6. PACKAGE TOP DIMENSION MAY BE SLIGHTLY SMALLER THAN BOTTOM DIMENSION.

Rev. A

MICREL, INC. 2180 FORTUNE DRIVE SAN JOSE, CA 95131 USA

TEL + 1 (408) 944-0800 FAX + 1 (408) 474-1000 WEB <http://www.micrel.com>

The information furnished by Micrel in this datasheet is believed to be accurate and reliable. However, no responsibility is assumed by Micrel for its use. Micrel reserves the right to change circuitry and specifications at any time without notification to the customer.

Micrel Products are not designed or authorized for use as components in life support appliances, devices or systems where malfunction of a product can reasonably be expected to result in personal injury. Life support devices or systems are devices or systems that (a) are intended for surgical implant into the body or (b) support or sustain life, and whose failure to perform can be reasonably expected to result in a significant injury to the user. A Purchaser's use or sale of Micrel Products for use in life support appliances, devices or systems is at Purchaser's own risk and Purchaser agrees to fully indemnify Micrel for any damages resulting from such use or sale.

© 2006 Micrel, Incorporated.