



Precision, High-Bandwidth Op Amp

MAX9622

General Description

The MAX9622 op amp features rail-to-rail output and 50MHz GBW at just 1mA supply current. At power-up, this device autocalibrates its input offset voltage to less than 100 μ V. It operates from a single-supply voltage of 2.0V to 5.25V.

The MAX9622 is available in a tiny 2mm x 2mm, 5-pin SC70 package and is rated over the -40°C to +125°C automotive temperature range.

Features

- ◆ 50MHz UGBW
- ◆ Low Input Voltage Offset Voltage (100 μ V max)
- ◆ Input Common-Mode Voltage Range Extends Below Ground
- ◆ Wide 2.0V to 5.25V Supply Range
- ◆ Low 1mA Supply Current

Applications


Power Modules
Automotive Power Supplies
ADC Drivers for Industrial Systems
Instrumentation
Filters

Ordering Information

PART	TEMP RANGE	PIN-PACKAGE	TOP MARK
MAX9622AXK+T	-40°C to +125°C	5 SC70	AUA

+ Denotes a lead(Pb)-free/RoHS-compliant package.
T = Tape and reel.

Typical Application Circuit



USING THE MAX9622 AS A LOWPASS BESSEL FILTER (CORNER FREQUENCY = 100kHz).

Precision, High-Bandwidth Op Amp

ABSOLUTE MAXIMUM RATINGS

Supply Voltage (V_{CC} to GND).....-0.3V to +5.5V
 All Other Pins.....(GND - 0.3V) to (V_{CC} + 0.3V)
 Short-Circuit Duration to GND or V_{CC} 1s
 Continuous Input Current (any pins)..... ± 20 mA
 Thermal Limits (Note 1)
 Continuous Power Dissipation ($T_A = +70^\circ\text{C}$)
 5-Pin SC70 (derate 3.1mW/ $^\circ\text{C}$ above $+70^\circ\text{C}$) 245.4mW

Operating Temperature Range..... -40°C to $+125^\circ\text{C}$
 Junction Temperature $+150^\circ\text{C}$
 Storage Temperature Range..... -65°C to $+150^\circ\text{C}$
 Lead Temperature (soldering, 10s) $+300^\circ\text{C}$
 Soldering Temperature (reflow) $+260^\circ\text{C}$

Note 1: Package thermal resistances were obtained using the method described in JEDEC specification JESD51-7, using a four-layer board. For detailed information on package thermal considerations, refer to www.maxim-ic.com/thermal-tutorial.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS

($V_{CC} = 5\text{V}$, $V_{IN+} = V_{IN-} = 0\text{V}$, $R_L = 10\text{k}\Omega$ to $V_{CC}/2$, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$, unless otherwise noted. Typical values are at $T_A = +25^\circ\text{C}$.) (Note 2)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
POWER SUPPLY						
Supply Voltage Range	V_{CC}	Guaranteed by PSRR	2		5.25	V
Supply Current	I_{CC}	No load		1	1.5	mA
		$-40^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$			2.1	
Power-Supply Rejection Ratio	PSRR	$T_A = +25^\circ\text{C}$	97	126		dB
		$-40^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$	93			
Power-Up Time	t_{ON}			3		ms
DC SPECIFICATIONS						
Input Offset Voltage	V_{OS}	After power-up autocalibration		8	100	μV
		$-40^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$		8	3000	
Input Offset Voltage Drift	ΔV_{OS}			3		$\mu\text{V}/^\circ\text{C}$
Input Bias Current	I_B	$T_A = +25^\circ\text{C}$		62	150	nA
		$-40^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$			320	
Input Offset Current	I_{OS}	$T_A = +25^\circ\text{C}$		3	12	nA
		$-40^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$			30	
Input Common-Mode Range	V_{CM}	Guaranteed by CMRR, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$	-0.1		$V_{CC} - 1.3$	V
Common-Mode Rejection Ratio	CMRR	$T_A = +25^\circ\text{C}$	87	121		dB
		$-40^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$	80			
Large-Signal Gain	A_{VOL}	$400\text{mV} \leq V_{OUT} \leq V_{CC} - 400\text{mV}$		$T_A = +25^\circ\text{C}$	91	dB
				$-40^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$	84	
		$400\text{mV} \leq V_{OUT} \leq V_{CC} - 400\text{mV}$, $R_L = 1\text{k}\Omega$ to $V_{CC}/2$		$T_A = +25^\circ\text{C}$	77	
				$-40^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$	69	
Output Voltage Swing	$V_{OH} - V_{CC}$	$R_L = 10\text{k}\Omega$ to $V_{CC}/2$			60	mV
	V_{OL}	$R_L = 10\text{k}\Omega$ to $V_{CC}/2$			60	
		$R_L = 10\text{k}\Omega$ to GND, $T_A = +25^\circ\text{C}$			40	
		$R_L = 10\text{k}\Omega$ to GND			48	
Short-Circuit Current	I_{SC}	(Note 3)		80		mA

Precision, High-Bandwidth Op Amp

ELECTRICAL CHARACTERISTICS (continued)

($V_{CC} = 5V$, $V_{IN+} = V_{IN-} = 0V$, $R_L = 10k\Omega$ to $V_{CC}/2$, $T_A = -40^\circ C$ to $+125^\circ C$, unless otherwise noted. Typical values are at $T_A = +25^\circ C$.) (Note 2)







PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
AC SPECIFICATIONS						
Gain-Bandwidth Product	GBW			50		MHz
Large-Signal Bandwidth	BW _{LS}	$V_{OUT} = 2V_{P-P}$		3		MHz
Slew Rate	SR	$V_{OUT} = 2V_{P-P}$, 10% to 90%		20		V/ μs
Settling Time	t_S	To 0.1%, $V_{OUT} = 2V_{P-P}$, $C_L = 10pF$		200		ns
Total Harmonic Distortion	THD	$f = 10kHz$, $V_{OUT} = 2V_{P-P}$		90		dB
Input Voltage Noise Density	E_N	$f = 10kHz$		13		$nV/\sqrt{Hz}$
Input Current Noise Density	I_N	$f = 10kHz$		3		$pA/\sqrt{Hz}$

Note 2: The device is 100% production tested at $T_A = +25^\circ C$. Temperature limits are guaranteed by design.

Note 3: Guaranteed by design.

Typical Operating Characteristics

($V_{CC} = 5V$, $R_L = 10k\Omega$ to $V_{CC}/2$, $T_A = +25^\circ C$, unless otherwise noted.)




Precision, High-Bandwidth Op Amp


Typical Operating Characteristics (continued)

($V_{CC} = 5V$, $R_L = 10k\Omega$ to $V_{CC}/2$, $T_A = +25^\circ C$, unless otherwise noted.)


**OUTPUT HIGH VOLTAGE vs. TEMPERATURE
SOURCING CURRENT ($V_{CC} - V_{OUT}$)**




**OUTPUT LOW VOLTAGE vs. TEMPERATURE
SINKING CURRENT**




INPUT BIAS CURRENT vs. TEMPERATURE




**INPUT BIAS CURRENT
vs. TEMPERATURE**




**COMMON-MODE REJECTION RATIO
vs. FREQUENCY**




**POWER-SUPPLY REJECTION RATIO
vs. FREQUENCY**




0.01Hz TO 10Hz INPUT VOLTAGE NOISE



INPUT VOLTAGE NOISE vs. FREQUENCY



INPUT CURRENT NOISE vs. FREQUENCY




Precision, High-Bandwidth Op Amp


Typical Operating Characteristics (continued)

($V_{CC} = 5V$, $R_L = 10k\Omega$ to $V_{CC}/2$, $T_A = +25^\circ C$, unless otherwise noted.)


TURN-ON RESPONSE
 $V_{IN} = 22.34mV$, $A_V = 100V/V$




QUIESCENT CURRENT vs. TEMPERATURE
 $V_{CC} = 5V$, V_{OUT} IN SATURATION




OUTPUT RECOVERY FROM SATURATION
 V_{OUT} SATURATED TO POSITIVE RAIL




OUTPUT RECOVERY FROM SATURATION
 V_{OUT} SATURATED TO NEGATIVE RAIL



TOTAL HARMONIC DISTORTION
PLUS NOISE vs. FREQUENCY



OPEN-LOOP GAIN vs. FREQUENCY




Precision, High-Bandwidth Op Amp


Typical Operating Characteristics (continued)

($V_{CC} = 5V$, $R_L = 10k\Omega$ to $V_{CC}/2$, $T_A = +25^\circ C$, unless otherwise noted.)


LARGE-SIGNAL RESPONSE




SMALL-SIGNAL RESPONSE




CAPACITIVE LOADING STABILITY vs. ISOLATION RESISTANCE, $A_V = 1V/V$



PARALLEL CAPACITIVE LOADING




CROSSTALK vs. FREQUENCY



Precision, High-Bandwidth Op Amp

MAX9622

Pin Configuration



Pin Description

PIN	NAME	FUNCTION
1	IN+	Positive Input
2	GND	Ground
3	IN-	Negative Input
4	OUT	Output
5	VCC	Positive Power Supply. Bypass with a 0.1μF capacitor to ground.

Precision, High-Bandwidth Op Amp

Detailed Description

The MAX9622 is a power-efficient, high-speed op amp ideal for capturing fast edges in a wide variety of signal processing applications.

It precisely calibrates its VOS on power-up to eliminate the effects of package stresses, power supplies, and temperature.

Applications Information

Power-Up Autotrim

The MAX9622 features power-up autotrimming that allows the devices to achieve less than 100 μ V of input offset voltage. The startup sequence takes approximately 4ms to complete after the supply voltage exceeds an internal threshold of 1.8V. During this time, the inputs and outputs are connected to an auxiliary amplifier that has an input offset of 5mV (typ). As soon as the autotrimming is completed, the inputs and outputs switch from the auxiliary amplifier to the calibrated amplifier. The calibration settings hold until the supply voltage drops below an internal threshold of 1.4V. This could be used to recalibrate the amplifier. The supply current of the part increases to about 2.5mA during the power-up autotrim period. Use good supply decoupling with low ESR capacitors.

Active Filters

The MAX9622 is ideal for a wide variety of active filter circuits that make use of their wide output voltage swings and large bandwidth capabilities. The *Typical Application Circuit* shows a multiple feedback active filter circuit example with a 100kHz corner frequency. At low frequencies, the amplifier behaves like a simple low-distortion inverting amplifier gain = -1, while its high bandwidth gives excellent stopband attenuation above its corner frequency. See the *Typical Application Circuit*.

Input Differential Voltage Protection

During normal op-amp operation, the inverting and non-inverting inputs of the MAX9622 are at essentially the same voltage. However, either due to fast input voltage transients or due to loss of negative feedback, these pins can be forced to different voltages. Internal back-to-back diodes and series resistors protect input-stage transistors from large input differential voltages (see Figure 2). IN+ and IN- can survive any voltage between the power-supply rails.

This op amp has been designed to exhibit no phase inversion to overdriven inputs.




Figure 1. Autotrim Timing Diagram




Figure 2. Input Protection Circuit


Precision, High-Bandwidth Op Amp

Package Information

For the latest package outline information and land patterns, go to www.maxim-ic.com/packages. Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.

PACKAGE TYPE	PACKAGE CODE	OUTLINE NO.	LAND PATTERN NO.
5 SC70	X5+1	21-0076	90-0188

MAX9622



SC70, 5LEPS

Precision, High-Bandwidth Op Amp

MAX9622

Revision History

REVISION NUMBER	REVISION DATE	DESCRIPTION	PAGES CHANGED
0	9/10	Initial release	—

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

10 **Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600**

© 2010 Maxim Integrated Products

Maxim is a registered trademark of Maxim Integrated Products, Inc.