

**MMBZ5223BW-
MMBZ5259BW**

SURFACE MOUNT ZENER DIODE

VOLTAGE RANGE 2.7 to 39 Volts POWER RATING 200 mWatts



FEATURES

- * Planar Die Construction
- * 200mW Power Dissipation on FR-4 PCB
- * General purpose, Medium Current
- * Ideally Suited for Automated Assembly

MECHANICAL DATA

- * Case: Molded plastic
- * Epoxy: UL 94V-O rate flame retardant
- * Lead: MIL-STD-202E method 208C guaranteed
- * Mounting position: Any
- * Weight: 0.006 gram

SOT-323



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.

MAXIMUM RATINGS (@ TA = 25°C unless otherwise noted)

RATINGS	SYMBOL	VALUE	UNITS
Max. Steady State Power Dissipation @TA=25°C (Note 1)	P _D	200	mW
Max. Operating Temperature Range	T _J	-65 to +150	°C
Storage Temperature Range	T _{STG}	-65 to +150	°C

ELECTRICAL CHARACTERISTICS (@ TA = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	MIN.	TYP.	MAX.	UNITS
Thermal Resistance Junction to Ambient (Note 1)	R _{θJA}	-	-	625	°C/W
Max. Instantaneous Forward Voltage at I _F = 10mA	V _F	-	-	0.9	Volts

Note 1. Valid provided that device terminals are kept at ambient temperature.

2008-12
REV: A

ELECTRICAL CHARACTERISTICS (@TA=25°C unless otherwise specified)

TYPE	Zener voltage Range (Note 1) Vz (V) @ IZT			Test current IZT (mA)	Maximum Zener impedance			Maximum reverse leakage current	
	Nom	Min	Max		ZZT at IZT (W)	ZZK (W)	at Izk (mA)	IR (uA)	at VR (V)
	Volts	Volts	Volts						
MMBZ5223BW	2.7	2.57	2.84	20	30	1300	0.25	75	1.0
MMBZ5225BW	3.0	2.85	3.15	20	30	1600	0.25	50	1.0
MMBZ5226BW	3.3	3.14	3.47	20	28	1600	0.25	25	1.0
MMBZ5227BW	3.6	3.42	3.78	20	24	1700	0.25	15	1.0
MMBZ5228BW	3.9	3.71	4.10	20	23	1900	0.25	10	1.0
MMBZ5229BW	4.3	4.09	4.52	20	22	2000	0.25	5.0	1.0
MMBZ5230BW	4.7	4.47	4.94	20	19	1900	0.25	5.0	2.0
MMBZ5231BW	5.1	4.85	5.36	20	17	1600	0.25	5.0	2.0
MMBZ5232BW	5.6	5.32	5.88	20	11	1600	0.25	5.0	3.0
MMBZ5234BW	6.2	5.89	6.51	20	7	1000	0.25	5.0	4.0
MMBZ5235BW	6.8	5.89	7.14	20	5	750	0.25	3.0	5.0
MMBZ5236BW	7.5	6.46	7.88	20	6	500	0.25	3.0	6.0
MMBZ5237BW	8.2	7.13	8.61	20	8	500	0.25	3.0	6.5
MMBZ5239BW	9.1	7.79	9.56	20	10	600	0.25	3.0	7.0
MMBZ5240BW	10	8.65	10.50	20	17	600	0.25	3.0	8.0
MMBZ5241BW	11	9.50	11.55	20	22	600	0.25	2.0	8.4
MMBZ5242BW	12	10.45	12.60	20	30	600	0.25	1.0	9.1
MMBZ5243BW	13	11.40	13.65	9.5	13	600	0.25	0.5	9.9
MMBZ5245BW	15	12.35	15.75	8.5	16	600	0.25	0.1	11
MMBZ5246BW	16	14.25	16.80	7.8	17	600	0.25	0.1	12
MMBZ5248BW	18	15.20	18.90	7.0	21	600	0.25	0.1	14
MMBZ5250BW	20	17.10	21.00	6.2	25	600	0.25	0.1	15
MMBZ5251BW	22	19.00	23.10	5.6	29	600	0.25	0.1	17
MMBZ5252BW	24	20.90	25.20	5.2	33	600	0.25	0.1	18
MMBZ5254BW	27	22.80	28.35	5.0	41	600	0.25	0.1	21
MMBZ5255BW	28	25.65	29.40	4.5	44	600	0.25	0.1	21
MMBZ5256BW	30	28.50	31.50	4.2	49	600	0.25	0.1	23
MMBZ5257BW	33	31.35	34.65	3.8	58	700	0.25	0.1	25
MMBZ5258BW	36	34.20	37.80	3.4	70	700	0.25	0.1	27
MMBZ5259BW	39	37.05	40.95	3.2	80	800	0.25	0.1	30

Note 1. Tested with pulses, $T_p \leq 1.0\text{ms}$.

RATING AND CHARACTERISTICS CURVES (MMBZ5223BW-MMBZ5259BW)




Figure 1 Power Dissipation vs Ambient Temperature




Figure 2 Total Capacitance vs Nominal Zener Voltage




Figure 3 Zener Voltage vs Zener Impedance




Figure 4 Maximum Non-repetitive Surge Power




Figure 5 Zener Breakdown Characteristics




Figure 6 Zener Breakdown Characteristics

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.