

120X120X25 mm

JF1225-00 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JF1225B1UR00	B, H	12	10.2 ~ 13.8	100.50	0.269	3000	0.50	6.00	0.50	45.7	195
JF1225B1SR00	B, H			89.87	0.224	2700	0.37	4.44	0.37	42.8	
JF1225-1H-00	B, H, S			80.11	0.186	2400	0.25	3.00	0.30	39.5	
JF1225-1M-00	B, H, S			69.57	0.147	2100	0.20	2.40	0.25	36.3	
JF1225-1L-00	B, H, S			59.57	0.111	1800	0.14	1.68	0.20	32.4	
JF1225-1E-00	B, H, S			47.88	0.078	1500	0.10	1.20	0.12	27.4	
JF1225B2UR00	B, H	24	20.4 ~ 27.6	100.50	0.269	3000	0.28	6.72	0.28	45.7	
JF1225B2SR00	B, H			89.87	0.224	2700	0.21	5.04	0.21	42.8	
JF1225-2H-00	B, H, S			80.11	0.186	2400	0.20	4.80	0.25	39.5	
JF1225-2M-00	B, H, S			69.57	0.147	2100	0.14	3.36	0.20	36.3	
JF1225-2L-00	B, H, S			59.57	0.111	1800	0.11	2.64	0.15	32.4	
JF1225-2E-00	B, H, S			47.88	0.078	1500	0.08	1.92	0.10	27.4	
JF1225B4UR00	Dual Ball	48	40.8 ~ 60.0	100.50	0.269	3000	0.14	6.72	0.14	45.7	
JF1225B4SR00				89.87	0.224	2700	0.12	5.76	0.12	42.8	
JF1225B4HR00				80.11	0.186	2400	0.10	4.80	0.10	39.5	
JF1225B4MR00				69.57	0.147	2100	0.08	3.84	0.08	36.3	
JF1225B4LR00				59.57	0.111	1800	0.07	3.36	0.07	32.4	
JF1225B4ER00				47.88	0.078	1500	0.06	2.88	0.06	27.4	

Specifications subject to change without notice

The 7TH character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM". Please contact us for detail if your request bearing system is not shown in the above list.

