



- Low Insertion Loss
- 5.0 X 5.0 mm Surface-mount Case
- Single-ended Input and Output
- Complies with Directive 2002/95/EC (RoHS)




SF2091C

**385.00 MHz
SAW Filter**

Absolute Maximum Ratings

Rating	Value	Units
Maximum Incident Power in Passband	+13	dBm
Maximum DC Voltage on any Non-ground Terminal	30	VDC
Storage Temperature Range in Tape and Reel	-40 to +85	°C
Suitable for Lead-free Soldering - Maximum Soldering Temperature	260 °C for 30 s	



SM5050-8

Electrical Characteristics

Characteristic	Sym	Notes	Min	Typ	Max	Units
Nominal Center Frequency	f_C	1		385.00		MHz
Insertion Loss	IL_{MAX}	1			12	dB
1.2 dB Bandwidth	$BW_{1.2}$	1	30	32		MHz
Amplitude Ripple, $f_C \pm 15$ MHz, within Adjacent 5 MHz Windows		1			1	dB _{p-p}
Group Delay Deviation, $f_C \pm 15$ MHz, within Adjacent 5 MHz Windows		1			50	ns _{p-p}
Group Delay Deviation, $f_C \pm 15$ MHz, full bandwidth		1		305		ns _{p-p}
VSWR at f_C		1			2.5:1	
Group Delay, $f_C \pm 15$ MHz		1		305		ns
40 dB Rejection Bandwidth		1, 2			65	MHz
Operating Temperature Range			-40		85	°C
Case Style		SM5050-8 5 x 5 mm Nominal Footprint				
Lid Symbolization (Y=year, WW=week, S=shift)		RFM 593 YWWS				

Electrical Connections

Connection		Terminals
Port 1	Input	1
Port 2	Output	5
	Ground	All others
Dot indicates Pin 1		




CAUTION: Electrostatic Sensitive Device. Observe precautions for handling.

Notes:



1. Unless noted otherwise, all specifications apply over the operating temperature range with filter soldered to the specified demonstration board with impedance matching to 50 Ω and measured with 50 Ω network analyzer.
2. Rejection is measured as attenuation below the minimum IL point in the passband. Rejection in final user application is dependent on PCB layout and external impedance matching design. See Application Note No. 42 for details.
3. The design, manufacturing process, and specifications of this filter are subject to change.
4. Tape and Reel Standard ANSI / EIA 481.
5. Either Port 1 or Port 2 may be used for either input or output in the design. However, impedances and impedance matching may vary between Port 1 and Port 2, so that the filter must always be installed in one direction per the circuit design.
6. US and international patents may apply.
7. RFM, stylized RFM logo, and RF Monolithics, Inc. are registered trademarks of RF Monolithics, Inc.

18 Nov 2005 16:11:28

CH1 S11 1 UFS
1: 36.736 Ω 13.063 Ω 5.3999 nH
385.000 000 MHz
hp sf2091c




CH3 S22 1 UFS
1: 41.326 Ω 14.670 Ω 6.0644 nH
385.000 000 MHz




CH2 Markers
Max Δ REF=1
34.092049 MHz
cent : 385.259820 MHz
Q: 11.301
1 loss : -9.1736 dB


18 Nov 2005 16:14:40




CH1 Markers
Δ REF=2
mean : 303 . 07 ns
s . dev : 8 . 1164 ns
p-p : 29 . 840 ns




CH3 Markers
Δ REF=2
mean : -9 . 6368 dB
s . dev : . 20680 dB
p-p : . 91380 dB



use RFM 400-1624-001 demo board
0603 Coilcraft inductor
0603 capacitor



1.590 REF.



DRILL ALL HOLES #76 DRILL (0.020)
ALL HOLES ARE PLATED THRU.

SM5050-8 Surface-Mount 8-Terminal Ceramic Case


5.0 X 5.0 mm Nominal Footprint

Case Dimensions


Dimension	mm			Inches		
	Min	Nom	Max	Min	Nom	Max
A	4.80	5.00	5.20	0.189	0.197	0.205
B	4.80	5.00	5.20	0.189	0.197	0.205
C	1.30	1.50	1.70	0.050	0.060	0.067
D	1.98	2.08	2.18	0.078	0.082	0.086
E	1.07	1.17	1.27	0.042	0.046	0.050
F	0.50	0.64	0.70	0.020	0.025	0.028
G	2.39	2.54	2.69	0.094	0.100	0.106
H		1.27			0.050	
I		0.76			0.030	
J		1.55			0.061	
K		2.79			0.110	
L		0.76			0.030	
M		2.36			0.093	
N		1.55			0.061	
O		2.79			0.110	
P		2.79			0.110	
Q		2.79			0.110	

Case Materials


Materials	
Solder Pad Plating	0.3 to 1.0 μ m Gold over 1.27 to 8.89 μ m Nickel
Lid Plating	2.0 to 3.0 μ m Nickel
Body	Al ₂ O ₃ Ceramic
Pb Free	




TOP VIEW



BOTTOM VIEW



Tape and Reel Specifications



"B" Nominal Size		Quantity Per Reel
Inches	millimeters	
7	178	500
13	330	3000

COMPONENT ORIENTATION and DIMENSIONS

Carrier Tape Dimensions	
Ao	5.3 mm
Bo	5.3 mm
Ko	2.0 mm
Pitch	8.0 mm
W	12.0 mm

