

Incremental encoders

Hollow shaft $\varnothing 20$ to $\varnothing 27$ mm

Resolution 200...2048 pulses

ITD 40 A 4 Y79



ITD 40 A 4 Y79 with hollow shaft

Technical data - electrical ratings

Voltage supply	5 VDC ± 5 % 8...30 VDC
Reverse polarity protection	Yes
Consumption w/o load	≤ 100 mA
Resolution (steps/turn)	200...2048
Reference signal	Zero pulse, width 90°
Sensing method	Optical
Output frequency	≤ 120 kHz
Output signals	A, B, N + inverted
Output circuit	TTL linedriver (short-circuit proof) HTL push-pull (short-circuit proof)
Interference immunity	DIN EN 61000-6-2
Emitted interference	DIN EN 55011

Features

- Encoder with hollow shaft $\varnothing 20$ -27 mm
- Resolution max. 2048 ppr
- Optical sensing
- Mounting by torque support
- TTL or HTL output signals
- Cable output radial

Optional

- Cable with connector
- Extended operating temperature range

Technical data - mechanical design

Dimensions (flange)	$\varnothing 80$ mm
Shaft	$\varnothing 20$ mm hollow shaft $\varnothing 22$ mm hollow shaft $\varnothing 25$ mm hollow shaft $\varnothing 27$ mm hollow shaft
Motor shaft tolerance	0.25 mm axial 0.1 mm radial
Mounting kit variant	050
Protection DIN EN 60529	IP 65
Operating speed	≤ 5000 rpm ≤ 3000 rpm IP 65 ($> 70^\circ\text{C}$)
Starting torque	≤ 0.015 Nm
Materials	Housing: aluminium, black, powder-coated Shaft: stainless steel
Operating temperature	$-20 \dots +70^\circ\text{C}$ $-20 \dots +100^\circ\text{C}$
Relative humidity	90 % non-condensing
Resistance	DIN EN 60068-2-6 Vibration 10 g, 55-2000 Hz DIN EN 60068-2-27 Shock 100 g, 6 ms
Connection	Cable 1 m
Weight approx.	600 g

Incremental encoders

Hollow shaft $\varnothing 20$ to $\varnothing 27$ mm

Resolution 200...2048 pulses

ITD 40 A 4 Y79

Part number

ITD 40 A 4 Y79

			KR1			050
--	--	--	-----	--	--	-----

Mounting kit
050 Mounting accessory kit 050

Protection
IP54 IP 54
IP65 IP 65

Hollow shaft
20 Hollow shaft $\varnothing 20$ mm
22 Hollow shaft $\varnothing 22$ mm
25 Hollow shaft $\varnothing 25$ mm
27 Hollow shaft $\varnothing 27$ mm

Operating temperature
S -20...+70 °C
E -20...+100 °C

Connection
KR1 Cable 1 m, radial

Output signals
BI A, A inv, B, B inv
NI A, A inv, B, B inv, 0, 0 inv

Voltage supply / signals
T 5 VDC / TTL level, linedriver
H 8...30 VDC / HTL level, push pull
R 8...30 VDC / TTL level, linedriver

See part number (pulses)

Part number (pulses)

200	500	720	1024	2048
360	512	1000	2000	

Incremental encoders
Hollow shaft $\varnothing 20$ to $\varnothing 27$ mm
Resolution 200...2048 pulses

ITD 40 A 4 Y79
