

## **Economy Welded Steel 2-Post Open Frame Rack RB-2P**

## Series



## **Features**

- Constructed in 12-gauge steel.
- 44U 83.12" Overall Height.
- 19" EIA-310-D compliant 10-32 tapped rails.
- Side ganging and accessory mounting holes.
- Two (2) bonding studs included:
  - One (1) at bottom to accommodate grounding from floor.
  - One (1) at top to accommodate grounding from overhead.
- Finished in smooth black powder paint.
- Rails and Base packaged in cardboard to prevent freight damage.
- Maximum load capacity of 800 lb.
- RoHS EU Directive 2002/95/EC compliant.
- Manufactured by an ISO 9001:2008 certified company, located in North America.

## **Accessories**







- Two Post Mounting Cantilever Shelf
- Two Post Mounting Clamping Shelf
- Two Post Mounting Deep Channel **Battery Shelf**
- <u>Two Post Mounting Deep Channel</u> **Monitor Shelf**
- <u>Hinged Acrylic Door Panel Cover</u>
- Outlet Strips
- Cup Washer
- Small Head 10-32 Thumb Screw
- <u>Lite Duty Caster Set for Open Frame</u> <u>Rack Panels</u> Rack
- Rack Unit Label

- Two Post Mounting Adjustable Shelf
- Two Post Centered Shelf
- Two Post Mounting Keyboard & **Monitor Shelf**
- Two Post Mounting Adjustable Depth DIN Rail
- <u>Cable Management</u>
- 10-32 Black Rack Screw with Nylon Washer
- 10-32 Nickel Rack Screw with Plastic 10-32 Black Rack Screw with Nylon Washer and Pilot Point
  - Grounding

	Overall Dimensions			Mounting Dimensions			Rail
Part No.	Height	Width	Depth	Height	Width	Rack Units	Tapping
RB-2P77	83.13	20.56	15.00	77.00	19.00	44U	10-32 Front Only
RB-2P77B	83.13	20.56	15.00	77.00	19.00	44U	10-32 Front & Back

Data subject to change without notice.

© 2012. Hammond Manufacturing Ltd. All rights reserved.