




- ▼ 100% Avalanche Test
- ▼ Simple Drive Requirement
- ▼ Lower On-resistance
- ▼ RoHS Compliant




BV_{DSS}	250V
$R_{DS(ON)}$	68m Ω
I_D	36A

Description

AP30N30 from APEC provide the designer with the best combination of fast switching , low on-resistance and cost-effectiveness .

The TO-3P package is preferred for commercial & industrial applications with higher power level preclusion than TO-220 device.



Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	250	V
V_{GS}	Gate-Source Voltage	± 30	V
$I_D@T_C=25^\circ C$	Continuous Drain Current, V_{GS} @ 10V	36	A
$I_D@T_C=100^\circ C$	Continuous Drain Current, V_{GS} @ 10V	23	A
I_{DM}	Pulsed Drain Current ¹	144	A
$P_D@T_C=25^\circ C$	Total Power Dissipation	208	W
	Linear Derating Factor	1.7	W/ $^\circ C$
E_{AS}	Single Pulse Avalanche Energy ³	450	mJ
I_{AR}	Avalanche Current	30	A
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ C$
T_J	Operating Junction Temperature Range	-55 to 150	$^\circ C$

Thermal Data

Symbol	Parameter	Value	Units
Rthj-c	Thermal Resistance Junction-case	Max. 0.6	$^\circ C/W$
Rthj-a	Thermal Resistance Junction-ambient	Max. 40	$^\circ C/W$



AP30N30W

Electrical Characteristics @ $T_j=25^\circ\text{C}$ (unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=1mA$	250	-	-	V
$\Delta BV_{DSS}/\Delta T_j$	Breakdown Voltage Temperature Coefficient	Reference to $25^\circ\text{C}, I_D=1mA$	-	0.24	-	$V/^\circ\text{C}$
$R_{DS(ON)}$	Static Drain-Source On-Resistance ²	$V_{GS}=10V, I_D=15A$	-	-	68	$m\Omega$
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	1.5	-	3.5	V
g_{fs}	Forward Transconductance	$V_{DS}=10V, I_D=15A$	-	23	-	S
I_{DSS}	Drain-Source Leakage Current ($T_j=25^\circ\text{C}$)	$V_{DS}=250V, V_{GS}=0V$	-	-	10	μA
	Drain-Source Leakage Current ($T_j=150^\circ\text{C}$)	$V_{DS}=200V, V_{GS}=0V$	-	-	100	μA
I_{GSS}	Gate-Source Leakage	$V_{GS}=\pm 30V$	-	-	± 1	μA
Q_g	Total Gate Charge ²	$I_D=15A$	-	63	100	nC
Q_{gs}	Gate-Source Charge	$V_{DS}=200V$	-	19	-	nC
Q_{gd}	Gate-Drain ("Miller") Charge	$V_{GS}=10V$	-	14	-	nC
$t_{d(on)}$	Turn-on Delay Time ²	$V_{DS}=125V$	-	28	-	ns
t_r	Rise Time	$I_D=15A$	-	36	-	ns
$t_{d(off)}$	Turn-off Delay Time	$R_G=10\Omega, V_{GS}=10V$	-	84	-	ns
t_f	Fall Time	$R_D=8.3\Omega$	-	45	-	ns
C_{iss}	Input Capacitance	$V_{GS}=0V$	-	4290	6900	pF
C_{oss}	Output Capacitance	$V_{DS}=25V$	-	550	-	pF
C_{rss}	Reverse Transfer Capacitance	$f=1.0MHz$	-	6	-	pF
R_g	Gate Resistance	$f=1.0MHz$	-	1.9	3	Ω

Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_{SD}	Forward On Voltage ²	$I_S=36A, V_{GS}=0V$	-	-	1.5	V
t_{rr}	Reverse Recovery Time ²	$I_S=15A, V_{GS}=0V$	-	235	-	ns
Q_{rr}	Reverse Recovery Charge	$dI/dt=100A/\mu s$	-	2.24	-	μC

Notes:

1. Pulse width limited by safe operating area.
2. Pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.
3. Starting $T_j=25^\circ\text{C}$, $V_{DD}=50V$, $L=1mH$, $R_G=25\Omega$, $I_{AS}=30A$.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance v.s. Gate Voltage




Fig 4. Normalized On-Resistance v.s. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode




Fig 6. Gate Threshold Voltage v.s. Junction Temperature




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Transfer Characteristics




Fig 12. Gate Charge Waveform