

RG316DS 50 Ohm Coaxial Cables
SMA / SMA [Straight/Straight]



Electrically Matched:

Each cable pair is electrically matched at 1GHz to within
10pSec. at +25°C

Electrical Data:

PN: CCSMA-MM-RG316DS-24P

Freq. (MHz)	Insertion Loss	VSWR
50	-0.035	1:1.014
500	-0.173	1:1.092
1000	-0.303	1:1.159
2000	-0.468	1:1.358
3000	-0.502	1:1.257
4000	-0.787	1:1.473
5000	-0.822	1:1.288
6000	-1.09	1:1.596
7000	-1.27	1:1.473
8000	-1.42	1:1.579

Features:

Strain Relief: Adhesive shrink tubing over crimp area

Center Conductor: SPC (Silver-plated copper)

Shielding: Double Braid, SPC(2) (Silver-plated copper)

Insulation: PTFE (Polytetrafluoroethylene) dielectric

Jacket: FEP (Fluorinated Ethylene Propylene)

Operating Temperature: -55°C to +85°C

Minimum Bend Radius: 0.6"

SMA / SMA [Straight/Straight]

Part Number	Description	Length
CCSMA-MM-RG316DS-6P	RG316 Double Shielded Cable, SMA Male/Male, Straight/Straight	6"
CCSMA-MM-RG316DS-12P	RG316 Double Shielded Cable, SMA Male/Male, Straight/Straight	12"
CCSMA-MM-RG316DS-24P	RG316 Double Shielded Cable, SMA Male/Male, Straight/Straight	24"
CCSMA-MM-RG316DS-36P	RG316 Double Shielded Cable, SMA Male/Male, Straight/Straight	36"
CCSMA-MM-RG316DS-48P	RG316 Double Shielded Cable, SMA Male/Male, Straight/Straight	48"