




PERFORMANCE SPECIFICATION	MIN	TYP	MAX	UNITS
Lower Frequency:			320	MHz
Upper Frequency:	343			MHz
Tuning Voltage:	1.0		9.0	VDC
Supply Voltage:	12.5	13.5	14.5	VDC
Output Power:	+10.0	+12.0	+14.0	dBm
Supply Current:			40	mA
Harmonic Suppression (2 nd Harmonic)			-10	dBc
Pushing:			3.0	MHz/V
Pulling, all Phases:			5.0	MHz pk-pk
Tuning Sensitivity:		5		MHz/V
Phase Noise @ 10kHz offset:			-107	dBc/Hz
Phase Noise @ 100kHz offset:			-127	dBc/Hz
Load Impedance:		50		Ω
Input Capacitance:			220	pF
Operating Temperature Range:	-40		+85	$^{\circ}\text{C}$
Storage Temperature Range:	-45		+90	$^{\circ}\text{C}$



● Unless otherwise specified, Dimensions are in: $\frac{\text{IN}}{\text{(mm)}}$

Product Control:


Crystek Part Number:	CRBV55CL-0320-0343	Release Date:	30-Jan-12
Revision Level:	A	Responsible:	C. Vales




CRYSTEK
MICROWAVE
 A DIVISION OF CRYSTEK CORPORATION

RedBox VCO
 CRBV55CL-0320-0343

Phase Noise (1 Hz BW, Typical)



Tuning Curve (Typical)



Product Control:

Crystek Part Number:	CRBV55CL-0320-0343	Release Date:	30-Jan-12
Revision Level:	A	Responsible:	C. Vales

Specification is subject to change without notice



12730 COMMONWEALTH DRIVE • FORT MYERS, FLORIDA 33913
 PHONE: 239-561-3311 • 800-237-3061
 FAX: 239-561-1025 • WWW.CRYSTEK.COM