

PART NUMBER: CPE-267

DESCRIPTION: piezo audio transducer


SPECIFICATIONS

| | | |
|----------------------------|--------------------------------------|------------------------------------|
| operating frequency | 2.8 ± 0.5 kHz | |
| rated voltage | 12 V dc | |
| operating voltage range | 6 ~ 14 V dc | |
| current consumption | 35 mA max. | at 12 V dc |
| sound pressure level | 85 dB min. | at 30 cm/12 V dc |
| tone | continuous | at 12 V dc |
| operating temperature | -30 ~ +85° C | |
| storage temperature | -40 ~ +95° C | |
| dimensions | ø25 x H16 mm | |
| weight | 41 g max. | |
| material | ABS UL-94 1/16" HB high heat (black) | |
| terminal | wire type | |
| RoHS | yes | |
| dustproof/waterproof level | IP67 | IEC standard 529 edition 2.0(1989) |

APPEARANCE DRAWING

tolerance: ±0.5


units: mm




PART NUMBER: CPE-267

DESCRIPTION: piezo audio transducer

VOLTAGE: SOUND PRESSURE LEVEL / CURRENT CONSUMPTION CHARACTERISTICS



MEASUREMENT METHOD



S.P.L. Measuring Circuit
Mic: RION S.P.L. meter UC30 or equivalent
S.G.: Hewlett Packard 33120A function generator or equivalent


PART NUMBER: CPE-267

DESCRIPTION: piezo audio transducer

MECHANICAL CHARACTERISTICS

| item | test condition | evaluation standard |
|---------------------------------------|---|--|
| solderability (connector excepted) | Lead terminals are immersed in rosin for 5 seconds and then immersed in solder bath of $270 \pm 5^{\circ}\text{C}$ for 3 ± 0.5 seconds. | 90% min. of the lead terminals will be wet with solder (except the edge of the terminal). |
| lead wire pull strength | The pull force shall be applied to double lead wire: Horizontal 3.0N (0.306 kg) for 30 seconds Vertical 2.0N (0.204 kg) for 30 seconds | No damage or cutting off. |
| vibration | The buzzer shall be measured after applying a vibration amplitude of 1.5 mm with 10 to 55 Hz band of vibration frequency to each of the 3 perpendicular directions for 2 hours. | The value of oscillation frequency/current consumption should be $\pm 10\%$ of the initial measurements. The SPL should be within $\pm 10\text{dB}$ compared with the initial measurement. |
| drop test | The part will be dropped from a height of 75 cm onto a 40 mm thick wooden board 3 times in 3 axes (X, Y, Z) for a total of 9 drops. | |

ENVIRONMENT TEST

| item | test condition | evaluation standard |
|------------------|---|---|
| high temp. test | After being placed in a chamber at $+95^{\circ}\text{C}$ for 240 hours. | The buzzer will be measured after being placed at $+25^{\circ}\text{C}$ for 4 hours. The value of the oscillation frequency/current consumption should be $\pm 10\%$ compared to the initial measurements. The SPL should be within $\pm 10\text{dB}$ compared to the initial measurements. |
| low temp. test | After being placed in a chamber at -40°C for 240 hours. | |
| humidity test | After being placed in a chamber at $+40^{\circ}\text{C}$ and $90 \pm 5\%$ relative humidity for 240 hours. | |
| temp. cycle test | The part shall be subjected to 5 cycles. One cycle will consist of:  | |

PART NUMBER: CPE-267**DESCRIPTION:** piezo audio transducer**RELIABILITY TEST**

| item | test condition | evaluation standard |
|-----------------------|---|--|
| operating (life test) | <p>1. Continuous life test: The part will be subjected to 48 hours of continuous operation at +70°C with rated voltage applied.</p> <p>2. Intermittent life test: A duty cycle of 1 minute on, 1 minute off, a minimum of 5,000 times at room temp (+25 ±2°C) with rated voltage applied.</p> | <p>The buzzer will be measured after being placed at +25°C for 4 hours. The value of the oscillation frequency/current consumption should be ±10% compared to the initial measurements. The SPL should be within ±10dB compared to the initial measurements.</p> |

TEST CONDITIONS

| | | | |
|--------------------------|----------------------------|-----------------------|----------------------------|
| standard test condition | a) temperature: +5 ~ +35°C | b) humidity: 45 - 85% | c) pressure: 860-1060 mbar |
| judgement test condition | a) temperature: +25 ±2°C | b) humidity: 60 - 70% | c) pressure: 860-1060 mbar |

PART NUMBER: CPE-267

DESCRIPTION: piezo audio transducer

PACKAGING

