

# Absolute encoders - parallel

Hollow shaft  $\varnothing 14$  mm

Optical multiturn encoders 12 bit ST / 12 bit MT / 250 cams

## GXN1H



GXN1H with hollow shaft

### Features

- Encoder multiturn / parallel
- Optical sensing
- Resolution: singleturn 12 bit, multiturn 12 bit
- Hollow shaft  $\varnothing 14$  mm
- 250 cams freely programmable
- 16 parallel outputs
- Encoder programming by Windows software
- RS232 encoder programming interface
- Electronic setting to preset

### Technical data - electrical ratings

Voltage supply	10...30 VDC
Reverse polarity protection	Yes
Consumption w/o load	$\leq 50$ mA (24 VDC)
Initializing time (typ.)	50 ms after power on
Interfaces	Parallel (cams), 5 special outputs programmable
Function	Multiturn
Number of cams	250
Steps per turn	$\leq 4096$ / 12 bit
Number of turns	$\leq 4096$ / 12 bit
Absolute accuracy	$\pm 0.03^\circ$
Sensing method	Optical
Code	Binary
Code sequence	CW/CCW coded by connection
Inputs	TxD, RxD (RS232) Control signals UP/DOWN and zero ENABLE
Output circuit	PNP or NPN open collector
Interference immunity	DIN EN 61000-6-2
Emitted interference	DIN EN 61000-6-4
Programming interface	RS232
Programmable parameters	Steps per revolution Number of revolutions 2 presets (limits) Rotation speed monitoring
Diagnostic functions	Code continuity check Signal frequency exceeded
Approval	UL approval / E63076

### Technical data - mechanical design

Dimensions (flange)	$\varnothing 75$ mm
Shaft	$\varnothing 14$ mm hollow shaft
Protection DIN EN 60529	IP 54
Operating speed	$\leq 6000$ rpm (mechanical) $\leq 6000$ rpm (electric)
Starting torque	$\leq 0.05$ Nm (IP 54)
Rotor moment of inertia	20 gcm <sup>2</sup>
Materials	Housing: steel Flange: aluminium
Operating temperature	-25...+70 °C
Relative humidity	95 % non-condensing
Resistance	DIN EN 60068-2-6 Vibration 10 g, 16-2000 Hz DIN EN 60068-2-27 Shock 200 g, 6 ms
Weight approx.	700 g
Connection	Cable 1 m, connector D-SUB, 37-pin

# Absolute encoders - parallel

Hollow shaft  $\varnothing$ 14 mm

Optical multiturn encoders 12 bit ST / 12 bit MT / 250 cams

**GXN1H**

## Part number

GXN1H. 

2		41	01
---	--	----	----

### Connection

41 Cable 1 m, radial, connector D-SUB, 37-pin

### Voltage supply / signals

10 10...30 VDC / open collector NPN

20 10...30 VDC / open collector PNP

Hollow shaft

2 Hollow shaft  $\varnothing$ 14 mm clamping ring

## Accessories

### Connectors and cables

Z 140.001 Female connector D-SUB, 37-pin

### Mounting accessories

Z 119.037 Rubber buffer element 18.5 mm long, as torque support

Z 119.039 Set of adjusting angles as torque support

Z 119.040 Shoulder screw M5 as torque support

Z 119.041 Torque support by rubber buffer element for encoders with 15 mm pin

Z 119.043 Spring coupling for GX and G1

### Programming accessories

Z 139.006 Programming cable for parallel hollow shaft encoders, CD with ProGeber software and manual

Z 150.008 CD with software ProGeber & manual

# Absolute encoders - parallel

Hollow shaft  $\varnothing 14$  mm

Optical multiturn encoders 12 bit ST / 12 bit MT / 250 cams

## GXN1H

Terminal significance	
UB	Encoder voltage supply.
GND	Encoder ground connection relating to UB.
Outputs D0-D16	16 programmable cams outputs. For PNP it is recommended to utilize pull-down resistors, for NPN pull-up resistors of 4.7 k $\Omega$ .
Outputs D19 - D23	Special outputs. These outputs can be assigned to special functions.
Zero setting	Input for setting a zero point anywhere within the programmed encoder resolution. The zero setting operation is triggered by a High impulse and has to be in line with the selected direction of rotation (UP/DOWN). Connect to GND after setting operation for maximum interference immunity. Impulse duration $\geq 100$ ms
UP/DOWN	UP/DOWN counting direction input. This input is standard on High. UP/DOWN means ascending output data with clockwise shaft rotation when looking at flange. UP/DOWN-Low means ascending values with counterclockwise shaft rotation when looking at flange.
ENABLE	Input for activating the output drivers that are triggered by input level Low. Upon being on High (or less potential) the output drivers switch to high-impedance (Tristate).
RxD	Encoder receiver input for RS232 programming interface.
TxD	Encoder transmitter output for RS232 programming interface.

Terminal assignment		
Connector	Core colour	Assignment
Pin 1	white	Output D0
Pin 2	brown	Output D1
Pin 3	green	Output D2
Pin 4	yellow	Output D3
Pin 5	grey	Output D4
Pin 6	pink	Output D5
Pin 7	black	Output D6
Pin 8	violet	Output D7
Pin 9	grey/pink	Output D8
Pin 10	red/blue	Output D9
Pin 11	white/green	Output D10
Pin 12	brown/green	Output D11
Pin 13	white/yellow	Output D12
Pin 14	yellow/brown	Output D13
Pin 15	white/grey	Output D14
Pin 16	grey/brown	Output D15
Pin 17	white/pink	–
Pin 18	pink/brown	–
Pin 19	white/black	–
Pin 20	brown/black	Output D19
Pin 21	grey/green	Output D20
Pin 22	yellow/grey	Output D21
Pin 23	pink/green	Output D22
Pin 24	yellow/pink	Output D23
Pin 25	–	–
Pin 26	–	–
Pin 27	yellow/blue	Zero setting
Pin 28	brown/blue	ENABLE
Pin 29	–	–
Pin 30	green/blue	UP/DOWN
Pin 31	–	–
Pin 32	–	–
Pin 33	–	–
Pin 34	white/blue	TxD
Pin 35	white/red	RxD
Pin 36	red	UB
Pin 37	blue	GND

# Absolute encoders - parallel

Hollow shaft  $\varnothing 14$  mm

Optical multiturn encoders 12 bit ST / 12 bit MT / 250 cams

**GXN1H**

## Terminal assignment programming cable

Encoder function	Connector D-SUB, 37-pins	PC connector D-SUB, 9-pins
UB	Pin 36	–
RxD	Pin 35	Pin 3
GND	Pin 37	Pin 5
TxD	Pin 34	Pin 2
		Jumper 4-6 and Jumper 7-8

Connect encoder to supply voltage using the supplementary connections (UB/red and GND/blue).

## Trigger level

Steuereingänge	Eingangsschaltung
Eingangspegel High	>0,7 UB
Eingangspegel Low	<0,3 UB
Eingangswiderstand	10 k $\Omega$
Parallelausgänge	Ausgangsschaltung
	Open Collector kurzschlussfest
Ausgangspegel High (PNP)	>UB -4,5 V (I = -15 mA)
Ausgangspegel Low (NPN)	<3,5 V (I = 15 mA)
Belastung High (PNP)	<-20 mA
Belastung Low (NPN)	<20 mA
Tristate	<200 $\mu$ A

## Dimensions

