

Absolute encoders - bus interfaces

Hollow shaft $\varnothing 14$ mm

Optical multiturn encoders 13 bit ST / 12 bit MT, Interbus

GXP6H



GXP6H with hollow shaft

Technical data - electrical ratings

Voltage supply	10...30 VDC
Reverse polarity protection	Yes
Consumption w/o load	≤ 60 mA (24 VDC)
Initializing time (typ.)	50 ms after power on
Interface	Interbus
Function	Multiturn
Transmission rate	500 kBaud
Profile conformity	Encoder profile 71
Steps per turn	≤ 8192 / 13 bit
Number of turns	≤ 4096 / 12 bit
Absolute accuracy	$\pm 0.025^\circ$
Sensing method	Optical
Code	Gray or binary
Code sequence	CW default, programmable
Output circuit	RS485
Interference immunity	DIN EN 61000-6-2
Emitted interference	DIN EN 61000-6-4
Programmable parameters	Total resolution Rotating direction and code Preset and offset Zero point setting
Approval	UL approval / E63076

Features

- Encoder multiturn / Interbus
- Optical sensing
- Resolution: singleturn 13 bit, multiturn 12 bit
- Hollow shaft $\varnothing 14$ mm
- Interbus encoder profile 71
- ENCOM profile K3
- High reliability by self-diagnostics
- Zero point, offset and turning direction programmable
- Cost-efficient mounting

Optional

- Transmission rate 2 MBaud

Technical data - mechanical design

Dimensions (flange)	$\varnothing 75$ mm
Shaft	$\varnothing 14$ mm hollow shaft
Protection DIN EN 60529	IP 54
Operating speed	≤ 6000 rpm (mechanical) ≤ 6000 rpm (electric)
Starting torque	≤ 0.05 Nm (IP 54)
Rotor moment of inertia	20 gcm ²
Materials	Housing: steel Flange: aluminium
Operating temperature	-25...+85 °C -40...+85 °C (optional)
Relative humidity	95 % non-condensing
Resistance	DIN EN 60068-2-6 Vibration 10 g, 16-2000 Hz DIN EN 60068-2-27 Shock 200 g, 6 ms
Weight approx.	430 g
Connection	Connector M23, 2 x 9-pin

Absolute encoders - bus interfaces

Hollow shaft $\varnothing 14$ mm

Optical multiturn encoders 13 bit ST / 12 bit MT, Interbus

GXP6H

Part number

GXP6H. **2** | **10** | **A1** | **01**

2	10	A1	01	Interface Interbus K3
		A1		Connection Connector M23, 2 x 9-pin, radial
	10			Voltage supply 10...30 VDC / galvanically isolated
2				Hollow shaft Hollow shaft $\varnothing 14$ mm with pin 15 mm clamping ring on housing

Accessories

Connectors and cables

Z 153.B01	Female connector M23, 9-pin, less cable
Z 153.S01	Cable connector M23, 9-pin, less cable

Mounting accessories

Z 119.037	Rubber buffer element 18.5 mm long, as torque support
Z 119.039	Set of adjusting angles as torque support
Z 119.040	Shoulder screw M5 as torque support
Z 119.041	Torque support by rubber buffer element for encoders with 15 mm pin
Z 119.043	Spring coupling for GX and G1

Interbus features

Bus protocol	Interbus
Device profile	Encoder profile 71
Coupling	
IB user type	2 wire remote bus
IB bus width	4 byte
PCP length	No parameter channel
ID-Code	55
Interface	
Type A1	2 wire remote bus (galvanically isolated)
Type W1	2 wire remote bus
Programmable parameters	<ul style="list-style-type: none"> – Resolution steps and revolutions – Rotating direction and code – Preset – Zero point shift – Offset – Measuring range – Encoder reset

Absolute encoders - bus interfaces


Hollow shaft $\varnothing 14$ mm

Optical multiturn encoders 13 bit ST / 12 bit MT, Interbus


GXP6H

Terminal significance	
D01, $\overline{D01}$ D11, $\overline{D11}$	Arriving remote bus (galvanically isolated).
GND I	Ground connection for arriving remote bus (galvanically isolated).
UB	Connections for voltage supply UB carried by the bus, current load between the arriving and departing connections max. 700 mA.
GND B	
D02, $\overline{D02}$ D12, $\overline{D12}$	Outgoing remote bus.
GND	Ground connection for ongoing remote bus.
PE	Shield connected to encoder housing.
\overline{RBST}	Input for recognition of other bus users. Connection open: final user / termination Connected to GND: user X.

Terminal assignment			
Male connector	Assignment	Female connector	Assignment
Pin 1	D01	Pin 1	D02
Pin 2	$\overline{D01}$	Pin 2	$\overline{D02}$
Pin 3	D11	Pin 3	D12
Pin 4	$\overline{D11}$	Pin 4	$\overline{D12}$
Pin 5	GND I	Pin 5	GND
Pin 6	PE	Pin 6	PE
Pin 7	UB	Pin 7	UB
Pin 8	GND B	Pin 8	GND B
Pin 9	–	Pin 9	\overline{RBST}



Arriving interface
(male connector)



Departing interface
(female connector)

Absolute encoders - bus interfaces

Hollow shaft $\varnothing 14$ mm

Optical multiturn encoders 13 bit ST / 12 bit MT, Interbus

GXP6H

Dimensions

