



### Fittings with swivel flange

#### • HG-SFL Straight Swivel Flange, IP66

Straight swivel flange.

#### Features and Benefits

- One piece, fast fit
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus

Technical Table

Article-No.	Type	Nominal Ø	Pack Cont.
166-21200	<b>HG16-SFL</b>	16	10
166-21201	<b>HG21-SFL</b>	21	10
166-21202	<b>HG28-SFL</b>	28	10
166-21203	<b>HG34-SFL</b>	34	10
166-21204	<b>HG42-SFL</b>	42	2

All dimensions in mm. Subject to technical changes.

Colour grey available on request.



HelaGuard HG-SFL Straight Swivel Flange, IP66.

Material Data

Material	<b>Polyamide 6.6 (PA66)</b>
Colour	<b>Black (BK)</b>
Operating Temperature	<b>-50 °C to +135 °C</b>
Flammability	<b>UL94 V2</b>



#### • HGL-SFL Straight Swivel Flange, IP68

Straight swivel flange with conduit seal and washer.

Fulfills IP66, IP67, IP68 and IP69k.

#### Features and Benefits

- One piece, fast fit
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus

Technical Table

Article-No.	Type	Nominal Ø	Pack Cont.
166-21800	<b>HGL16-SFL</b>	16	10
166-21801	<b>HGL21-SFL</b>	21	10
166-21802	<b>HGL28-SFL</b>	28	10
166-21803	<b>HGL34-SFL</b>	34	10
166-21804	<b>HGL42-SFL</b>	42	2

All dimensions in mm. Subject to technical changes.

Colour grey available on request.



HelaGuard HGL-SFL Straight Swivel Flange with conduit seal, IP68.



Please note! Not all products listed on this page may have this approval.  
For product specific approvals please refer to the Appendix.