



Fittings with swivel flange

• HG-90FL 90° Elbow Swivel Flange, IP66

90° elbow swivel flange.

Features and Benefits

- One piece, fast fit
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus

Technical Table

Article-No.	Type	Nominal Ø	Pack Cont.
166-22400	HG16-90FL	16	10
166-22401	HG21-90FL	21	10
166-22402	HG28-90FL	28	10
166-22403	HG34-90FL	34	10
166-22404	HG42-90FL	42	2

All dimensions in mm. Subject to technical changes.

Colour grey available on request.



HelaGuard HG-90FL 90° Elbow Swivel Flange, IP66.

Material Data

Material	Polyamide 6.6 (PA66)
Colour	Black (BK)
Operating Temperature	-50 °C to +135 °C
Flammability	UL94 V2



• HGL-90FL 90° Elbow Swivel Flange, IP68

90° elbow swivel flange with conduit seal and washer.

Fulfils IP66, IP67, IP68 and IP69k.

Features and Benefits

- One piece, fast fit
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus

Technical Table

Article-No.	Type	Nominal Ø	Pack Cont.
166-23000	HGL16-90FL	16	10
166-23001	HGL21-90FL	21	10
166-23002	HGL28-90FL	28	10
166-23003	HGL34-90FL	34	10
166-23004	HGL42-90FL	42	2

All dimensions in mm. Subject to technical changes.

Colour grey available on request.



HelaGuard HGL-90FL 90° Elbow Swivel Flange, IP68.



Please note! Not all products listed on this page may have this approval.
For product specific approvals please refer to the Appendix.